

Notice 007-2021

Health Insurance Act (chapter A-29)

Tariff for insured devices which compensate for a motor deficiency and related services

- Amendments

The RÉGIE DE L'ASSURANCE MALADIE DU QUÉBEC

HEREBY GIVES NOTICE that it has made, by resolution CA-551-21-30 of its board of directors, dated 13 October 2021, the Regulation to amend the Tariff for insured devices which compensate for a motor deficiency and related services, the text of which appears below.

Québec, 14 October 2021


ORIGINAL SIGNED by

Sonia Marceau Secretary General of the Régie de l'assurance maladie du Québec

REGULATION TO AMEND THE TARIFF FOR INSURED DEVICES WHICH COMPENSATE FOR A MOTOR DEFIENCY AND RELATED SERVICES

Health Insurance Act (chapter A-29, s. 3, 5th par. and s. 72.1, 1st par.)

- **1.** SCHEDULE I to the Tariff for insured devices which compensate for a motor deficiency and related services (chapter A-29, r. 9) is amended by replacing the text of PART I of TITLE TWO with the one appearing in Schedule 1 attached hereto.
- **2.** This regulation comes into force on 1 November 2021.



TITLE TWO: LOCOMOTOR AND POSTURE ASSISTS (FURNISHED SOLELY BY AN INSTITUTION)

PART I: LOCOMOTOR ASSISTS DIVISION I: MANUAL WHEELCHAIRS SUBDIVISION 1: MASS GROUP 1

			PRICE (including all the basic components)	
7210000	MANUAL WHEELCHAIRS CATEGORY FMA-GM 1-A-P2 (RIGID FRAME)		1,600.00	
	MOTION COMPOSITES INC.			
	"APEX P" DEVICE			
	Technical specifications of the device Maximum weight capacity: 50 kg (110 lb.) Device weight: 11.7 kg (25.8 lb.) Overall width: 63 cm (24¾ in.) Front seat-to-floor height: 35.6 cm to 53.3 cm (14 in. to 2 Rear seat-to-floor height: 35.6 cm to 53.3 cm (14 in. to 19			
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7210001	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.) or 38.1 cm (15 in.); depths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.) or 38.1 cm (15 in.)	N. C.	85.72	1
7210002	Seat, rigid base	200.00	285.72	12
7210003	Seat cushion, multilayer, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	30.00	12
7210005	Back support, flexible, non tension adjustable; heights from 22.9 cm (9 in.) to 53.3 cm (21 in.)	N. C.	52.50	1
7210006	Back support, flexible, tension adjustable	72.00	124.50	1
7210026	Push handle, with hand grip	49.00	49.00	12
7210027	Push bar, raised, removable	36.00	36.00	12
7210007 7210008	Postural support pelvic belt T-shaped arm support, short, removable; height- adjustable, from 15.2 cm to 35.6 cm (6 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	20.00 N. C.	20.00 41.74	12 1
7210009	T-shaped arm support, long, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210011	I-shaped arm support, flip-up; with locking mechanism	75.00	116.74	1
7210010	L-shaped arm support, swing-away from 20.3 cm to 27,9 cm (8 in. to 11 in.)	N. C.	41.74	1

7210019	Clothing guard for I-shaped or L-shaped arm support	100.00	100.00	12
7210013	Arm support pad, short, straight	N. C.	6.61	1
7210014	Arm support pad, long, straight	N. C.	6.61	1
7210015	Arm support pad, tubular	N. C.	6.61	1
7210016	Arm support pad, contoured	25.00	31.61	1
7210010	Arm support pad, gel	40.00	46.61	1
7210017	Foot support, fixed	N. C.	49.35	12
	**			
7210024	Foot support, full width, flip-up, angle and depth adjustable	120.00	169.35	12
7210020	Calf support strap, single	60.00	60.00	12
7210021	Calf support strap, double	60.00	60.00	12
7210022	Heel loop, adjustable	60.00	60.00	12
	FRAME			
7210028	Securement points for strap-type tiedowns for transport	N. C.	133.55	12
7210029	Anti-tip device	99.00	99.00	12
7210029	Reflective devices	20.00	20.00	12
7210030	Cane holder	40.00	40.00	12
/210031	Calle Holder	40.00	40.00	12
	DRIVE SYSTEM			
7210032	Handrim, smooth	N. C.	19.89	12
7210033	Handrim, plasticized	100.00	119.89	12
7210034	Handrim, anti-slip	245.00	264.89	12
7210035	Handrim, ergonomic	245.00	264.89	12
7210036	Handrim, with oblique projection	245.00	264.89	12
7210037	Parking brake, push-type activation	N. C.	23.02	12
7210038	Parking brake, pull-type activation	N. C.	23.02	12
7210039	Parking brake, scissor-type mechanism	N. C.	23.02	12
7210040	Anti-rollback brake	50.00	50.00	12
7210041	Brake lever extension, plug-in	5.00	5.00	12
7210042	Fork, adjustable height	N. C.	35.47	12
7210012	Tork, adjustable height	14. 6.	33.17	12
	WHEELS AND TIRES			
7210047	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	33.70	12
	61 cm (24 in.)			
7210048	Drive wheel, with puncture proof tire; 55.9 cm (22 in.) or	100.00	133.70	12
	61 cm (24 in.)			
7210049	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	10.08	1
	cm (22 in.) or 61 cm (24 in.)			
7210050	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	10.08	1
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7210051	Drive wheel time high angegone in an take 50 8 cm (20	50.00	60.00	1
7210051	Drive wheel tire, high pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	50.00	60.08	1
	III.), 33.9 CIII (22 III.) 01 01 CIII (24 III.)			
7210043	Caster wheel, with solid tire; 7.6 cm (3 in.), 10.2 cm (4	N. C.	15.86	12
	in.); 12.7 cm (5 in.) or 15.2 cm (6 in.)			
7210044	Caster wheel, semi-pneumatic tire; 10.2 cm (4 in.); 12.7	N. C.	15.86	12
	cm (5 in.) or 15.2 cm (6 in.)			
7210045	Caster wheel, with standard pressure inner tube tire; 15,2	N. C.	15.86	12
	cm (6 in.)			
7210046	Quick release drive wheel axle	N. C.	30.00	12
7210040	Adapter for amputee axle position	N. C.	N. C.	12
7210052	Spoke guards	49.00	49.00	12
7210053	Drive wheel camber; 0°, 2°, 4°, 6° or 8°	N. C.	52.90	12
1210034	Drive wheel camber, 0,2,4,0 or 6	1 v. C.	54.70	12

7210245 MANUAL WHEELCHAIRS 1,1	50.00
--------------------------------	-------

CATEGORY FMA-GM 1-B-P2 (FOLDING FRAME)

SUNRISE MEDICAL CANADA INC.

"QUICKIE 2 E" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 50 kg (110 lb.)

Device weight: 15.2 kg (33.5 lb.)

Overall width: 49 cm to 78.7 cm (19¼ in. à 31 in.)

Front seat-to-floor height: 34.3 cm to 55.9 cm (13½ in. to 22 in.) Rear seat-to-floor height: 33 cm to 55.9 cm (13 in. to 22 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7210246	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.) or 40.6 cm (16 in.); depths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12	N. C.	35.00	1
	in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.) or			
7210317	40.6 cm (16 in.) Seat depth adjustement	N. C.	N. C.	12
7210247	Seat cushion, multilayer flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	50.00	12
7210249	Back support, flexible, non tension adjustable	N. C.	35.00	1
7210250	Back support, flexible, tension adjustable	40.00	75.00	1
7210251	Back support upright, straight, height and angle ajustable	N. C.	65.00	12
7210252	Back support upright, angled, height and angle ajustable	N. C.	65.00	12
7210285	Push handle, fixed, with hand grip	N. C.	15.00	12
7210286	Push handle, raised, removable	5.00	20.00	12
7210253	Pelvic positioning belt	N. C.	25.00	12
7210254	T-shaped arm support, short, removable; height-adjustable, 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210255	T-shaped arm support, long, removable; height-adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210256	U-shaped arm support, short, flip-up and removable; height-adjustable, from 21.6 cm to 34.3 cm (8½ in. of 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1

7210257	U-shaped arm support, long, flip-up and removable; height adjustable, from 21.6 cm to 34.3 cm (8½ in. of 13½ in.) by	N. C.	114.00	1
	maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard			
7210259	I-shaped arm support, flip-up; height-adjustable, from 15.8 cm to 37.6 cm (6 ¹ / ₄ in to 14 ³ / ₄ in) by maximum	N. C.	114.00	1
	increments of 2.5 cm (1 in.), with locking mechanism			
7210258	L-shaped arm support, swing-away; from 22.9 cm to 33 cm (9 in. to 13 in.)	N. C.	114.00	1
7210267	Clothing guard for L-shaped arm support	20.00	20.00	12
7210261	Arm support pad, short, straight	N. C.	6.00	1
7210262	Arm support pad, long, straight	N. C.	6.00	1
7210263	Arm support pad, tubular	N. C.	6.00	1
7210264	Arm support pad, contoured	9.00	15.00	1
7210265	Arm support pad, gel	14.00	20.00	1
7210268	Parallel lower leg support, swing-away inward or outward;	N. C.	55.00	12
	70°, 80° or 90°; with locking mechanism; adjustable			
	length from 8.9 cm to 24.2 cm ($3\frac{1}{2}$ in. to $9\frac{1}{2}$ in.) or from			
	22.9 cm to 50.8 cm (9 in. to 20 in.)			
7210270	Lower leg support, compensating elevating	55.00	110.00	12
7210275	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7210276	Foot support, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7210277	Foot support, flip-up, angle and depth adjustable, standard length	N. C.	35.00	12
7210278	Foot support, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7210279	Foot support, flip-up, full width	72.00	107.00	12
7210273	Padded calf support, angle, height and depth adjustable,	25.00	25.00	12
	including flat pad			
7210271	Calf support strap, single	15.00	15.00	12
7210272	Calf support strap, double	18.00	18.00	12
7210274	Heel loop, adjustable	1.00	1.00	12
7210282	Back support tension bar	45.00	45.00	12
7210283	Securement for head support for back support tension bar	40.00	40.00	12
7210281	Head support, height and depth adjustable	55.00	55.00	12
7210280	Contoured cushion for head support, all sizes	35.00	35.00	12
7010000	FRAME	N. C	100.00	10
7210288	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
7210289	Anti-tip device	N. C.	18.00	12
7210290	Reflective devices	5.00	5.00	12
7210284	Front impact guard	10.00	10.00	12
7210291	Cane holder	28.00	28.00	12
7210318	Growth kit	N. C.	N. C.	12
	DRIVE SYSTEM			
7210293	Handrim, smooth	N. C.	40.00	12
7210294	Handrim, plasticized	N. C.	40.00	12
7210295	Handrim, anti-slip	35.00	75.00	12

7210296	Handrim, ergonomic	70.00	110.00	12
7210297	Handrim, with vertical projection	40.00	80.00	12
7210292	Unilateral manuel propulsion mechanism	305.00	345.00	12
7210299	Parking brake, push-type activation	N. C.	25.00	12
7210300	Parking brake, pull-type activation	N. C.	25.00	12
7210298	Parking brake, unilateral activation	125.00	150.00	12
7210301	Anti-rollback brake	36.00	36.00	12
7210302	Brake lever extension, plug-in	5.00	5.00	12
7210303	Fork, adjustable height	N. C.	15.00	12
	WHEELS AND TIRES			
7210309	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	65.00	12
7210310	Drive wheel, with puncture proof tire; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	15.00	80.00	12
7210311	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	20.00	1
7210312	Drive wheel tire, standard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	20.00	1
7210313	Drive wheel tire, high pressure inner tube; 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	20.00	1
7210305	Caster wheel, with semi-pneumatic tire; 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)	N. C.	15.00	12
7210306	Caster wheel, with standard pressure inner tube tire; 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)	N. C.	15.00	12
7210307	Drive wheel axle, fixed	N. C.	10.00	12
7210308	Quick release drive wheel axle	N. C.	10.00	12
7210314	Adaptor for amputee position	25.00	25.00	12
7210315	Spoke guards	20.00	20.00	12
7210316	Drive wheel camber; 0° or 2°	N. C.	2.00	12

PRICE
(including all
the basic
components)

1,600.00

CATEGORY FMA-GM 2-A-P2 (RIGID FRAME)

SUNRISE MEDICAL CANADA INC.

"QUICKIE NITRUM" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Device weight: 13.2 kg (29 lb.)

Overall width: 48.3 cm to 78.7 cm (19 in. to 31 in.)

Front seat-to-floor height: 40.6 cm to 53.3 cm (16 in. to 20 in.) Rear seat-to-floor height: 33 cm to 50.8 cm (13 in. to 20 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7210056	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	35.00	1
7210057	Seat, rigid base	115.00	150.00	12
7210058	Seat cushion, multilayer, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	50.00	12
7210060	Back support, flexible, non tension adjustable; heights from 20.3 cm (8 in.) to 53.3 cm (21 in.)	N. C.	35.00	1
7210061	Back support, flexible, tension adjustable	40.00	75.00	1
7210078	Push handle with hand grip	15.00	15.00	12
7210062	Postural support pelvic belt	25.00	25.00	12
7210063	T-shaped arm support, short, removable; height-adjustable, from 16.5 cm to 34.3 cm (6½ in. to 13 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210064	T-shaped arm support, long, removable; height-adjustable, from 16.5 cm to 34.3 cm (6½ in. to 13 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210065	L-shaped arm support, swing-away from 22.9 cm to 35.6 cm (9 in. to 14 in.)	N. C.	114.00	1
7210072	Clothing guard for L-shaped arm support	20.00	20.00	12

7210066	Arm support pad, short, straight	N. C.	6.00	1
7210067	Arm support pad, long, straight	N. C.	6.00	1
7210068	Arm support pad, tubular	N. C.	6.00	1
7210069	Arm support pad, contoured	9.00	15.00	1
7210070	Arm support pad, gel	14.00	20.00	1
7210076	Foot support, fixed	N. C.	65.00	12
7210077	Foot support, full width, flip-up, angle and depth	N. C.	65.00	12
	adjustable			
7210073	Calf support strap, single	15.00	15.00	12
7210074	Calf support strap, double	18.00	18.00	12
7210075	Heel loop, adjustable	1.00	1.00	12
	17 3			
	FRAME			
7210079	Securement points for strap-type tiedowns for transport	N. C.	185.00	12
7210080	Anti-tip device	18.00	18.00	12
7210081	Reflective devices	5.00	5.00	12
7210082	Cane holder	28.00	28.00	12
	DRIVE SYSTEM			
7210083	Handrim, smooth	N. C.	40.00	12
7210084	Handrim, plasticized	N. C.	40.00	12
7210085	Handrim, anti-slip	35.00	75.00	12
7210086	Handrim, ergonomic	70.00	110.00	12
7210087	Handrim, with vertical or oblique projection	40.00	80.00	12
7210088	Parking brake, push-type activation	N. C.	25.00	12
7210089	Parking brake, pull-type activation	N. C.	25.00	12
7210090	Parking brake, scissor-type mechanism	10.00	35.00	12
7210091	Anti-rollback brake	36.00	36.00	12
7210092	Brake lever extension plug-in	5.00	5.00	12
7210093	Fork, ajustable height	N. C.	35.00	12
	WHEELS AND TIRES			
7210098	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.), 61	N. C.	65.00	12
	cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)			
7210099	Drive wheel, with puncture proof tire; 50.8 cm (20 in.),	15.00	80.00	12
	55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.)			
			20.00	
7210100	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	20.00	1
	cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26			
7010101	in.)	N. 6	20.00	
7210101	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	20.00	1
	(20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.)			
7010100	or 66 cm (26 in.)		20.00	
7210102	Drive wheel tire, high pressure inner tube; 55.9 cm (22	N. C.	20.00	1
	in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)			
7210005		NG	15.00	10
7210095	Caster wheel, with semi-pneumatic tire; 7.6 cm (3 in.),	N. C.	15.00	12
7210006	10.2 cm (4 in.), 12.7 cm (5 in.) or 15,2 cm (6 in.)	N. C	15.00	10
7210096	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	15.00	12
	cm (6 in.)			
7210097	Quick release drive wheel axle	N. C.	10.00	12
7210103	Adaptor for amputee position	50.00	50.00	12
7210104	Spoke guards	20.00	20.00	12
7210105	Drive wheel camber; 0°, 3° or 6°	N. C.	20.00	12

2,495.00

CATEGORY FMA-GM 2-A-P2 (FOLDING FRAME)

MOTION COMPOSITES INC.

"HELIO C2" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120.2 kg (265 lb.)

Device weight: 12.5 kg (26.5 lb.) **Overall width:** 63.5 cm (25.2 in.)

Front seat-to-floor height: 33 cm to 54.6 cm (13 in. to $21\frac{1}{2}$ in.) Rear seat-to-floor height: 31.8 cm to 51.4 cm ($12\frac{1}{2}$ in. to $21\frac{1}{4}$ in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210320	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro,	N. C.	20.35	1
	2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)			
7210321	Seat, rigid base	200.00	220.35	12
7210322	Seat cushion, multilayer foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	30.00	12
7210324	Back support, flexible, non tension adjustable	N. C.	37.90	1
210325	Back support, flexible, tension adjustable	20.00	57.90	1
210326	Back support upright, straight, height and angle ajustable	N. C.	94.65	12
210327	Back support upright, angled, height and angle ajustable	N. C.	94.65	12
210358	Push handle, fixed, with hand grip	N. C.	49.00	12
210328	Postural support pelvic belt	N. C.	20.00	12
7210329	T-shaped arm support, short, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 10 in.), from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1

7210330	T-shaped arm support, long, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 10 in.), from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210331	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210332	U-shaped arm support, long, flip-up and removable; height adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210333	L-shaped arm support, swing-away	N. C.	41.74	1
7210334	Arm support pad, short, straight	N. C.	6.61	1
7210335	Arm support pad, long, straight	N. C.	6.61	1
7210336	Arm support pad, tubular	N. C.	6.61	1
7210337	Arm support pad, contoured	25.00	31.60	1
7210338	Arm support pad, gel	40.00	46.61	1
7210340	Clothing guard for L-shaped arm support	100.00	100.00	12
7210341	Parallel lower leg support, swing-away outward; 60°, 70° or 80°; with locking mechanism; adjustable length from 34.3 cm to 52.1 cm (13½ in. to 20½ in.), or 90° (front mount) with locking mechanism; adjustable length from 19.1 cm to 36.9 cm (7½ in. to 14½ in.)	N. C.	36.87	12
7210342	Parallel lower leg support, swing-away inward; 60°, 70° or 80°; with locking mechanism; adjustable length from 34.3 cm to 52.1 cm (13½ in. to 20½ in.), or 90° (front mount) with locking mechanism; adjustable length from 19.1 cm to 36.9 cm (7½ in. to 14½ in.)	N. C.	36.87	12
7210343	Lower leg support, compensating elevating	130.00	166.87	12
7210348		N. C.	4.73	12
	Foot support, flip-up, not angle adjustable, standard lenght			
7210349	Foot support, flip-up, not angle adjustable, extra long	N. C.	4.73	12
7210350	Foot support, flip-up, angle and depth adjustable, standard length	25.00	29.73	12
7210351	Foot support, flip-up, angle and depth adjustable, extra long	25.00	29.73	12
7210352	Foot support, flip-up, full width	120.00	124.73	12
7210346	Padded calf support, angle, height and depth adjustable, including flat pad	85.00	85.00	12
7210344	Calf support strap, single	60.00	60.00	12
7210345	Calf support strap, double	60.00	60.00	12
7210347	Heel loop, adjustable	5.00	5.00	12
7210355	Back support tension bar	30.00	30.00	12
7210356	Securement for head support for back support tension bar	150.00	150.00	12
7210354	Head support, height and depth adjustable	90.00	90.00	12

7210353	Contoured cushion for head support, all sizes	85.00	85.00	12
	FRAME			
7210359	Securement points for strap-type tiedowns for transport	N. C.	188.15	12
7210360	Anti-tip device	N. C.	16.93	12
7210361	Reflective devices	20.00	20.00	12
7210357	Front impact guard	35.00	35.00	12
7210362	Cane holder	60.00	60.00	12
	DRIVE SYSTEM			
7210364	Handrim, smooth	N. C.	19.89	12
7210365	Handrim, plasticized	100.00	119.89	12
7210366	Handrim, anti-slip	245.00	264.89	12
7210367	Handrim, ergonomic	245.00	264.89	12
7210368	Handrim, with oblique projection	245.00	264.89	12
7210363	Unilateral manuel propulsion mechanism	950.00	969.89	12
7210370	Parking brake, push-type activation	N. C.	23.02	12
7210371	Parking brake, pull-type activation	N. C.	23.02	12
7210369	Parking brake, unilateral activation	295.00	318.02	12
7210372	Anti-rollback brake	50.00	50.00	12
7210373	Brake lever extension, plug-in	5.00	5.00	12
7210374	Fork, adjustable height	N. C.	5.36	12
	WHEELS AND TIRES			
7210380	Drive wheel, spoked	N. C.	33.70	12
7210381	Drive wheel, with puncture proof tire	100.00	133.70	12
7210382	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	10.08	1
	cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26			
	in.)			
7210383	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	10.08	1
	(20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.)			
	or 66 cm (26 in.)			
7210384	Drive wheel tire, high pressure inner tube; 50.8 cm (20	50.00	60.08	1
	in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or			
	66 cm (26 in.)			
7210375	Caster wheel, with solid tire; from 7.6 cm to 20.3 cm (3 in.	N. C.	15.86	12
	to 8 in.)			
7210376	Caster wheel, with pneumatic tire; from 10.2 cm to 15.2	N. C.	15.86	12
	cm (4 in. to 6 in.)			
7210377	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	15.86	12
	cm (6 in.) or 20.3 cm (8 in.)			
7210378	Drive wheel axle, fixed	N. C.	5.00	12
7210379	Quick release drive wheel axle	25.00	30.00	12
7210385	Adaptor for amputee position	90.00	90.00	12
7210386	Spoke guards	49.00	49.00	12
7210387	Drive wheel camber; 0° , 3° or 6°	N. C.	169.40	12
			PRICE	
			1 11	

1,400.00

(including all the basic

CATEGORY FMA-GM 2-B-P2 (RIGID FRAME)

SUNRISE MEDICAL CANADA INC.

"QUICKIE 5R" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Device weight: 14.7 kg (32.5 lb.)

Overall width: 48.3 cm to 78.7 (19 in. to 31 in.)

Front seat-to-floor height: 35.6 cm to 53.3 cm (14 in. to 21 in.) Rear seat-to-floor height: 33 cm to 50.8 cm (13 in. to 20 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210107	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	35.00	1
7210108	Seat, rigid base	115.00	150.00	12
7210108	Seat cushion, multilayer foam, flat, 5.1 cm (2 in.);	N. C.	50.00	12
/210109	including removable, waterproof and machine washable cover	N.C.	30.00	12
7210111	Back support, flexible, non tension adjustable; heights from 25.4 cm to 53.3 cm (10 in. to 21 in.)	N. C.	35.00	1
7210112	Back support, flexible, tension adjustable	40.00	75.00	1
7210129	Push handle with hand grip	15.00	15.00	12
7210113	Postural support pelvic belt	25.00	25.00	12
7210114	T-shaped arm support, short, removable; height-adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210115	T-shaped arm support, long, removable; height-adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210116	L-shaped arm support, swing-away	N. C.	114.00	1
7210123	Clothing guard for L-shaped arm support	20.00	20.00	12
7210117	Arm support pad, short, straight	N. C.	6.00	1
7210118	Arm support pad, long, straight	N. C.	6.00	1
7210119	Arm support pad, tubular	N. C.	6.00	1
7210120	Arm support pad, contoured	9.00	15.00	1
7210121	Arm support pad, gel	14.00	20.00	1
7210127	Foot support, fixed	N. C.	65.00	12
7210128	Foot support, full width, flip-up, angle and depth adjustable	N. C.	65.00	12
7210124	Calf support strap, single	15.00	15.00	12
7210125	Calf support strap, double	18.00	18.00	12
7210126	Heel loop, adjustable	1.00	1.00	12

	FRAME			
7210130	Securement points for strap-type tiedowns for transport	N. C.	185.00	12
7210131	Anti-tip device	18.00	18.00	12
7210132	Reflective devices	5.00	5.00	12
7210133	Cane holder	28.00	28.00	12
	DRIVE SYSTEM			
7210134	Handrim, smooth	N. C.	40.00	12
7210135	Handrim, plasticized	N. C.	40.00	12
7210136	Handrim, anti-slip	35.00	75.00	12
7210137	Handrim, ergonomic	70.00	110.00	12
7210138	Handrim, with vertical or oblique projection	40.00	80.00	12
7210139	Parking brake, push-type activation	N. C.	25.00	12
7210140	Parking brake, pull-type activation	N. C.	25.00	12
7210141	Parking brake, scissor-type mechanism	10.00	35.00	12
7210142	Anti-rollback brake	36.00	36.00	12
7210143	Brake lever extension, plug-in	5.00	5.00	12
7210144	Fork, adjustable height	N. C.	35.00	12
	WHEELS AND TIRES			
7210149	Drive wheel, spoked	N. C.	65.00	12
7210150	Drive wheel, with puncture proof tire	15.00	80.00	12
7210151	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	20.00	1
	cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26			
	in.)			
7210152	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	20.00	1
	(20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.)			
	or 66 cm (26 in.)			
7210153	Drive wheel tire, high pressure inner tube; 55.9 cm (22	N. C.	20.00	1
	in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)			
7210146	Caster wheel, with semi-pneumatic tire; 7.6 cm (3 in.),	N. C.	15.00	12
	10.2 cm (4 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)			
7210147	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	15.00	12
	cm (6 in.)			
7210148	Quick release drive wheel axle	N. C.	10.00	12
7210154	Adaptor for amputee position	50.00	50.00	12
7210155	Spoke guards	20.00	20.00	12
7210156	Drive wheel camber; 0°, 3°, 4°, 6° or 8°	N. C.	20.00	12
			PRICE	

PRICE (including all the basic components)

980.00

7210577 MANUAL WHEELCHAIRS

CATEGORY FMA-GM 2-B-P2 (RIGID FRAME)

MOTION COMPOSITES INC.

"APEX A" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120.2 kg (265 lb.)

Device weight: 11.7 kg (24.3 lb.) **Overall width:** 60.96 cm (24¾ po)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210578	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.) 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 30.5 cm (12 in.), 33 cm (13 in.), 35.4 cm (14 in.), 38.1 cm (15 in.) 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.);	N. C.	85.72	1
7210579	Seat, rigid base	200.00	285.72	12
7210580	Seat cushion, multilayer, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	30.00	12
7210582	Back support, flexible, non tension adjustable; heights from 22.9 cm to 53.3 cm (9 in. to 21 in.)	N. C.	52.50	1
7210583	Back support, flexible, tension adjustable	72.00	124.50	1
7210599	Push handle with hand grip	49.00		12
7210584	Postural support pelvic belt	20.00		12
7210585	T-shaped arm support, short, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210586	T-shaped arm support, long, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210587	L-shaped arm support, swing-away from 20.3 cm to 27,9 cm (8 in. to 11 in.)	N. C.	41.74	1
7210593	Clothing guard for L-shaped arm support	100.00	100.00	12
7210588	Arm support pad, short, straight	N. C.	6.61	1
7210589	Arm support pad, long, straight	N. C.	6.61	1
7210590	Arm support pad, tubular	N. C.	6.61	1
7210591	Arm support pad, contoured	25.00	31.61	1
7210592	Arm support pad, gel	40.00	46.61	1
7210597	Foot support, fixed	N. C.	49.35	12
7210598	Foot support, full width, flip-up, angle and depth adjustable;	120.00	169.35	12
7210594	Calf support strap, single	60.00	60.00	12
7210595	Calf support strap, double	60.00	60.00	12
7210596	Heel loop, adjustable	60.00	60.00	12
501 0600	FRAME	** ~	122.55	4.5
7210600	Securement points for strap-type tiedowns for transport	N. C.	133.55	12
7210601	Anti-tip device	99.00		12
7210602 7210603	Reflective devices Cane holder	20.00 40.00	20.00 40.00	12 12
1210003	Calle Holder	40.00	40.00	1.2

	DRIVE SYSTEM			
7210604	Handrim, smooth	N. C.	19.89	12
7210605	Handrim, plasticized	100.00	119.89	12
7210606	Handrim, anti-slip	245.00	264.89	12
7210607	Handrim, ergonomic	245.00	264.89	12
7210608	Handrim, with oblique projection	245.00	264.89	12
7210609	Parking brake, push-type activation	N. C.	23.02	12
7210610	Parking brake, pull-type activation	N. C.	23.02	12
7210611	Parking brake, scissor-type mechanism	N. C.	23.02	12
7210612	Anti-rollback brake	50.00	50.00	12
7210613	Brake lever extension, plug-in	5.00	5.00	12
7210614	Fork, adjustable height	N. C.	35.47	12
	WHEELS AND TIRES			
7210619	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)	N. C.	33.70	12
7210620	Drive wheel, with puncture proof tire; 55.9 cm (22 in.), 61	100.00	133.70	12
	cm (24 in.) or 66 cm (26 in.)			
7210621	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	10.08	1
	cm (22 in.) or 61 cm (24 in.)			
7210622	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	10.08	1
	(20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.)			
	or 66 cm (26 in.)			
7210623	Drive wheel tire, high pressure inner tube; 50.8 cm (20	50.00	60.08	1
	in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or			
	66 cm (26 in.)			
7210615	Caster wheel, with solid tire; 7.6 cm (3 in.), 10.2 cm (4	N. C.	15.86	12
	in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)			
7210616	Caster wheel, with semi-pneumatic tire; 10.2 cm (4 in.),	N. C.	15.86	12
	12.7 cm (5 in.) or 15.2 cm (6 in.)			
7210617	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	15.86	12
	cm (6 in.)			
7210618	Quick release drive wheel axle	N. C.	30.00	12
7210624	Adapter for amputee axle position	N. C.	N. C.	12
7210625	Spoke guards	49.00	49.00	12
7210626	Drive wheel camber; 0°, 2°, 4°, 6° or 8°	N. C.	52.90	12
			PRICE	
		*	cluding all	
			the basic	
			mponents)	
7210388	MANUAL WHEELCHAIRS		1,050.00	

CATEGORY FMA-GM 2-B-P2 (FOLDING FRAME)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q2 LITE" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Device weight: 15 kg (33 lb.)

Overall width: 48.9 cm to 78.7 cm (19¼ in. to 31 in.)

Front seat-to-floor height: 35.6 cm to 53.3 cm (14 in. to 21 in.) **Rear seat-to-floor height:** 33 cm to 53.3 cm (13 in. to 21 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210389	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.4 cm (14 in.), 38.1 cm (15 in.) 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.4 cm (14 in.), 38.1 cm (15 in.) 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	35.00	1
7210390 7210391	Seat, rigid base Seat cushion, multilayer foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	115.00 N. C.	150.00 50.00	12 12
7210393 7210394 7210395 7210396	Back support, flexible, non tension adjustable Back support, flexible, tension adjustable Back support upright, straight, height and angle ajustable Back support upright, angled, height and angle ajustable	N. C. 40.00 N. C. N. C.	35.00 75.00 65.00 65.00	1 1 12 12
7210427 7210397 7210398	Push handle, fixed, with hand grip Pelvic positioning belt T-shaped arm support, short, removable; height- adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking	N. C. N. C. N. C.	15.00 25.00 114.00	12 12 1
7210399	mechanism; including clothing guard T-shaped arm support, long, removable; height-adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210400	U-shaped arm support, short, flip-up and removable; height-adjustable, from 21.6 cm to 34.3 cm (8½ in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210401	U-shaped arm support, long, flip-up and removable; height adjustable, from 21.6 cm to 34.3 cm (8½ in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210402 7210409 7210403 7210404 7210405 7210406 7210407	L-shaped arm support, swing-away Clothing guard for L-shaped arm support Arm support pad, short, straight Arm support pad, long, straight Arm support pad, tubular Arm support pad, contoured Arm support pad, gel	N. C. 20.00 N. C. N. C. N. C. 9.00 14.00	114.00 20.00 6.00 6.00 6.00 15.00 20.00	1 12 1 1 1 1

7210410	Parallel lower leg support, swing-away outward or inward; 70° or 80°; with locking mechanism; adjustable length from 8.9 cm to 24.1 cm (3½ in. to 9½ in.); or 60°, 70° or 80°; with locking mechanism; adjustable length from 22.9 cm to 50.8 cm (9 in. to 20 in.)	N. C.	55.00	12
7210412	Lower leg support, compensating elevating	55.00	110.00	12
7210417	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7210418	Foot support, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7210419	Foot support, flip-up, angle and depth adjustable, standard length	N. C.	35.00	12
7210420	Foot support, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7210421	Foot support, flip-up, full width	72.00	107.00	12
7210415	Padded calf support, angle, height and depth adjustable, including flat pad	25.00	25.00	12
7210413	Calf support strap, single	15.00	15.00	12
7210414	Calf support strap, double	18.00	18.00	12
7210416	Heel loop, adjustable	1.00	1.00	12
7210424	Back support tension bar	45.00	45.00	12
7210425	**	40.00	40.00	12
	Securement for head support for back support tension bar			
7210423	Head support, height and depth adjustable	55.00	55.00	12
7210422	Contoured cushion for head support, all sizes	35.00	35.00	12
	FRAME			
7210428	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
7210429	Anti-tip device	N. C.	18.00	12
7210430	Reflective devices	5.00	5.00	12
7210426	Front impact guard	10.00	10.00	12
7210431	Cane holder	28.00	28.00	12
7210131	Cuite notati	20.00	20.00	12
	DRIVE SYSTEM			
7210433	Handrim, smooth	N. C.	40.00	12
7210434	Handrim, plasticized	N. C.	40.00	12
7210435	Handrim, anti-slip	35.00	75.00	12
7210436	Handrim, ergonomic	70.00	110.00	12
7210437	Handrim, with vertical or oblique projection	40.00	80.00	12
7210432	Unilateral manuel propulsion mechanism	305.00	345.00	12
7210439	Parking brake, push-type activation	N. C.	25.00	12
7210440	Parking brake, pull-type activation	N. C.	25.00	12
7210438	Parking brake, unilateral activation	125.00	150.00	12
7210441	Anti-rollback brake	36.00	36.00	12
7210442	Brake lever extension, plug-in	5.00	5.00	12
7210443	Fork, adjustable height	N. C.	15.00	12
	WHEELS AND TIRES			
7210449	Drive wheel, spoked	N. C.	65.00	12
7210450	Drive wheel, with puncture proof tire	15.00	80.00	12
7210451	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26	N. C.	20.00	1
	in.)			

7210452	Drive wheel tire, standard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)	N. C.	20.00	1
7210453	Drive wheel tire, high pressure inner tube; 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.) or 66 cm (26 in.)	N. C.	20.00	1
7210445	Caster wheel, with semi-pneumatic tire; 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.) or 20.3 cm (8 in.)	N. C.	15.00	12
7210446	Caster wheel, with standard pressure inner tube tire; 15.2 cm (6 in.)	N. C.	15.00	12
7210447	Drive wheel axle, fixed	N. C.	10.00	12
7210448	Quick release drive wheel axle	N. C.	10.00	12
7210454	Adaptor for amputee position	25.00	25.00	12
7210455	Spoke guards	20.00	20.00	12
7210456	Drive wheel camber; 0° or 2°	N. C.	2.00	12
7210130	Brive wheel earnoer, v or 2	1 0.	2.00	12
			PRICE	
			(including all	
			the basic	
			components)	
7210627	MANUAL WHEELCHAIRS		1,055.00	
	CATEGORY FMA-GM 2-B-P2 (FOLDING FRAME)			
	ORTHOFAB INC.			
	"PRIMA" DEVICE			
	TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 136 kg (300 lb.) Device weight: 15 kg (33.6 lb.) Overall width: 66 cm (26 in.) Front seat-to-floor height: 35.6 cm to 54.6 cm (14 in. to 2 Rear seat-to-floor height: 33.7 cm to 50,8 cm (131/4 in. to			
	BASIC AND OPTIONAL COMPONENTS	Unit price for component	Unit price for	Warranty
		during device purchase	component replacement	(months)
7210628	BODY SUPPORT SYSTEM	-	•	•
7210026		-	•	· · · · · · · · · · · · · · · · · · ·
	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	purchase N. C.	replacement 40.00	(months)
7210629 7210630	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19	purchase	replacement	(months)
7210629 7210630	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.) Seat, rigid base Seat cushion, injected foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	purchase N. C. 20.00 N. C.	40.00 60.00 80.00	(months) 60 60 60
7210629	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.) Seat, rigid base Seat cushion, injected foam, flat, 5.1 cm (2 in.); including	purchase N. C.	40.00 60.00	(months) 60

7210634	Back support upright, straight, height and angle ajustable	N. C.	75.00	60
7210635		N. C.	75.00	60
	Back support upright, angled, height and angle ajustable			
7210665	Push handle, fixed, with hand grip	N. C.	10.00	60
7210636	Pelvic positioning belt	N. C.	10.00	60
7210637	T-shaped arm support, short, removable; height-	N. C.	110.00	60
	adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or			
	from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism;			
	including clothing guard			
7210638	T-shaped arm support, long, removable; height-adjustable,	N. C.	110.00	60
	from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm			
	to 35.6 cm (10 in. to 14 in.) by maximum increments of			
	2.5 cm (1 in.), with locking mechanism; including			
	clothing guard			
7210639	U-shaped arm support, short, flip-up and removable;	N. C.	110.00	60
7210037	height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.)	14. 6.	110.00	00
	or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism;			
	including clothing guard			
7210640	U-shaped arm support, long, flip-up and removable; height	N. C.	110.00	60
7210040	adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or	IV. C.	110.00	00
	from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism;			
	including clothing guard			
7210641	L-shaped arm support, swing-away; including clothing	N. C.	110.00	60
	guard			
7210642	Arm support pad, short, straight	N. C.	8.00	60
7210643	Arm support pad, long, straight	N. C.	8.00	60
7210644	Arm support pad, tubular	8.00	16.00	60
7210645	Arm support pad, contoured	20.00	28.00	60
7210646	Arm support pad, gel	72.00	80.00	60
7210648	Parallel lower leg support, swing-away outward; 60° or	N. C.	20.00	60
	70°; with locking mechanism; adjustable length from			
	30.5 cm to 35.6 cm (12 in. to 14 in.), or from 35.6 cm to			
	45.7 cm (14 in. to 18 in.) or from 43.2 cm to 53.3 cm (17			
	in. to 21 in.);			
	or 90°; with locking mechanism; adjustable length from			
	35.6 cm to 48.3 cm (14 in. to 19 in.)			
7210649	Parallel lower leg support, swing-away inward; 60° or 70°;	N. C.	20.00	60
	with locking mechanism; adjustable length from 30.5 cm			
	to 35.6 cm (12 in. to 14 in.), or from 35.6 cm to 45.7 cm			
	(14 in. to 18 in.) or from 43.2 cm to 53.3 cm (17 in. to 21			
	in.);			
	or 90°; with locking mechanism; adjustable length from			
	35.6 cm to 48.3 cm (14 in. to 19 in.)			
7210650	Lower leg support, compensating elevating	100.00	120.00	60
7210655	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	15.00	60
, = = = = =				
7210656		N. C.	15.00	60
	Foot support, flip-up, not angle adjustable, extra long			
7210657	Foot support, flip-up, angle and depth adjustable, standard	N. C.	15.00	60
	length			
7210658	Foot support, flip-up, angle and depth adjustable, extra	45.00	60.00	60
	long			

7210659	Foot support, flip-up, full width	85.00	100.00	60
7210653	Padded calf support, angle, height and depth adjustable,	50.00	50.00	60
	including flat pad			
7210651	Calf support strap, single	15.00	15.00	60
7210652	Calf support strap, double	30.00	30.00	60
7210654	Heel loop, adjustable	5.00	5.00	60
7210662	Back support tension bar	35.00	35.00	60
7210663	Securement for head support for back support tension bar	90.00	90.00	60
	••			
7210661	Head support, height and depth adjustable	40.00	40.00	60
7210660	Contoured cushion for head support, all sizes	40.00	40.00	60
	FRAME			
7210666	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
7210667	Anti-tip device	N. C.	12.00	60
7210668	Reflective devices	50.00	50.00	60
7210664	Front impact guard	5.00	5.00	60
7210669	Cane holder	25.00	25.00	60
	DRIVE SYSTEM			
7210671	Handrim, smooth	N. C.	80.00	60
7210672	Handrim, plasticized	N. C.	80.00	60
7210673	Handrim, anti-slip	80.00	160.00	60
7210674	Handrim, ergonomic	140.00	220.00	60
7210675	Handrim, with oblique projection	N. C.	80.00	60
7210670	Unilateral manuel propulsion mechanism	470.00	550.00	60
7210677	Parking brake, push-type activation	N. C.	30.00	60
7210678	Parking brake, pull-type activation	N. C.	30.00	60
7210676	Parking brake, unilateral activation	140.00	170.00	60
7210679	Anti-rollback brake	45.00	45.00	60
7210680	Brake lever extension, telescopic	10.00	10.00	60
7210681	Fork, adjustable height	N. C.	20.00	60
	WHEELS AND TIRES			
7210687	Drive wheel, spoked	N. C.	30.00	60
7210688	Drive wheel, with puncture proof tire	N. C.	30.00	60
7210689	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	30.00	60
	cm (22 in.) or 61 cm (24 in.)			
7210690	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	30.00	60
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7210691	Drive wheel tire, high pressure inner tube; 50.8 cm (20	N. C.	30.00	60
	in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7210683	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	40.00	60
	15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)			
7210684	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	30.00	60
	cm (6 in.) or 20.3 cm (8 in.)			
7210685	Drive wheel axle, fixed	N. C.	7.00	60
7210686	Quick release drive wheel axle	N. C.	7.00	60
7210692	Adaptor for amputee position	50.00	50.00	60
7210693	Spoke guards	70.00	70.00	60
7210694	Drive wheel camber; 3°	N. C.	N. C.	60
505 .				

PRICE
(including all
the basic
components)

1,055.00

CATEGORY FMA-GM 2-C-P1 (FOLDING FRAME)

ORTHOFAB INC.

"PRIMA 4" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 136 kg (300 lb.)

Device weight: 15.9 kg (35 lb.) **Overall width:** 67.3 cm (26½ in.)

Front seat-to-floor height: 35.6 cm to 50.8 cm (14 in. to 20 in.) Rear seat-to-floor height: 33 cm to 49.6 cm (13 in. to 19½ in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7210458	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	40.00	60
7210459	Seat cushion, injected foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	80.00	60
7210461	Back support, flexible, non tension adjustable	N. C.	100.00	60
7210462	Back support, flexible, tension adjustable	N. C.	100.00	60
7210463	Back support upright, straight, height and angle ajustable	N. C.	75.00	60
7210464	Back support upright, angled, height and angle ajustable	N. C.	75.00	60
7210487	Push handle, fixed, with hand grip	N. C.	10.00	60
7210465	Pelvic positioning belt	N. C.	10.00	60
7210466	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210467	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60

7210468	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210469	U-shaped arm support, long, flip-up and removable; height adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210470	Arm support pad, short, straight	N. C.	8.00	60
7210471	Arm support pad, long, straight	N. C.	8.00	60
7210472	Arm support pad, contoured	20.00	28.00	60
7210473	Arm support pad, gel	72.00	80.00	60
7210475	Parallel lower leg support, swing-away inward or outward; 60° or 70°; with locking mechanism; adjustable length from 30.5 cm to 35.6 cm (12 in. to 14 in.), or from	N. C.	50.00	60
	35.6 cm to 45.7 cm (14 in. to 18 in.) or from 43.2 cm to			
	53.3 cm (17 in. to 21 in.); or 90°; with locking mechanism; adjustable length from 35.6 cm to 48.3 cm (14 in. to 19 in.)			
7210476	Lower leg support, compensating elevating	N. C.	50.00	60
7210480	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	15.00	60
7210481	Foot support, flip-up, not angle adjustable, extra long	N. C.	15.00	60
7210482	Foot support, flip-up, angle and depth adjustable, standard length	N. C.	15.00	60
7210483	Foot support, flip-up, angle and depth adjustable, extra long	25.00	40.00	60
7210478	Padded calf support, angle, height and depth adjustable, including flat pad	50.00	50.00	60
7210477	Calf support strap, single	15.00	15.00	60
7210479	Heel loop, adjustable	5.00	5.00	60
7210485	Head support, height and depth adjustable	40.00	40.00	60
7210484	Contoured cushion for head support, all sizes	40.00	40.00	60
	FRAME			
7210488	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
7210489	Anti-tip device	N. C.	12.00	60
7210490	Reflective devices	50.00	50.00	60
7210486	Front impact guard	5.00	5.00	60
7210491	Cane holder	25.00	25.00	60
	DRIVE SYSTEM			
7210493	Handrim, smooth	N. C.	80.00	60
7210494	Handrim, plasticized	N. C.	80.00	60
7210492	Unilateral manuel propulsion mechanism	470.00	550.00	60
7210495	Parking brake, push-type activation	N. C.	30.00	60
7210496	Parking brake, pull-type activation	N. C.	30.00	60
7210497	Brake lever extension, telescopic	10.00	10.00	60
7210498	Fork, adjustable height	N. C.	20.00	60

	WHEELS AND TIRES			
7210503	Drive wheel, spoked	N. C.	30.00	60
7210504	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	30.00	60
7210505	Drive wheel tire, standard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	30.00	60
7210500	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)	N. C.	40.00	60
7210501	Drive wheel axle, fixed	N. C.	7.00	60
7210502	Quick release drive wheel axle	N. C.	7.00	60
7210506	Adaptor for amputee position	50.00	50.00	60
7210507	Drive wheel camber; 3°	N. C.	N. C.	60
			PRICE cluding all	
		t	he basic mponents)	
7210695	MANUAL WHEELCHAIRS		885.00	
	CATEGORY FMA-GM 2-C-P1 (FOLDING FRAME)			

MOTION COMPOSITES INC.

"HELIO A6" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Device weight: 13.9 kg (30.6 lb.) Overall width: 63.5 cm (25 in.)

Front seat-to-floor height: 30.5 cm to 52.1 cm (12 in. to 20½ in.) Rear seat-to-floor height: 30.5 cm to 51.4 cm (12 in. to 201/4 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210696	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	20.35	1
7210697	Seat cushion, multilayer foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	30.00	12
7210699	Back support, flexible, non tension adjustable	N. C.	32.16	1
7210700	Back support, flexible, tension adjustable	20.00	52.16	1
7210701	Back support upright, straight, height and angle ajustable	N. C.	66.42	12

7210702	Back support upright, angled, height and angle ajustable	N. C.	66.42	12
7210724	Push handle, fixed, with hand grip	N. C.	49.00	12
7210703	Pelvic positioning belt	N. C.	20.00	12
7210704	T-shaped arm support, short, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 10 in.), from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including	N. C.	41.74	1
7210705	Clothing guard T-shaped arm support, long, removable; height-adjustable, from 15.2 cm to 35.6 cm (6 in. to 10 in.), from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in.	N. C.	41.74	1
	to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard			
7210706	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210707	U-shaped arm support, long, flip-up and removable; height adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	41.74	1
7210708	Arm support pad, short, straight	N. C.	6.61	1
7210709	Arm support pad, long, straight	N. C.	6.61	1
7210710	Arm support pad, contoured	25.00	31.61	1
7210711	Arm support pad, gel	40.00	46.61	1
7210712	Parallel lower leg support, swing-away outward; 60°, 70° or 80°; with locking mechanism; adjustable length from 34.3 cm to 52.1 cm (13½ in. to 20½ in.), or 90° (front mount) with locking mechanism; adjustable length from 19.1 cm to 36.9 cm (7½ in. to 14½ in.)	N. C.	36.87	12
7210713	Lower leg support, compensating elevating	130.00	166.87	12
7210717	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	4.73	12
/210/1/	1 oot support, riip up, not angle adjustable, standard tenght	14. C.	4.73	12
7210718	Foot support, flip-up, not angle adjustable, extra long	N. C.	4.73	12
7210719	Foot support, flip-up, angle and depth adjustable, standard length	25.00	29.73	12
7210720	Foot support, flip-up, angle and depth adjustable, extra long	25.00	29.73	12
7210715	Padded calf support, angle, height and depth adjustable, including flat pad	85.00	85.00	12
7210714	Calf support strap, single	60.00	60.00	12
7210716	Heel loop, adjustable	5.00	5.00	12
7210722	Head support, height and depth adjustable	90.00	90.00	12
7210721	Contoured cushion for head support, all sizes	85.00	85.00	12
	FRAME			
7210725	Securement points for strap-type tiedowns for transport	N. C.	104.45	12

7210726	Anti-tip device	N. C.	16.93	12
7210727	Reflective devices	20.00	20.00	12
7210723	Front impact guard	35.00	35.00	12
7210728	Cane holder	60.00	60.00	12
	DRIVE SYSTEM			
7210730	Handrim, smooth	N. C.	19.89	12
7210731	Handrim, plasticized	100.00	119.89	12
7210729	Unilateral manuel propulsion mechanism	298.13	318.02	12
7210732	Parking brake, push-type activation	N. C.	23.02	12
7210733	Parking brake, pull-type activation	N. C.	23.02	12
7210734	Brake lever extension, plug-in	5.00	5.00	12
7210735	Fork, adjustable height	N. C.	5.36	12
	WHEELS AND TIRES			
7210740	Drive wheel, spoked	N. C.	33.70	12
7210741	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	10.08	1
	cm (22 in.) or 61 cm (24 in.)			
7210742	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	10.08	1
	(20 in.), 55.9 cm (22 in.), 61 cm (24 in.), 63.5 cm (25 in.)			
	or 66 cm (26 in.)			
7210736	Caster wheel, with solid tire; from 7.6 cm to 20.3 cm (3 in.	N. C.	15.86	12
	to 8 in.)			
7210737	Caster wheel, with semi-pneumatic tire; from 10.2 cm to	N. C.	15.86	12
	15.2 cm (4 in. to 6. in.)			
7210738	Drive wheel axle, fixed	N. C.	5.00	12
7210739	Quick release drive wheel axle	25.00	30.00	12
7210743	Adaptor for amputee position	90.00	90.00	12
7210744	Drive wheel camber; 0° or 3°	N. C.	169.40	12
			PRICE	
			(including all	
			the basic	
			components)	
7210745	MANUAL WHEELCHAIRS		985.00	
	CATEGORY FMA-GM 2-C-P1 (FOLDING FRAME)			
	LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.			
	"XL5" DEVICE			
	TECHNICAL SPECIFICATIONS OF THE DEVICE			
	Maximum weight capacity: 120 kg (265 lb.)			
	Device weight: 18.9 kg (37.7 lb.)			
	Overall width: 57.2 cm à 72.3 cm (22½ in. to 28½ in.)			
	Front seat-to-floor height: 29.3 cm to 53.3 cm (11½ in. to	,		
	Rear seat-to-floor height: 29.3 cm to 49.6 cm (11½ in. to	19½ in.)		
		Unit price for		
		component	Unit price for	Warranty
	BASIC AND OPTIONAL COMPONENTS	during device	component	(months)
		purchase	replacement	(months)
		Parenase		

BODY SUPPORT SYSTEM

7210746	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	30.00	1
7210747	Seat cushion, multilayer foam, flat, 5.1 cm (2 in.), 7.6 cm (3 in.) or 10.2 cm (4 in.); including removable, waterproof and machine washable cover	N. C.	84.00	12
7210749 7210750 7210751 7210752	Back support, flexible, non tension adjustable Back support, flexible, tension adjustable Back support upright, straight, height and angle ajustable Back support upright, angled, height and angle ajustable	N. C. 59.50 N. C. N. C.	35.50 95.00 28.00 28.00	1 1 12 12
7210774 7210753 7210754	Push handle, fixed, with hand grip Pelvic positioning belt T-shaped arm support, short, removable; height- adjustable, from 17.8 cm to 30.5 cm (7 in. to 12 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C. N. C. N. C.	17.50 15.50 90.00	12 12 1
7210755	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 35.6 cm (8 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210756	U-shaped arm support, short, flip-up and removable; height-adjustable, from 17.2 cm to 24.2 cm (6¾ in. to 9½ in.) or from 21.6 cm to 33 cm (8½ in. to 13 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210757	U-shaped arm support, long, flip-up and removable; height-adjustable, from 30.5 cm to 41,9 cm (12 in. to 16½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210758 7210759 7210760 7210761 7210762	Arm support pad, short, straight Arm support pad, long, straight Arm support pad, contoured Arm support pad, gel Parallel lower leg support, swing-away outward; 60°, 70° or 90°; with locking mechanism; adjustable length from 26.7 cm to 33 cm (10½ in. to 13 in.), from 30.5 cm to 43.2 cm (12 in. to 17 in.) or from 40.6 cm to 53.3 cm (16 in. to 21 in.)	N. C. N. C. 34.50 50.50 N. C.	5.50 5.50 40.00 56.00 59.50	1 1 1 1 12
7210763 7210767	Lower leg support, compensating elevating Foot support, flip-up, not angle adjustable, standard lenght	130.50 N. C.	190.00 28.00	12 12
7210768	Foot support, flip-up, not angle adjustable, extra long	7.00	35.00	12
7210769	Foot support, flip-up, angle and depth adjustable, standard length	22.00	50.00	12

7210795	MANUAL WHEELCHAIRS		1,150.00	
501050 5			mponents)	
		1	the basic	
		(in	PRICE scluding all	
0, 7 .				
7210794	Drive wheel camber; 0° or 3°	N. C.	50.00	12
7210793	Adaptor for amputee position	20.00	20.00	12
7210789	Quick release drive wheel axle	5.00	10.00	12
7210788	Drive wheel axle, fixed	N. C.	5.00	12
7210787	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)	N. C.	11.25	12
7210792	Drive wheel tire, standard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	21.00	1
	cm (22 in.) or 61 cm (24 in.)			
7210791	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	21.00	1
7210790	Drive wheel, spoked	N. C.	24.50	12
	WHEELS AND TIRES			
7210785	Fork, adjustable height	N. C.	12.00	12
7210784	Brake lever extension, telescopic or fixe	10.00	10.00	12
7210783	Parking brake, pull-type activation	N. C.	25.00	12
7210782	Parking brake, push-type activation	N. C.	25.00	12
7210779	Unilateral manuel propulsion mechanism	804.00	820.00	12
7210781	Handrim, plasticized	18.00	34.00	12
7210780	Handrim, smooth	N. C.	16.00	12
	DRIVE SYSTEM			
7210778	Cane holder	30.00	30.00	12
7210773	Front impact guard	35.00	35.00	12
7210777	Reflective devices	5.00	5.00	12
7210776	Anti-tip device	N. C.	17.00	12
7210775	FRAME Securement points for strap-type tiedowns for transport	N. C.	5.00	12
7210771	Contoured cushion for head support, all sizes	57.00	57.00	12
7210700	Head support, height and depth adjustable	80.00	80.00	12
7210764	Heel loop, adjustable	3.00	3.00	12
7210764	including flat or contoured pad Calf support strap, single	20.00	20.00	12
7210765	long Padded calf support, angle, height and depth adjustable,	60.50	60.50	12
7210770	Foot support, flip-up, angle and depth adjustable, extra	37.00	65.00	12

CATEGORY FMA-GM 2-C-P1 (FOLDING FRAME)

SUNRISE MEDICAL CANADA INC.

"QUICKIE 2" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Device weight: 16.8 kg (37 lb.)

Overall width: 49.6 cm to 78.7 cm (19½ in. to 31 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210796	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	35.00	1
7210797	Seat cushion, multilayer foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	50.00	12
7210799	Back support, flexible, non tension adjustable	N. C.	35.00	1
7210800	Back support, flexible, tension adjustable	40.00		1
7210801	Back support upright, straight, height and angle ajustable	N. C.	65.00	12
7210802	Back support upright, angled, height and angle ajustable	N. C.	65.00	12
7210824	Push handle, fixed, with hand grip	N. C.	15.00	12
7210803	Pelvic positioning belt	N. C.	25.00	12
7210804	T-shaped arm support, short, removable; height-adjustable, from 17.8 cm to 34.3 cm (7 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210805	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210806	U-shaped arm support, short, flip-up and removable; height-adjustable, from 21.6 cm to 34.3 cm (8.5 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210807	U-shaped arm support, long, flip-up and removable; height adjustable, from 21.6 cm to 34.3 cm (8.5 in. to 13½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7210808	Arm support pad, short, straight	N. C.	6.00	1
7210809	Arm support pad, long, straight	N. C.	6.00	1
7210810	Arm support pad, contoured	9.00		1
7210811	Arm support pad, gel	14.00	20.00	1
7210812	Parallel lower leg support, swing-away inward; 70°, 80° or 90°; with locking mechanism; adjustable length from 8.9 cm to 24.2 cm (3½ in. to 9½ in.) or from 22.9 cm to 50.8 cm (9 in. to 20 in.)	N. C.	55.00	12
7210813	Lower leg support, non-compensating elevating	35.00	90.00	12

7210817	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7210818	Foot support, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7210819	Foot support, flip-up, angle and depth adjustable, standard length	N. C.	35.00	12
7210820	Foot support, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7210815	Padded calf support, angle, height and depth adjustable, including flat pad	25.00	25.00	12
7210814	Calf support strap, single	15.00	15.00	12
7210816	Heel loop, adjustable	1.00	1.00	12
7210822	Head support, height and depth adjustable	55.00	55.00	12
7210821	Contoured cushion for head support, all sizes	35.00	35.00	12
	FRAME			
7210825	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
7210826	Anti-tip device	N. C.	18.00	12
7210827	Reflective devices	5.00	5.00	12
7210823	Front impact guard	10.00	10.00	12
7210828	Cane holder	28.00	28.00	12
	DRIVE SYSTEM			
7210830	Handrim, smooth	N. C.	40.00	12
7210831	Handrim, plasticized	N. C.	40.00	12
7210829	Unilateral manuel propulsion mechanism	305.00	345.00	12
7210832	Parking brake, push-type activation	N. C.	25.00	12
7210833	Parking brake, pull-type activation	N. C.	25.00	12
7210834	Brake lever extension, plug-in	5.00	5.00	12
7210835	Fork, adjustable height	N. C.	15.00	12
7010040	WHEELS AND TIRES	N. C	65.00	10
7210840	Drive wheel, spoked	N. C.	65.00	12
7210841	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	20.00	1
7210842	Drive wheel tire, standard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	20.00	1
7210837	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)	N. C.	15.00	12
7210838	Drive wheel axle, fixed	N. C.	10.00	12
7210839	Quick release drive wheel axle	N. C.	10.00	12
7210843	Adaptor for amputee position	25.00	25.00	12
7210844	Drive wheel camber; 0° or 2°	N. C.	2.00	12

7210508	MANUAL WHEELCHAIRS		PRICE (including all the basic components) 1,150.00	
,,,	CATEGORY FMA-GM 3-C-P2 (FOLDING FRAME)		-,	
	LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.			
	"XL RF" DEVICE			
	TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Device weight: 17.7 kg (39 lb.) Overall width: 62.3 cm to 82.5 cm (24½ in. to 32½ in.) Front seat-to-floor height: 29.3 cm to 53.3 cm (11½ in. to Rear seat-to-floor height: 29.3 cm to 52.1 cm (11½ in. to 20.3 cm)			
	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
7210509	BODY SUPPORT SYSTEM Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	30.00	1
7210510 7210511	Seat, rigid base Seat cushion, multilayer foam, flat, 5.1 cm (2 in.), 7.6 cm (3 in.) or 10.2 cm (4 in.); including removable, waterproof and machine washable cover	85.00 N. C.	115.00 84.00	12 12
7210513 7210514 7210515 7210516	Back support, flexible, non tension adjustable Back support, flexible, tension adjustable Back support upright, straight, height and angle ajustable Back support upright, angled, height and angle ajustable	N. C. 59.50 N. C. N. C.	35.50 95.00 28.00 28.00	1 1 12 12
7210547 7210517 7210518	Push handle, fixed, with hand grip Pelvic positioning belt T-shaped arm support, short, removable; height- adjustable, from 17.8 cm to 30.5 cm (7 in. to 12 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C. N. C. N. C.	17.50 15.50 90.00	12 12 1

7210519	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 35.6 cm (8 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210520	U-shaped arm support, short, flip-up and removable; height-adjustable, from 17.2 cm to 24.2 cm (6¾ in. to 9½ in.) or from 21.6 cm to 33 cm (8½ in. to 13 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210521	U-shaped arm support, long, flip-up and removable; height adjustable, from 30.5 cm to 41.9 cm (12 in. to 16½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7210522	L-shaped arm support, swing-away, including clothing guard	N. C.	90.00	1
7210523	Arm support pad, short, straight	N. C.	5.50	1
7210524	Arm support pad, long, straight	N. C.	5.50	1
7210525	Arm support pad, tubular	66.00	71.50	
7210526	Arm support pad, contoured	34.50	40.00	1
7210527	Arm support pad, gel	50.50	56.00	1
7210530	Parallel lower leg support, swing-away inward and outward; 60°, 70° or 90°; with locking mechanism; adjustable length from 26.7 cm to 33 cm (10½ in. to 13 in.), from 30.5 cm to 43.2 cm (12 in. to 17 in.) or from 40.6 cm to 53.3 cm (16 in. to 21 in.)	N. C.	59.50	12
7210532	Lower leg support, compensating elevating	130.50	190.00	12
7210537	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	28.00	12
7210538	Foot support, flip-up, not angle adjustable, extra long	7.00	35.00	12
7210539	Foot support, flip-up, angle and depth adjustable, standard length	22.00	50.00	12
7210540	Foot support, flip-up, angle and depth adjustable, extra long	37.00	65.00	12
7210541	Foot support, flip-up, full width	102.00	130.00	12
7210535	Padded calf support, angle, height and depth adjustable, including flat or contoured pad	60.50	60.50	12
7210533	Calf support strap, single	20.00	20.00	12
7210534	Calf support strap, double	20.00	20.00	12
7210536	Heel loop, adjustable	3.00	3.00	12
7210544	Back support tension bar	50.00	50.00	12
7210545	Securement for head support for back support tension bar	95.00	95.00	12
7210543	Head support, height and depth adjustable	80.00	80.00	12
7210542	Contoured cushion for head support, all sizes	57.00	57.00	12

Securement points for strap-type tiedowns for transport	N. C.	5.00	12
Anti-tip device	N. C.	17.00	12
Reflective devices	5.00	5.00	12
Front impact guard	35.00	35.00	12
• •			12
DRIVE SYSTEM			
Handrim, smooth	N. C.	16.00	12
Handrim, plasticized	18.00	34.00	12
Handrim, anti-slip	64.00	80.00	12
Handrim, ergonomic	89.00	105.00	12
Handrim, with vertical projection	64.00	80.00	12
Unilateral manuel propulsion mechanism	804.00	820.00	12
Parking brake, push-type activation	N. C.	25.00	12
Parking brake, pull-type activation	N. C.	25.00	12
Parking brake, unilateral activation	175.00	200.00	12
Anti-rollback brake	75.00	75.00	12
Brake lever extension, telescopic or fixe		10.00	12
Fork, adjustable height	N. C.	12.00	12
WHERE CAND THE			
	N. C	24.50	12
• •			12
			12
	N. C.	21.00	1
*	N. C.	21.00	1
(20 in.), 55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.)			
Drive wheel tire high pressure inner tube: 50 8 cm (20	25.00	46.00	1
	23.00	40.00	1
m.), 33.7 cm (22 m.), 61 cm (24 m.) 61 66 cm (26 m.)			
Caster wheel, with semi-pneumatic tire: 12.7 cm (5 in.).	N. C.	11.25	12
	38.75	50.00	12
÷	30.73	30.00	12
CIII (6 III.) 61 20.3 CIII (8 III.)	N. 6	- 00	
Drive wheel ayle fixed	NI ('	5.00	17
Drive wheel axle, fixed	N. C. 5.00	5.00	12
Quick release drive wheel axle	5.00	10.00	12
Quick release drive wheel axle Adaptor for amputee position	5.00 20.00	10.00 20.00	12 12
Quick release drive wheel axle	5.00	10.00	12
	Anti-tip device Reflective devices Front impact guard Cane holder DRIVE SYSTEM Handrim, smooth Handrim, plasticized Handrim, anti-slip Handrim, ergonomic Handrim, with vertical projection Unilateral manuel propulsion mechanism Parking brake, push-type activation Parking brake, pull-type activation Parking brake, unilateral activation Anti-rollback brake Brake lever extension, telescopic or fixe	Anti-tip device Reflective devices Front impact guard Cane holder 35.00 BRIVE SYSTEM Handrim, smooth Handrim, plasticized Handrim, anti-slip Handrim, ergonomic Handrim, with vertical projection Unilateral manuel propulsion mechanism Parking brake, push-type activation Parking brake, pull-type activation Parking brake, unilateral activation Anti-rollback brake Brake lever extension, telescopic or fixe Fork, adjustable height N. C. WHEELS AND TIRES Drive wheel, with puncture proof tire Drive wheel, with puncture proof tire Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.) Drive wheel tire, high pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.) Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.) Caster wheel, with standard pressure inner tube tire; 15.2 38.75	Anti-tip device Reflective devices 5.00 Front impact guard 35.00 Cane holder 30.00 30.00 DRIVE SYSTEM Handrim, smooth Handrim, plasticized Handrim, anti-slip 64.00 Handrim, egonomic Handrim, egonomic Handrim, with vertical projection Unilateral manuel propulsion mechanism 804.00 Parking brake, push-type activation Parking brake, push-type activation Parking brake, pull-type activation N. C. 25.00 Parking brake, unilateral activation Anti-rollback brake 75.00 Brake lever extension, telescopic or fixe Fork, adjustable height N. C. 12.00 WHEELS AND TIRES Drive wheel, with puncture proof tire Drive wheel, with puncture proof tire Drive wheel, with pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.) Drive wheel tire, slandard pressure inner tube; 50.8 cm (20 in.), 55.9 cm (22 in.), 61 cm (24 in.) or 66 cm (26 in.) Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.) Caster wheel, with standard pressure inner tube tire; 15.2 38.75 50.00

PRICE					
(including all					
the basic					
components)					

1,285.00

CATEGORY FMA-GM 3-C-P2 (FOLDING FRAME)

ORTHOFAB INC.

"PRIMA ROBUSTE" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 159 kg (350 lb.)

Device weight: 16.8 kg (37 lb.) **Overall width:** 72.9 cm (28.7 in.)

Front seat-to-floor height: 35.6 cm to 50.8 cm (14 in. to 20 in.) Rear seat-to-floor height: 33 cm to 49.6 cm (13 in. to 19½ in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price for component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7210846	Seat, flexible, tension adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; handle to fold chair; widths of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	40.00	60
7210847	Seat, rigid base	20.00	60.00	60
7210848	Seat cushion, injected foam, flat, 5.1 cm (2 in.); including removable, waterproof and machine washable cover	N. C.	80.00	60
7210850	Back support, flexible, non tension adjustable	N. C.	100.00	60
7210851	Back support, flexible, tension adjustable	N. C.	100.00	60
7210852	Back support upright, straight, height and angle ajustable	N. C.	75.00	60
7210853	Back support upright, angled, height and angle ajustable	N. C.	75.00	60
7210883	Push handle, fixed, with hand grip	N. C.	10.00	60
7210854	Pelvic positioning belt	N. C.	10.00	60
7210855	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210856	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60

7210857	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210858	U-shaped arm support, long, flip-up and removable; height adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7210859	L-shaped arm support, swing-away, including clothing guard	N. C.	110.00	60
7210860	Arm support pad, short, straight	N. C.	8.00	60
7210861	Arm support pad, long, straight	N. C.	8.00	60
7210862	Arm support pad, tubular	8.00	16.00	60
7210863	Arm support pad, contoured	20.00	28.00	60
7210864	Arm support pad, gel	72.00	80.00	60
7210866	Parallel lower leg support, swing-away outward; 60° or	N. C.	20.00	60
7210000	70°; with locking mechanism; adjustable length from 30.5 cm to 35.6 cm (12 in. to 14 in.), or from 35.6 cm to	IV. C.	20.00	00
	45.7 cm (14 in. to 18 in.) or from 43.2 cm to 53.3 cm (17 in. to 21 in.); or 90°; with locking mechanism; adjustable length from 35.6 cm to 48.3 cm (14 in. to 19 in.)			
7210867	Parallel lower leg support, swing-away inward; 60° or 70°; with locking mechanism; adjustable length from 30.5 cm to 35.6 cm (12 in. to 14 in.), or from 35.6 cm to 45.7 cm	N. C.	20.00	60
	(14 in. to 18 in.) or from 43.2 cm to 53.3 cm (17 in. to 21 in.); or 90°; with locking mechanism; adjustable length from 35.6 cm to 48.3 cm (14 in. to 19 in.)			
7210868	Lower leg support, compensating elevating	100.00	120.00	60
7210873	Foot support, flip-up, not angle adjustable, standard lenght	N. C.	15.00	60
7210874	Foot support, flip-up, not angle adjustable, extra long	N. C.	15.00	60
7210875	Foot support, flip-up, angle and depth adjustable, standard length	N. C.	15.00	60
7210876	Foot support, flip-up, angle and depth adjustable, extra long	45.00	60.00	60
7210877	Foot support, flip-up, full width	85.00	100.00	60
7210871	Padded calf support, angle, height and depth adjustable, including flat pad	50.00	50.00	60
7210869	Calf support strap, single	15.00	15.00	60
7210870	Calf support strap, double	30.00	30.00	60
7210872	Heel loop, adjustable	5.00	5.00	60
7210880	Back support tension bar	35.00	35.00	60
7210881	Securement for head support for back support tension bar	90.00	90.00	60
7210879	Head support, height and depth adjustable	40.00	40.00	60
7210878	Contoured cushion for head support, all sizes	40.00	40.00	60 60
	FRAME			60
7210884	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60

7210885	Anti-tip device	N. C.	12.00	60
7210886	Reflective devices	50.00	50.00	60
7210882	Front impact guard	5.00	5.00	60
7210887	Cane holder	25.00	25.00	60
	DRIVE SYSTEM			
7210889	Handrim, smooth	N. C.	80.00	60
7210890	Handrim, plasticized	N. C.	80.00	60
7210891	Handrim, anti-slip	80.00	160.00	60
7210892	Handrim, ergonomic	140.00	220.00	60
7210893	Handrim, with oblique projection	N. C.	80.00	60
7210888	Unilateral manuel propulsion mechanism	470.00	550.00	60
7210895	Parking brake, push-type activation	N. C.	30.00	60
7210896	Parking brake, pull-type activation	N. C.	30.00	60
7210894	Parking brake, unilateral activation	140.00	170.00	60
7210897	Anti-rollback brake	45.00	45.00	60
7210898	Brake lever extension, telescopic	10.00	10.00	60
7210899	Fork, adjustable height	N. C.	20.00	60
	WHEELS AND TIRES			
7210905	Drive wheel, spoked	N. C.	30.00	60
7210906	Drive wheel, with puncture proof tire	N. C.	30.00	60
7210907	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	30.00	60
	cm (22 in.) or 61 cm (24 in.)			
7210908	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	30.00	60
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7210909	Drive wheel tire, high pressure inner tube; 50.8 cm (20	N. C.	30.00	60
7210707	in.), 55.9 cm (22 in.) or 61 cm (24 in.)	1	30.00	
7210901	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	40.00	60
	15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.)			
7210902	Caster wheel, with standard pressure inner tube tire; 15.2	N. C.	40.00	60
	cm (6 in.) or 20.3 cm (8 in.)			
7210903	Drive wheel axle, fixed	N. C.	7.00	60
7210904	Quick release drive wheel axle	5.00	7.00	60
7210910	Adaptor for amputee position	50.00	50.00	60
7210911	Spoke guards	70.00	70.00	60
7210912	Drive wheel camber; 3°	N. C.	N. C.	60

DIVISION II: POWERED WHEELCHAIRS

SUBDIVISION 1 : MASS GROUP 1

PRICE
(including all
the basic
components)

7213000 POWERED WHEELCHAIR

4,275.00

CATEGORY FMO-GM 1-B-P2 (MID-WHEEL DRIVE)

AMYLIOR INC.

"ALLTRACK M ATM1B" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 50 kg (110 lb.)

Seat-to-floor height: 39.5 cm to 52.1 cm (15½ in. to 20½ in.)

Frame: mid-wheel drive base, overall width ≤ 63.5 cm (25 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213001	Seat-to-back assembly structure; resizable	N. C.	550.00	12
7213002	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	200.00	12
7213003	Seat, padded and contoured	200.00	400.00	1
7213006	Back support, padded and contoured; heights of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.) or 71 cm (28 in.)	N. C.	450.00	1
7213005	Back support, flexible, tension adjustable	N. C.	450.00	1
7213007	Back support upright, straight, height and angle adjustable; angle-adjustable from 86° to 122° by maximum increments of 4°	N. C.	94.00	12
7213008	Push handle, with hand grip	N. C.	8.00	12

7213010	Powered reclining back support, including biomechanical adjustment	1,800.00	1,800.00	12
7213011	Power tilt mechanism	1,600.00	1,600.00	12
7213011	Postural support pelvic belt	N. C.	25.00	12
7213012	T-shaped arm support, short, removable; height-	N. C.	150.00	1
7213013	adjustable, from 18.42 cm to 38.7 cm (7½ in. to 15¼ in.)	14. C.	150.00	1
	by maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213014	T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
/215014	from 18.42 cm to 38.7 cm (7 ¹ / ₄ in. to 15 ¹ / ₄ in.) by	14. C.	150.00	1
	maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213015	U-shaped arm support, short, flip-up and removable;	33.00	183.00	1
7213013	height-adjustable, from 18.42 cm to 38.7 cm (7½ in. to	33.00	103.00	1
	15¼ in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism			
7213016	U-shaped arm support, long, flip-up and removable; height	33.00	183.00	1
7213010	adjustable, from 18.42 cm to 38.7 cm (7 ¹ / ₄ in. to 15 ¹ / ₄ in.)	33.00	103.00	1
	by maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213018	I-shaped arm support, flip-up; height-adjustable, from	33.00	183.00	1
7213010	18.42 cm to 38.7 cm (7 ¹ / ₄ in. to 15 ¹ / ₄ in.) by maximum	33.00	103.00	1
	increments of 2.5 cm (1 in.), with locking mechanism			
7213019	L-shaped arm support, flip-up; height-adjustable, from	25.00	175.00	1
7213019	17.8 cm to 38,1 cm (7 in. to 15 in.) by maximum	20.00	170,00	-
	increments of 2.5 cm (1 in.), with locking mechanism			
7213020	Arm support pad, short, straight	N. C.	13.00	1
7213021	Arm support pad, long, straight	N. C.	13.00	1
7213022	Arm support pad, contoured	7.00	20.00	1
7213023	Arm support pad, gel	19.00	32.00	1
7213024	Parallel lower leg support, 60°, 70°, 80° or 90°; detachable	N. C.	192.00	12
	and pivoting with locking mechanism; adjustable length			
	from 14 cm to 49.5 cm (5½ in. to 19½ in.)			
7213025	Lower leg support, compensating elevating; with locking	108.00	300.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7213026	Powered elevating lower leg support, individually	558.00	750.00	12
	controlled			
7213027	Powered elevating lower leg support, paired control	558.00	750.00	12
7213028	One-piece powered elevating lower leg support	1,308.00	1,500.00	12
7213029	Padded calf support, angle, height and depth adjustable,	70.00	70.00	12
	including contoured pad			
7213030	Foot support, separate, flip-up, not angle adjustable,	N. C.	50.00	12
	standard lenght			

7213031	Foot support, separate, flip-up, not angle adjustable, extra long	30.00	80.00	12
7213032	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	30.00	80.00	12
7213033	Foot support, separate, flip-up, angle and depth adjustable, extra long	30.00	80.00	12
7213034	Foot support, flip-up, one-piece platform	110.00	160.00	12
7213035	Heel loop, adjustable	10.00	10.00	12
7213036	Head support, depth adjustable	90.00	90.00	12
7213037	Contoured cushion for head support, all sizes	50.00	50.00	12
7213037	Back support tension bar	100.00	100.00	12
7213038	Securement for head support for back support tension bar	20.00	20.00	12
/213039	Securement for nead support for back support tension bar	20.00	20.00	12
	FRAME			
7213040	Front impact guard	20.00	20.00	12
7213041	Lighting systems	400.00	400.00	12
7213042	Reflective devices	N. C.	10.00	12
7213043	Emergency flashers	N. C.	N. C.	12
7213044	Triangular-shaped flag, orange, 300 cm ² minimum surface	10.00	10.00	12
7213045	Securement points for strap-type tiedowns for transport	N. C.	N. C.	12
7213043		14. C.	14. C.	12
7212046	DRIVE SYSTEM	N. C	750.00	10
7213046	Standard control device for multipurpose programmable	N. C.	750.00	12
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7213047	Compact control device	N. C.	750.00	12
7213048	Control device operated by an assistant	750.00	750.00	12
7213049	Control device for powered repositionning, for an	200.00	200.00	12
72100.5	accessory			
7213050	Control device for powered repositionning, for four	600.00	600.00	12
	accessories			
7213051	Infrared option	N. C.	N. C.	12
7213052	Bluetooth option	N. C.	N. C.	12
7213053	Separate control for powered tilt mechanism	250.00	250.00	12
7213054	Control device support, standard lateral, adjustable front- rear position	N. C.	100.00	12
7213055	Control device support, lateral, flip-up with locking	100.00	200.00	12
	mechanism, adjustable front-rear position			
7213056	Control device support, central, flip-up, adjustable front- rear position	200.00	300.00	12
7213057	Controller for multipurpose programmable electronic	N. C.	660.00	12
7210007	system	1		12
7213058	Motor, including electric brake	N. C.	600.00	12
7213060	Battery charger, compatible with group 22NF or 24	N. C.	219.00	12
5010 000	batteries	4.000.00	4.000.00	4.5
7213061	Adapted non-proportional control, cephalic	4,000.00	4,000.00	12
7213062	Adapted non-proportional control, chin-controlled	600.00	600.00	12
7213063	Adapted non-proportional control, breath-controlled	1,500.00	1,500.00	12
7213064	Adapted proportional control, cephalic	4,000.00	4,000.00	12

7213065	Adapted proportional control, chin-controlled	1,500.00	1,500.00	12
7213066	Adapted proportional control, mini joystick	1,500.00	1,500.00	12
7213067	Mounting bracket for adapted control	350.00	350.00	12
7213068	Adapted control interface	350.00	1,100.00	12
7213069	Mounting bracket for interface	350.00	350.00	12
7213070	Lever extension, ball	58.00	58.00	12
7213071	Lever extension, conicospherical	58.00	58.00	12
7213072	Lever extension, stick	58.00	58.00	12
7213073	Lever extension, T-shaped	58.00	58.00	12
7213074	Lever extension, mushroom	80.00	80.00	12
7213075	Lever extension, U-shaped	95.00	95.00	12
7213076	Trajectory correction system	895.00	895.00	12
	WHEELS AND TIRES			
7213077	Drive wheel; 31.75 cm (12½ in.) or 35.6 cm (14 in.)	N. C.	70.00	12
7213078	Drive wheel tire, standard pressure inner tube; 31.75 cm	N. C.	58.00	1
	(12½ in.) or 35.6 cm (14 in.)			
7213079	Puncture proof tire for drive wheel	17.00	75.00	1
7213080	Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.)	N. C.	70.00	12
7213081	Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.)	N. C.	70.00	12
7213082	Caster wheel, with puncture proof tire; 20.3 cm (8 in.)	N. C.	70.00	12
7213083	Suspension independent of wheels	N. C. N. C.	29.00 38.00	12

PRICE (including all the basic components)

7213086 **POWERED WHEELCHAIR** 4,575.00

CATEGORY FMO-GM 1-B-P2 (MID-REAR WHEEL DRIVE)

AMYLIOR INC.

"ALLTRACK R ATR1B" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 50 kg (110 lb.)

Seat-to-floor height: 38,7 cm to 52,1 cm (15% in. to $20\frac{1}{2}$ in.)

Frame: mid-rear wheel drive base, overall width ≤ 66 cm (26 in.)

 $\label{prive system:manual freewheel lever; control cable replaceable separately} \textbf{Drive system:} \ \ \text{manual freewheel lever; control cable replaceable separately}$

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213087	Seat-to-back assembly structure; resizable	N. C.	550.00	12
7213088	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	200.00	12
7213089	Seat, padded and contoured	200.00	400.00	1
7213092	Back support, padded and contoured; heights of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.) or 71.1 cm (28 in.)	N. C.	450.00	1
7213091	Back support, flexible, tension adjustable	N. C.	450.00	1
7213093	Back support upright, straight, height and angle adjustable; angle-adjustable from 86° to 122° by maximum increments of 4°	N. C.	94.00	12
7213094	Push handle, with hand grip	N. C.	8.00	12
7213096	Powered reclining back support, including biomechanical adjustment	1,800.00	1,800.00	12
7213097	Power tilt mechanism	1,600.00	1,600.00	12
7213098	Postural support pelvic belt	N. C.	25.00	12

7213099	T-shaped arm support, short, removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism;	N. C.	150.00	1
7213100	T-shaped arm support, long, removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213101	U-shaped arm support, short, flip-up and removable; height-adjustable, from 18.4 cm to 38.7 cm (71/4 in. to 151/4 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213102	U-shaped arm support, long, flip-up and removable; height adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213104	I-shaped arm support, flip-up; height-adjustable, from 18.4 cm to 38.7 cm (71/4 in. to 151/4 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213105	L-shaped arm support, flip-up; height-adjustable, from 17.8 cm to 38.1 cm (7 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	25.00	175.00	1
7213106	Arm support pad, short, straight	N. C.	13.00	1
7213107	Arm support pad, long, straight	N. C.	13.00	1
7213108	Arm support pad, contoured	7.00	20.00	1
7213109	Arm support pad, gel	19.00	32.00	1
7213110	Parallel lower leg support, 60°, 70°, 80° or 90°; detachable and pivoting with locking mechanism; adjustable length from 14 cm to 49.5 cm (5½ in. to 19½ in.)	N. C.	192.00	12
7213111	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	108.00	300.00	12
7213112	Powered elevating lower leg support, individually controlled	558.00	750.00	12
7213113	Powered elevating lower leg support, paired control	558.00	750.00	12
7213114	Padded calf support, angle, height and depth adjustable, including contoured pad	70.00	70.00	12
7213115	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	50.00	12
7213116	Foot support, separate, flip-up, not angle adjustable, extra long	30.00	80.00	12
7213117	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	30.00	80.00	12
7213118	Foot support, separate, flip-up, angle and depth adjustable, extra long	30.00	80.00	12
7213119	Heel loop, adjustable	10.00	10.00	12
7213120	Head support, depth adjustable	90.00	90.00	12
7213121	Contoured cushion for head support, all sizes	50.00	50.00	12
7213122	Back support tension bar	100.00	100.00	12
7213123	Securement for head support for back support tension bar	20.00	20.00	12

7213124 7213125 7213126 7213127 7213128 7213129	Anti-tip device Front impact guard Lighting systems Reflective devices Emergency flashers Triangular-shaped flag, orange, 300 cm ² minimum surface	N. C. 20.00 400.00 N. C. N. C. 10.00	70.00 20.00 400.00 10.00 N. C. 10.00	12 12 12 12 12 12
7213130	Securement points for strap-type tiedowns for transport DRIVE SYSTEM	N. C.	N. C.	12
7213131	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	750.00	12
7213132	Compact control device	N. C.	750.00	12
7213133	Control device operated by an assistant	750.00	750.00	12
7213134	Control device for powered repositionning, for an accessory	200.00	200.00	12
7213135	Control device for powered repositionning, for four accessories	600.00	600.00	12
7213136	Infrared option	N. C.	N. C.	12
7213137	Bluetooth option	N. C.	N. C.	12
7213138	Separate control for powered tilt mechanism	250.00	250.00	12
7213139	Control device support, standard lateral, adjustable front- rear position	N. C.	100.00	12
7213140	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	100.00	200.00	12
7213141	Control device support, central, flip-up, adjustable front- rear position	200.00	300.00	12
7213142	Controller for multipurpose programmable electronic system	N. C.	660.00	12
7213143	Motor, including electric brake	N. C.	600.00	12
7213145	Battery charger, compatible with group 22NF or 24 batteries	N. C.	219.00	12
7213146	Adapted non-proportional control, cephalic	4,000.00	4,000.00	12
7213147	Adapted non-proportional control, chin-controlled	600.00	600.00	12
7213148	Adapted non-proportional control, breath-controlled	1,500.00	1,500.00	12
7213149	Adapted proportional control, cephalic	4,000.00	4,000.00	12
7213150	Adapted proportional control, chin-controlled	1,500.00	1,500.00	12
7213151	Adapted proportional control, mini joystick	1,500.00	1,500.00	12
7213152	Mounting bracket for adapted control	350.00	350.00	12
7213153	Adapted control interface	350.00	1,100.00	12
7213154	Mounting bracket for interface	350.00	350.00	12
7213155	Lever extension, ball	58.00	58.00	12
7213156	Lever extension, conicospherical	58.00	58.00	12
7213157	Lever extension, stick	58.00	58.00	12
7213158	Lever extension, T-shaped	58.00	58.00	12
7213159	Lever extension, mushroom	80.00	80.00	12
7213160	Lever extension, U-shaped	95.00	95.00	12
7213161	Trajectory correction system	895.00	895.00	12

	WHEELS AND TIRES			
7213162	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.)	N. C.	70.00	12
7213163	Drive wheel tire, standard pressure inner tube; 31.8 cm $(12\frac{1}{2} \text{ in.})$ or 35.6 cm (14 in.)	N. C.	58.00	1
7213164	Puncture proof tire for drive wheel	17.00	75.00	1
7213166	Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	N. C.	70.00	12
7213167	Caster wheel, with puncture proof tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	N. C.	70.00	12
7213168	Suspension independent of wheels	N. C.	29.00	12
7213169	Fork, standard	N. C.	38.00	12
		(in-	PRICE cluding all he basic mponents)	
7213171	DOM/EDED WHITE ON A D	·		

POWERED WHEELCHAIR

4,675.00

CATEGORY FMO-GM 1-B-P2 (MID-WHEEL DRIVE)

AMYLIOR INC.

"ALLTRACK M ATM1C" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 50 kg (110 lb.)

Seat-to-floor height: 39,5 cm to 52,1 cm (15½ in. to 20½ in.)

Frame: mid-wheel drive base, overall width \leq 64.47 cm (25.38 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213172	Seat-to-back assembly structure; resizable	N. C.	550.00	12
7213173	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	200.00	12
7213174	Seat, padded and contoured	200.00	400.00	1

5010155	D 1	N. C	450.00	4
7213177	Back support, padded and contoured; heights of 40.6 cm	N. C.	450.00	1
	(16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19			
	in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 66 cm (26 in.) or 71.1 cm			
	(28 in.)			
7213176	Back support, flexible, tension adjustable	N. C.	450.00	1
7213176	Back support upright, straight, height and angle	N. C.	94.00	12
/2131/6	adjustable; angle-adjustable from 86° to 122° by	IV. C.	94.00	12
	maximum increments of 4°			
7213179	Push handle, with hand grip	N. C.	8.00	12
7213177	Powered reclining back support, including biomechanical	1,800.00	1,800.00	12
,213101	adjustment	1,000.00	1,000.00	
7213182	Power tilt mechanism	1,600.00	1,600.00	12
7213183	Postural support pelvic belt	N. C.	25.00	12
7213184	T-shaped arm support, short, removable; height-	N. C.	150.00	1
	adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by			
	maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213185	T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
	from 18.4 cm to 38.7 cm (7½ in. to 15¼ in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
	, ,			
7213186	U-shaped arm support, short, flip-up and removable;	33.00	183.00	1
	height-adjustable, from 18.4 cm to 38.7 cm (71/4 in. to 151/4			
	in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism			
7213187	U-shaped arm support, long, flip-up and removable; height	33.00	183.00	1
	adjustable, from 18.4 cm to 38.7 cm ($7\frac{1}{4}$ in. to $15\frac{1}{4}$ in.) by			
	maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213189	I-shaped arm support, flip-up; height-adjustable, from	33.00	183.00	1
,	18.4 cm to 38.7 cm (7 ¹ / ₄ in. to 15 ¹ / ₄ in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7213190	L-shaped arm support, flip-up; height-adjustable, from	25.00	175.00	1
	17.8 cm to 38.1 cm (7 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7213191	Arm support pad, short, straight	N. C.	13.00	1
7213192	Arm support pad, long, straight	N. C.	13.00	1
7213193	Arm support pad, contoured	7.00	20.00	1
7213194	Arm support pad, gel	19.00	32.00	1
7213195	Parallel lower leg support, 60°, 70°, 80° or 90°; detachable	N. C.	192.00	12
	and pivoting with locking mechanism; adjustable length			
	from 14 cm to 49.5 cm (5½ in. to 19½ in.)			
7213196	Lower leg support, compensating elevating; with locking	108.00	300.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7213197	Powered elevating lower leg support, individually	558.00	750.00	12
	controlled			
7213198	Powered elevating lower leg support, paired control	558.00	750.00	12
7213199	One-piece powered elevating lower leg support	1,308.00	1,500.00	12
7213200	Padded calf support, angle, height and depth adjustable,	70.00	70.00	12
	including contoured pad			

7213201	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	50.00	12
7213202	Foot support, separate, flip-up, not angle adjustable, extra long	30.00	80.00	12
7213203	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	30.00	80.00	12
7213204	Foot support, separate, flip-up, angle and depth adjustable, extra long	30.00	80.00	12
7213205	Foot support, flip-up, one-piece platform	110.00	160.00	12
7213206	Heel loop, adjustable	10.00	10.00	12
7213207	Head support, depth adjustable	90.00	90.00	12
7213207	Contoured cushion for head support, all sizes	50.00	50.00	12
7213209	Back support tension bar	100.00	100.00	12
7213210	Securement for head support for back support tension bar	20.00	20.00	12
,210210	community for new suppose for each suppose vention on	20.00	20.00	
5 040044	FRAME	20.00	20.00	10
7213211	Front impact guard	20.00	20.00	12
7213212	Lighting systems	N. C.	400.00	12
7213213	Reflective devices	N. C.	10.00	12
7213214	Emergency flashers	N. C.	N. C.	12
7213215	Triangular-shaped flag, orange, 300 cm ² minimum surface	10.00	10.00	12
7213216	Securement points for strap-type tiedowns for transport	N. C.	N. C.	12
	DRIVE SYSTEM			
7213217	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches	N. C.	750.00	12
	the functions: start-stop, horn and function selection; battery charge level indicator			
7213218	Compact control device	N. C.	750.00	12
7213219	Control device operated by an assistant	750.00	750.00	12
7213220	Control device for powered repositionning, for an accessory	200.00	200.00	12
7213221	Control device for powered repositionning, for four accessories	600.00	600.00	12
7213222	Infrared option	N. C.	N. C.	12
7213223	Bluetooth option	N. C.	N. C.	12
7213224	Separate control for powered tilt mechanism	250.00	250.00	12
7213225	Control device support, standard lateral, adjustable front- rear position	N. C.	100.00	12
7213226	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	100.00	200.00	12
7213227	Control device support, central, flip-up, adjustable front- rear position	200.00	300.00	12
7213228	Controller for multipurpose programmable electronic system	N. C.	660.00	12
7213229	Motor, including electric brake	N. C.	600.00	12
7213231	Battery charger, compatible with group 24 batteries	N. C.	219.00	12
7213232	Adapted non-proportional control, cephalic	4,000.00	4,000.00	12
7213232	Adapted non-proportional control, cepnane Adapted non-proportional control, chin-controlled	600.00	600.00	12
7213234	Adapted non-proportional control, breath-controlled	1,500.00	1,500.00	12

7213235	Adapted proportional control, cephalic	4,000.00	4,000.00	12
7213236	Adapted proportional control, chin-controlled	1,500.00	1,500.00	12
7213237	Adapted proportional control, mini joystick	1,500.00	1,500.00	12
7213238	Mounting bracket for adapted control	350.00	350.00	12
7213239	Adapted control interface	350.00	1,100.00	12
7213240	Mounting bracket for interface	350.00	350.00	12
7213241	Lever extension, ball	58.00	58.00	12
7213242	Lever extension, conicospherical	58.00	58.00	12
7213243	Lever extension, stick	58.00	58.00	12
7213244	Lever extension, T-shaped	58.00	58.00	12
7213245	Lever extension, mushroom	80.00	80.00	12
7213246	Lever extension, U-shaped	95.00	95.00	12
7213247	Trajectory correction system	895.00	895.00	12
	WHEELS AND TIRES			
7213248	WHEELS AND TIRES Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.)	N. C.	70.00	12
7213248 7213249	17	N. C. N. C.	70.00 58.00	12 1
	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.)			
	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm			
7213249	Drive wheel; $31.8 \text{ cm} (12\frac{1}{2} \text{ in.}) \text{ or } 35.6 \text{ cm} (14 \text{ in.})$ Drive wheel tire, standard pressure inner tube; $31.8 \text{ cm} (12\frac{1}{2} \text{ in.}) \text{ or } 35.6 \text{ cm} (14 \text{ in.})$	N. C.	58.00	1
7213249 7213250 7213251	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.)	N. C. 17.00 N. C.	58.00 75.00 70.00	1 1 12
7213249 7213250	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.) Caster wheel, with standard pressure inner tube tire; 20.3	N. C. 17.00	58.00 75.00	1
7213249 7213250 7213251	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.) Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.)	N. C. 17.00 N. C.	58.00 75.00 70.00	1 1 12
7213249 7213250 7213251	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.) Caster wheel, with standard pressure inner tube tire; 20.3	N. C. 17.00 N. C.	58.00 75.00 70.00	1 1 12
7213249 7213250 7213251 7213252 7213253	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.) Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.) Caster wheel, with puncture proof tire; 20.3 cm (8 in.)	N. C. 17.00 N. C. N. C. N. C.	58.00 75.00 70.00 70.00 70.00	1 1 12 12
7213249 7213250 7213251 7213252	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Drive wheel tire, standard pressure inner tube; 31.8 cm (12½ in.) or 35.6 cm (14 in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.) Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.)	N. C. 17.00 N. C. N. C.	58.00 75.00 70.00 70.00	1 1 12 12

PRICE
(including all
the basic
components)

7213257 **POWERED WHEELCHAIR**

4,975.00

CATEGORY FMO-GM 1-C-P2 (MID-REAR WHEEL DRIVE)

AMYLIOR INC.

"ALLTRACK R ATR1C" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 50 kg (110 lb.)

Seat-to-floor height: 38,7 cm to 52.1 cm $(15\frac{1}{4}$ in. to $20\frac{1}{2}$ in.)

Frame: mid-rear wheel drive base, overall width \leq 64.47 cm (25.38 in.) **Drive system:** manual freewheel lever; control cable replaceable separately

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213258	Seat-to-back assembly structure; resizable	N. C.	550.00	12
7213259	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.); depths of 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	200.00	12
7213260	Seat, padded and contoured	200.00	400.00	1
7213263	Back support, padded and contoured; heights of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.) or 71.1 cm (28 in.)	N. C.	450.00	1
7213262	Back support, flexible, tension adjustable	N. C.	450.00	1
7213264	Back support upright, straight, height and angle adjustable; angle-adjustable from 86° to 122° by maximum increments of 4°	N. C.	94.00	12
7213265	Push handle, with hand grip	N. C.	8.00	12
7213267	Powered reclining back support, including biomechanical adjustment	1,800.00	1,800.00	12
7213268	Power tilt mechanism	1,600.00	1,600.00	12
7213269	Postural support pelvic belt	N. C.	25.00	12

7213270	T-shaped arm support, short, removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213271	T-shaped arm support, long, removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15¼ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213272	U-shaped arm support, short, flip-up and removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213273	U-shaped arm support, long, flip-up and removable; height adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213275	I-shaped arm support, flip-up; height-adjustable, from 18.4 cm to 38.7 cm (7 ¹ / ₄ in. to 15 ¹ / ₄ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7213276	L-shaped arm support, flip-up; height-adjustable, from 17.8 cm to 38.1 cm (7 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	25.00	175.00	1
7213277	Arm support pad, short, straight	N. C.	13.00	1
7213278	Arm support pad, long, straight	N. C.	13.00	1
7213279	Arm support pad, contoured	7.00	20.00	1
7213280	Arm support pad, gel	19.00	32.00	1
7213281	Parallel lower leg support, 60°, 70°, 80° or 90°; detachable and pivoting with locking mechanism; adjustable length from 14 cm to 49,5 cm (5½ in. to 19½ in.)	N. C.	192.00	12
7213282	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	108.00	300.00	12
7213283	Powered elevating lower leg support, individually controlled	558.00	750.00	12
7213284	Powered elevating lower leg support, paired control	558.00	750.00	12
7213285	Padded calf support, angle, height and depth adjustable, including contoured pad	70.00	70.00	12
7213286	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	50.00	12
7213287	Foot support, separate, flip-up, not angle adjustable, extra long	30.00	80.00	12
7213288	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	30.00	80.00	12
7213289	Foot support, separate, flip-up, angle and depth adjustable, extra long	30.00	80.00	12
7213290	Heel loop, adjustable	10.00	10.00	12
7213291	Head support, depth adjustable	90.00	90.00	12
7213292	Contoured cushion for head support, all sizes	50.00	50.00	12
7213293	Back support tension bar	100.00	100.00	12
7213294	Securement for head support for back support tension bar	20.00	20.00	12

7213295	Anti-tip device	N. C.	70.00	12
7213296	Front impact guard	20.00	20.00	12
7213297	Lighting systems	N. C.	400.00	12
7213298	Reflective devices	N. C.	10.00	12
7213299	Emergency flashers	N. C.	N. C.	12
7213300	Triangular-shaped flag, orange, 300 cm ² minimum surface	10.00	10.00	12
7213301	Securement points for strap-type tiedowns for transport	N. C.	N. C.	12
	DRIVE SYSTEM			
7213302	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	750.00	12
7213303	Compact control device	N. C.	750.00	12
7213304	Control device operated by an assistant	750.00	750.00	12
7213305	Control device for powered repositionning, for an accessory	200.00	200.00	12
7213306	Control device for powered repositionning, for four accessories	600.00	600.00	12
7213307	Infrared option	N. C.	N. C.	12
7213308	Bluetooth option	N. C.	N. C.	12
7213309	Separate control for powered tilt mechanism	250.00	250.00	12
7213310	Control device support, standard lateral, adjustable front- rear position	N. C.	100.00	12
7213311	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	100.00	200.00	12
7213312	Control device support, central, flip-up, adjustable front- rear position	200.00	300.00	12
7213313	Controller for multipurpose programmable electronic system	N. C.	660.00	12
7213314	Motor, including electric brake	N.C.	600.00	12
7213316	Battery charger, compatible with group 24 batteries	N. C.	219.00	12
7213317	Adapted non-proportional control, cephalic	4,000.00	4,000.00	12
7213318	Adapted non-proportional control, chin-controlled	600.00	600.00	12
7213319	Adapted non-proportional control, breath-controlled	1,500.00	1,500.00	12
7213320	Adapted proportional control, cephalic	4,000.00	4,000.00	12
7213321	Adapted proportional control, chin-controlled	1,500.00	1,500.00	12
7213322	Adapted proportional control, mini joystick	1,500.00	1,500.00	12
7213323	Mounting bracket for adapted control	350.00	350.00	12
7213324	Adapted control interface	350.00	1,100.00	12
7213325	Mounting bracket for interface	350.00	350.00	12
7213326	Lever extension, ball	58.00	58.00	12
7213327	Lever extension, conicospherical	58.00	58.00	12
7213328	Lever extension, stick	58.00	58.00	12
7213329	Lever extension, T-shaped	58.00	58.00	12
7213330	Lever extension, mushroom	80.00	80.00	12
7213331	Lever extension, U-shaped	95.00	95.00	12
7213332	Trajectory correction system	895.00	895.00	12

7213333	Drive wheel; 31.8 cm (12½ in.) or 35.6 cm (14 in.)	N. C.	70.00	12
7213334	Drive wheel tire, standard pressure inner tube; 31.8 cm $(12\frac{1}{2} \text{ in.})$ or 35.6 cm (14 in.)	N. C.	58.00	1
7213335	Puncture proof tire for drive wheel	17.00	75.00	1
7213337	Caster wheel, with standard pressure inner tube tire; 20.3	N. C.	70.00	12
	cm (8 in.) or 22.9 cm (9 in.)			
7213338	Caster wheel, with puncture proof tire; 20.3 cm (8 in.) or	N. C.	70.00	12
	22.9 cm (9 in.)			
7213339	Suspension independent of wheels	N. C.	29.00	12
7213340	Fork, standard	N. C.	38.00	12

PRICE
(including all
the basic
components)

7213342 POWERED WHEELCHAIR 3,950.00

CATEGORY FMO-GM 2-A-P2 (MID-WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q500M I" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Seat-to-floor height: 41.9 cm to 50.8 cm ($16\frac{1}{2}$ in. to 20 in.) **Frame:** mid-front wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213343	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7213344	Rigid seat base, witdth and depth adjustable; strips of	N. C.	195.00	12
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.);			
	depths of 35. 6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16			
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.),			
	50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7213345	Seat, padded and contoured	N. C.	195.00	1
7213346	Back support, flexible, non tension adjustable; heights of	N. C.	90.00	1
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9			
	cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25			
	in.), 66 cm (26 in.), 68.6 cm (27 in.) or 71.1 cm (28 in.)			
7213347	Back support, flexible, tension adjustable	60.00	150.00	1
7213348	Back support, padded and contoured; heights of 53.3 cm	N. C.	90.00	1
	(21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)			
7213349	Back support upright, straight, height and angle	N. C.	250.00	12
	adjustable; angle-adjustable from 85° to 110° by			
	increments of 4°			
7213350	Push handle, with hand grip	N. C.	90.00	12
7213352	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7213353	Power tilt mechanism	1,200.00	1,200.00	12
7213354	Postural support pelvic belt	N. C.	25.00	12

7213355	T-shaped arm support, short, removable; height-	N. C.	150.00	1
	adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism			
7213356	T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
	from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7213357	U-shaped arm support, short, flip-up and removable;	N. C.	150.00	1
	height-adjustable, from 25.4 cm to 38.1 cm (10 in. to			
	15 in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism		4.50.00	
7213358	U-shaped arm support, long, flip-up and removable; height	N. C.	150.00	1
	adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7213360	I-shaped arm support, flip-up; height-adjustable, from	N. C.	150.00	1
	25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7213361	L-shaped arm support, flip-up; height-adjustable, from 28	N. C.	150.00	1
	cm to 38.1 cm (11 in. to 15 in.) by maximum increments			
7213362	of 2.5 cm (1 in.), with locking mechanism Arm support pad, short, straight	N. C.	15.00	1
7213363	Arm support pad, long, straight	N. C.	15.00	1
7213364	Arm support pad, contoured	5.00	20.00	1
7213365	Arm support pad, gel	70.00	85.00	1
7213366	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°;	N. C.	135.00	12
	removable and pivoting with locking mechanism;			
	adjustable length from 33 cm to 50,8 cm (13 in. to 22 in.)			
7213367	Lower leg support, compensating elevating; with locking	15.00	150.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7213368	Powered elevating lower leg support, individually	365.00	500.00	12
7213369	controlled Powered elevating lower leg support, paired control	365.00	500.00	12
7213370	One-piece powered elevating lower leg support	845.00	980.00	12
7213370	Padded calf support, angle, height and depth adjustable,	70.00	70.00	12
	including flat pad			
7213372	Foot support, separate, flip-up, not angle adjustable,	N. C.	35.00	12
7012272	standard lenght	N. C	25.00	12
7213373	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7213374	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	standard lenght			
7213375	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	extra long			
7213376	Foot support, flip-up, one-piece platform	190.00	225.00	12
7213377	Heel loop, adjustable	5.00 55.00	5.00 55.00	12 12
7213378 7213379	Head support, depth adjustable Contoured cushion for head support, all sizes	35.00	35.00	12
7213380	Back support tension bar	20.00	20.00	12
7213381	Securement for head support for back support tension bar	40.00	40.00	12
	11 11			

	FRAME			
7213382	Front impact guard	12.00	12.00	12
7213382	Lighting systems	425.00	425.00	12
7213384	Reflective devices	N. C.	5.00	12
7213385	Emergency flashers	15.00	15.00	12
7213386	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
7213300	Triangular-snaped flag, orange, 500 cm minimum surface	15.00	13.00	12
7213387	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7213388	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	585.00	12
7213389	Compact control device	N. C.	585.00	12
7213390	Control device operated by an assistant	560.00	560.00	12
7213391	Control device for powered repositionning, for an	100.00	100.00	12
7213392	accessory Control device for powered repositionning, for four	350.00	350.00	12
1213392	accessories	330.00	330.00	12
7213393	Infrared option	N. C.	N. C.	12
7213394	Bluetooth option	N. C.	N. C.	12
7213395	Separate control for powered tilt mechanism	510.00	510.00	12
7213396	Control device support, standard lateral, adjustable front-	N. C.	85.00	12
	rear position			
7213397	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7213398	Control device support, central, flip-up, adjustable front- rear position	65.00	150.00	12
7213399	Controller for multipurpose programmable electronic system	N. C.	575.00	12
7213400	Motor	N. C.	430.00	12
7213401	Electric brake	N. C.	60.00	12
7213402	Battery charger, compatible with group 22NF or 24	N. C.	145.00	12
7210.02	batteries		- 10111	
7213403	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7213404	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7213405	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7213406	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7213407	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7213408	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7213409	Mounting bracket for adapted control	250.00	250.00	12
7213410	Adapted control interface	365.00	950.00	12
7213411	Mounting bracket for interface	400.00	400.00	12
7213412	Lever extension, ball	55.00	55.00	12
7213413	Lever extension, conicospherical	25.00	25.00	12
7213414	Lever extension, stick	55.00	55.00	12
7213415	Lever extension, T-shaped	65.00	65.00	12
7213416	Lever extension, mushroom	55.00	55.00	12
7213417	Lever extension, U-shaped	55.00	55.00	12
7213418	Trajectory correction system	550.00	550.00	12

7213419 7213420	WHEELS AND TIRES Drive wheel; 33 cm (13 in.) Drive wheel tire, standard pressure inner tube; 33 cm (13 in.)	N. C. N. C.	75.00 55.00	12 1
7213421 7213422	in.) Puncture proof tire for drive wheel Caster wheel, with semi-pneumatic tire; 17.8 cm (7 in.)	10.00 N. C.	65.00 25.00	1 12
7213425 7213426	Suspension independent of wheels Fork, standard	N. C. N. C.	120.00 45.00	12 12
		1	PRICE cluding all the basic mponents)	
			1 /	
7213428	POWERED WHEELCHAIR		4,495.00	
7213428	POWERED WHEELCHAIR CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE)			
7213428	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL			
7213428	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PP" DEVICE			
7213428	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PP" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE			
7213428	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PP" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.)			
7213428	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PP" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE			

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213429	Seat-to-back assembly structure; resizable	N. C.	240.00	60
7213430	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.) or 58.4 cm (23 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) or 53.3 cm (21 in.)	N. C.	70.00	60
7213431	Seat, padded and contoured	50.00	120.00	60
7213434	Back support, padded and contoured; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)	N. C.	300.00	60
7213432	Back support, flexible, non tension adjustable; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)	N. C.	300.00	60
7213433	Back support, flexible, tension adjustable	N. C.	300.00	60

7213435	Back support upright, straight, height and angle adjustable; angle-adjustable from 90° to 110° by	N. C.	75.00	60
	maximum increments of 6°)	40700	
7213436 7213438	Push handle, with hand grip Powered reclining back support, including biomechanical	N. C. 700.00	105.00 700.00	60 60
	adjustment			
7213439	Power tilt mechanism	600.00	600.00	60
7213440	Postural support pelvic belt	N. C.	10.00	60
7213441	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213442	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213443	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213444	U-shaped arm support, long, flip-up and removable; height adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213445	U-shaped arm support, flip-up; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213447	L-shaped arm support, swing-away outward; height-adjustable, from 20.3 cm to 27.9 cm (8 in. to 11 in.) or from 27.9 cm to 35.6 cm (11 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213448	Arm support pad, short, straight	N. C.	8.00	60
7213449	Arm support pad, long, straight	N. C.	8.00	60
7213450	Arm support pad, contoured	26.00	34.00	60
7213451	Arm support pad, gel	72.00	80.00	60
7213452	Parallel lower leg support, 60° or 70°; removable and pivoting with locking mechanism; adjustable length from 36.6 cm to 48.3 cm (14 in. to 19 in.) or from 45.7 cm to 58.4 cm (18 in. to 23 in.)	N. C.	100.00	60
7213453	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening	200.00	300.00	60
7213454	system Powered elevating lower leg support, individually controlled	900.00	1,000.00	60
7213455	Powered elevating lower leg support, paired control	900.00	1,000.00	60
7213456	Padded calf support, angle, height and depth adjustable, including flat pad	30.00	30.00	60
7213457	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	10.00	60

7213458	Foot support, separate, flip-up, not angle adjustable, extra long	20.00	30.00	60
7213459	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	25.00	35.00	60
7213460	Foot support, separate, flip-up, angle and depth adjustable, extra long	35.00	45.00	60
7213461	Heel loop, adjustable	5.00	5.00	60
7213462	Head support, depth adjustable	35.00	35.00	60
7213463	Contoured cushion for head support	65.00	65.00	60
7213464	Back support tension bar	5.00	5.00	60
7213465	Securement for head support for back support tension bar	15.00	15.00	60
	FRAME			
7213466	Anti-tip device	N. C.	3.00	60
7213467	Front impact guard	5.00	5.00	60
7213468	Lighting systems	175.00	175.00	60
7213469	Reflective devices	N. C.	50.00	60
7213470	Emergency flashers	150.00	150.00	60
7213471	Triangular-shaped flag, orange, 300 cm ² minimum surface	5.00	5.00	60
7213472	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
	DRIVE SYSTEM			
7213473	Standard control device for multipurpose programmable	N. C.	800.00	60
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
		N. 6	000.00	
7213474	Compact control device	N. C.	800.00	60
7213475	Control device operated by an assistant	200.00	200.00	60
7213476	Control device for powered repositionning, for an accessory	N. C.	N. C.	60
7213477	Control device for powered repositionning, for four	N. C.	N. C.	60
	accessories			
7213478	Infrared option	N. C.	N. C.	60
7213479	Bluetooth option	1,600.00	1,600.00	60
7213480	Separate control for powered tilt mechanism	350.00	350.00	60
7213481	Control device support, standard lateral, adjustable front- rear position	N. C.	200.00	60
7213482	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	200.00	60
7213483	Control device support, central, flip-up, adjustable front-	N. C.	200.00	60
7213484	rear position Controller for multipurpose programmable electronic	N. C.	575.00	60
5010105	system	N. 6	600.00	
7213485	Motor, including electric brake	N. C.	600.00	60
7213487	Battery charger, compatible with group 22NF or 24 batteries	N. C.	130.00	60
7213488	Adapted non-proportional control, cephalic	500.00	500.00	60
7213489	Adapted non-proportional control, chin-controlled	700.00	700.00	60
7213490	Adapted non-proportional control, breath-controlled	500.00	500.00	60
7213491	Adapted proportional control, cephalic	500.00	500.00	60
7213492	Adapted proportional control, chin-controlled	500.00	500.00	60

7213494	Adapted proportional control, mini joystick	2,500.00	2,500.00	60
	Mounting bracket for adapted control	N. C.	N. C.	60
7213495	Adapted control interface	N. C.	800.00	60
7213496	Mounting bracket for interface	100.00	100.00	60
7213497	Lever extension, ball	20.00	20.00	60
7213498	Lever extension, conicospherical	20.00	20.00	60
7213499	Lever extension, stick	15.00	15.00	60
7213500	Lever extension, T-shaped	15.00	15.00	60
7213501	Lever extension, mushroom	15.00	15.00	60
7213502	Lever extension, U-shaped	15.00	15.00	60
7213503	Trajectory correction system	1,000.00	1,000.00	60
	WHEELS AND TIRES			
7213504	Drive wheel; 35.6 cm (14 in.)	N. C.	160.00	60
7213505	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	40.00	60
7213506	(14 in.) Puncture proof tire for drive wheel	35.00	75.00	60
7213508	Caster wheel, with standard pressure inner tube tire or	N. C.	75.00	60
7213300	puncture proof tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	14. C.	73.00	00
7213509	Caster wheel, with standard pressure inner tube tire or puncture proof tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	N. C.	75.00	60
7213510	Suspension independent of wheels	N. C.	100.00	60
7213510	Fork, adjustable height	N. C.	100.00	60
		`	PRICE including all the basic omponents)	
=010510				
7213513	POWERED WHEELCHAIR		4,100.00	
7213513	POWERED WHEELCHAIR CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE)		4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL		4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE)		4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) SUNRISE MEDICAL CANADA INC. "QUICKIE Q500H I" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.)		4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) SUNRISE MEDICAL CANADA INC. "QUICKIE Q500H I" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in	*	4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) SUNRISE MEDICAL CANADA INC. "QUICKIE Q500H I" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.)	(24 in.)	4,100.00	
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) SUNRISE MEDICAL CANADA INC. "QUICKIE Q500H I" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in Frame: mid-rear wheel drive base, overall width ≤ 61 cm (24 in.) ceable separately		
7213513	CATEGORY FMO-GM 2-A-P2 (MID-REAR WHEEL DRIVE) SUNRISE MEDICAL CANADA INC. "QUICKIE Q500H I" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in Frame: mid-rear wheel drive base, overall width ≤ 61 cm (24 in.) ceable separately Unit price of component during device	Unit price for component replacement	Warranty (months)

N. C.

400.00

12

7213514 Seat-to-back assembly structure; resizable

7213515	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	195.00	12
7213516 7213517	Seat, padded and contoured Back support, flexible, non tension adjustable; heights of 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29 in.) or 76.2 cm (30 in.)	N. C. N. C.	195.00 90.00	1 1
7213518	Back support, flexible, tension adjustable	60.00	150.00	1
7213519	Back support, padded and contoured; heights of 53.3 cm (21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)	N. C.	90.00	1
7213520	Back support upright, straight, height and angle adjustable; angle-adjustable from 85° to 110° by increments of 4°	N. C.	250.00	12
7213521	Push handle, with hand grip	N. C.	90.00	12
7213523	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7213524	Power tilt mechanism	1,200.00	1,200.00	12
7213525	Postural support pelvic belt	N. C.	25.00	12
7213526	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism;	N. C.	150.00	1
7213527	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213528	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213529	U-shaped arm support, long, flip-up and removable; height adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213531	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213532	L-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213533	Arm support pad, short, straight	N. C.	15.00	1
7213534	Arm support pad, long, straight	N. C.	15.00	1
7213535	Arm support pad, contoured	5.00	20.00	1
7213536	Arm support pad, gel	70.00	85.00	1

7213537	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°; removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	135.00	12
7213538	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7213539	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7213540	Powered elevating lower leg support, paired control	365.00	500.00	12
7213541	Padded calf support, angle, height and depth adjustable, including flat pad	70.00	70.00	12
7213542	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7213543	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7213544	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7213545	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7213546	Heel loop, adjustable	5.00	5.00	12
7213547	Head support, depth adjustable	55.00	55.00	12
7213548	Contoured cushion for head support, all sizes	35.00	35.00	12
7213549	Back support tension bar	20.00	20.00	12
7213550	Securement for head support for back support tension bar	40.00	40.00	12
	FRAME			
7213551	Anti-tip device	N. C.	12.00	12
7213552	Front impact guard	12.00	12.00	12
7213553	Lighting systems	425.00	425.00	12
7213554	Reflective devices	N. C.	5.00	12
7213555	Emergency flashers	15.00	15.00	12
7213556	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
7213557	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
7213558	DRIVE SYSTEM Standard control device for multipurpose programmable	N. C.	585.00	12
7213336	electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	363.00	12
7213559	Compact control device	N. C.	585.00	12
7213560	Control device operated by an assistant	560.00	560.00	12
7213561	Control device for powered repositionning, for an accessory	100.00	100.00	12
7213562	Control device for powered repositionning, for four accessories	350.00	350.00	12
7213563	Infrared option	N. C.	N. C.	12
7213564	Bluetooth option	N. C.	N. C.	12
7213565	Separate control for powered tilt mechanism	510.00	510.00	12
7213566	Control device support, standard lateral, adjustable front- rear position	N. C.	85.00	12

7213567	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7213568	Control device support, central, flip-up, adjustable front- rear position	65.00	150.00	12
7213569	Controller for multipurpose programmable electronic system	N. C.	575.00	12
7213570	Motor	N. C.	430.00	12
7213571	Electric brake	N. C.	60.00	12
7213572	Battery charger, compatible with group 22NF or 24 batteries	N. C.	145.00	12
7213573	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7213574	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7213575	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7213576	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7213577	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7213578	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7213579	Mounting bracket for adapted control	250.00	250.00	12
7213580	Adapted control interface	365.00	950.00	12
7213581	Mounting bracket for interface	400.00	400.00	12
7213582	Lever extension, ball	55.00	55.00	12
7213583	Lever extension, conicospherical	25.00	25.00	12
7213584	Lever extension, stick	55.00	55.00	12
7213585	Lever extension, T-shaped	65.00	65.00	12
7213586	Lever extension, mushroom	55.00	55.00	12
7213587	Lever extension, U-shaped	55.00	55.00	12
7213588	Trajectory correction system	550.00	550.00	12
	WHEELS AND TIRES			
7213589	Drive wheel; 33 cm (13 in.)	N. C.	75.00	12
7213590	Drive wheel tire, standard pressure inner tube; 33 cm (13 in.)	N. C.	55.00	1
7213591	Puncture proof tire for drive wheel	10.00	65.00	1
7213592	Caster wheel, with semi-pneumatic tire; 22.9 cm (9 in.)	N. C.	25.00	12
7213595	Suspension independent of wheels	N. C.	120.00	12
7213596	Fork, standard	N. C.	45.00	12

PRICE (including all the basic components)

4,495.00

7213598 POWERED WHEELCHAIR

CATEGORY FMO-GM 2-B-P2 (MID-REAR WHEEL DRIVE)

ORTHOFAB INC.

"OASIS PCM" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 136 kg (300 lb.)

Seat-to-floor height: 39,4 cm to 52,1 cm ($15\frac{1}{2}$ in. to $20\frac{1}{2}$ in.) **Frame:** mid-rear wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213599	Seat-to-back assembly structure; resizable	N. C.	240.00	60
7213600	Rigid seat base, witdth and depth adjustable; strips of	N. C.	70.00	60
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2			
	cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm			
	(20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.) or 58.4 cm (23			
	in.);			
	depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17			
	in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) or			
	53.3 cm (21 in.)			
7213601	Seat, padded and contoured	50.00	120.00	60
7213604	Back support, padded and contoured; heights of 45.7 cm	N. C.	300.00	60
	(18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21			
	in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)			
7213602	Back support, flexible, non tension adjustable; heights of	N. C.	300.00	60
	45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3			
	cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm			
5010 600	(24 in.)	N. C.	200.00	(0)
7213603	Back support, flexible, tension adjustable	N. C.	300.00	60
7213605	Back support upright, straight, height and angle	N. C.	75.00	60
	adjustable; angle-adjustable from 90° to 110° by maximum increments of 6°			
7212606		NG	105.00	60
7213606	Push handle, with hand grip	N. C.	105.00	60
7213608	Powered reclining back support, including biomechanical	700.00	700.00	60
7213609	adjustment Power tilt mechanism	600.00	600.00	60
7213610	Postural support pelvic belt	N. C.	10.00	60
/213010	r osturar support pervic beit	1 v. C.	10.00	UU

7213611	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism;	N. C.	110.00	60
7213612	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213613	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213614	U-shaped arm support, long, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213615	U-shaped arm support, flip-up; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213617	L-shaped arm support, swing-away outward; height-adjustable, from 20.3 cm to 27.9 cm (8 in. to 11 in.) or from 27.9 cm to 35.6 cm (11 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213618	Arm support pad, short, straight	N. C.	8.00	60
7213619	Arm support pad, long, straight	N. C.	8.00	60
7213620	Arm support pad, contoured	26.00	34.00	60
7213621	Arm support pad, gel	72.00	80.00	60
7213622	Parallel lower leg support, 60° or 70°; removable and pivoting with locking mechanism; adjustable length from 35.6 cm to 48.3 cm (14 in. to 19 in.) or from 45.7 cm to 58.4 cm (18 in. to 23 in.)	N. C.	100.00	60
7213623	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	200.00	300.00	60
7213624	Powered elevating lower leg support, individually controlled	900.00	1,000.00	60
7213625	Powered elevating lower leg support, paired control	900.00	1,000.00	60
7213626	One-piece powered elevating lower leg support	1,400.00	1,500.00	60
7213627	Padded calf support, angle, height and depth adjustable, including flat pad	30.00	30.00	60
7213628	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	10.00	60
7213629	Foot support, separate, flip-up, not angle adjustable, extra long	20.00	30.00	60
7213630	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	25.00	35.00	60
7213631	Foot support, separate, flip-up, angle and depth adjustable, extra long	35.00	45.00	60
7213632	Foot support, flip-up, one-piece platform	415.00	425.00	60
7213633	Heel loop, adjustable	5.00	5.00	60

7213634	Head support, depth adjustable	35.00	35.00	60
7213635	Contoured cushion for head support	65.00	65.00	60
7213636	Back support tension bar	5.00	5.00	60
7213637	Securement for head support for back support tension bar	15.00	15.00	60
7213037	Securement for near support for onek support tension our	13.00	13.00	00
	FRAME		- 00	
7213638	Front impact guard	5.00	5.00	60
7213639	Lighting systems	175.00	175.00	60
7213640	Reflective devices	N. C.	50.00	60
7213641	Emergency flashers	150.00	150.00	60
7213642	Triangular-shaped flag, orange, 300 cm ² minimum surface	5.00	5.00	60
7213643	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
	DRIVE SYSTEM			
7213644	Standard control device for multipurpose programmable	N. C.	800.00	60
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7213645	Compact control device	N. C.	800.00	60
7213646	Control device operated by an assistant	200.00	200.00	60
7213647	Control device for powered repositionning, for an	N. C.	N. C.	60
7213017	accessory	1	1 6.	00
7213648	Control device for powered repositionning, for four	N. C.	N. C.	60
	accessories			
7213649	Infrared option	N. C.	N. C.	60
7213650	Bluetooth option	1,600.00	1,600.00	60
7213651	Separate control for powered tilt mechanism	350.00	350.00	60
7213652	Control device support, standard lateral, adjustable front- rear position	N. C.	200.00	60
7213653	Control device support, lateral, flip-up with locking	N. C.	200.00	60
	mechanism, adjustable front-rear position			
7213654	Control device support, central, flip-up, adjustable front-	N. C.	200.00	60
	rear position			
7213655	Controller for multipurpose programmable electronic	N. C.	575.00	60
	system			
7213656	Motor, including electric brake	N. C.	600.00	60
7213658	Battery charger, compatible with group 22NF or 24	N. C.	130.00	60
7212650	Adouted way appropriated control combalic	500.00	500.00	60
7213659	Adapted non-proportional control, cephalic		700.00	
7213660	Adapted non-proportional control, chin-controlled	700.00		60
7213661	Adapted non-proportional control, breath-controlled	500.00	500.00	60
7213662	Adapted proportional control, cephalic	500.00	500.00	60
7213663	Adapted proportional control, chin-controlled	500.00	500.00	60
7213664	Adapted proportional control, mini joystick	2,500.00	2,500.00	60
7213665	Mounting bracket for adapted control	N. C.	N. C.	60
7213666	Adapted control interface	N. C.	800.00	60
7213667	Mounting bracket for interface	100.00	100.00	60
7213668	Lever extension, ball	20.00	20.00	60
7213669	Lever extension, conicospherical	20.00	20.00	60
7213670	Lever extension, stick	15.00	15.00	60
7213671	Lever extension, T-shaped	15.00	15.00	60

7213672	Lever extension, mushroom	15.00	15.00	60
7213673	Lever extension, U-shaped	15.00	15.00	60
7213674	Trajectory correction system	1,000.00	1,000.00	60
	WHEELS AND TIRES			
7213675	Drive wheel; 35.6 cm (14 in.)	N. C.	160.00	60
7213676	Drive wheel tire, standard pressure inner tube; 35.6 cm (14 in.)	N. C.	40.00	60
7213677	Puncture proof tire for drive wheel	35.00	75.00	60
7213679	Caster wheel, with standard pressure inner tube tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	N. C.	75.00	60
7213680	Caster wheel, with puncture proof tire; 20.3 cm (8 in.) or 22.9 cm (9 in.)	N. C.	75.00	60
7213681	Suspension independent of wheels	N. C.	100.00	60
7213683	Fork, adjustable height	N. C.	100.00	60
			PRICE	
		(iı	ncluding all	
			the basic	
		co	omponents)	
7213684	POWERED WHEELCHAIR		3,950.00	

CATEGORY FMO-GM 2-B-P2 (MID-FRONT WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q500M MixIE" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Seat-to-floor height: 41.9 cm to 49.5 cm ($16\frac{1}{2}$ in. to $19\frac{1}{2}$ in.) **Frame:** mid-front wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213685	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7213686	Rigid seat base, witdth and depth adjustable; strips of	N. C.	195.00	12
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9			
	cm (22 in.);			
	depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16			
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or			
	50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7213687	Seat, padded and contoured	N. C.	195.00	1

7213688	Back support, flexible, non tension adjustable; heights of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61.0 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.), 68.6 cm (27 in.) or 71.1 cm (28 in.)	N. C.	90.00	1
7213689	Back support, flexible, tension adjustable	60.00	150.00	1
7213690	Back support, padded and contoured; heights of 53.3 cm (21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)	N. C.	90.00	1
7213691	Back support upright, straight, height and angle adjustable; angle-adjustable from 85° to 110° by increments of 4°	N. C.	250.00	12
7213692	Push handle, with hand grip	N.C.	90.00	12
7213694	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7213695	Power tilt mechanism	1,200.00	1,200.00	12
7213696	Postural support pelvic belt	N. C.	25.00	12
7213697	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by	N. C.	150.00	1
	maximum increments of 2.5 cm (1 in.), with locking mechanism			
7213698	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213699	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with	N. C.	150.00	1
	locking mechanism			
7213700	U-shaped arm support, long, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213702	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213703	L-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213704	Arm support pad, short, straight	N. C.	15.00	1
7213705	Arm support pad, long, straight	N. C.	15.00	1
7213706	Arm support pad, contoured	5.00	20.00	1
7213707	Arm support pad, gel	70.00	85.00	1
7213708	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°; removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	135.00	12
7213709	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7213710	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7213711	Powered elevating lower leg support, paired control	365.00	500.00	12
7213712	One-piece powered elevating lower leg support	845.00	980.00	12

7213713	Padded calf support, angle, height and depth adjustable, including flat pad	70.00	70.00	12
7213714	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7213715	Foot support, separate, flip-up, not angle adjustable, extra	N. C.	35.00	12
7213716	long Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7213717	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7213718	Foot support, flip-up, one-piece platform	190.00	225.00	12
7213719	Heel loop, adjustable	5.00	5.00	12
7213719	Head support, depth adjustable	55.00	55.00	12
7213721	Contoured cushion for head support, all sizes	35.00	35.00	12
7213721	Back support tension bar	20.00	20.00	12
7213723	Securement for head support for back support tension bar	40.00	40.00	12
	FRAME			
7213724	Front impact guard	12.00	12.00	12
7213725	Lighting systems	425.00	425.00	12
7213726	Reflective devices	N. C.	5.00	12
7213727	Emergency flashers	15.00	15.00	12
7213728	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
7213729	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7213730	Standard control device for multipurpose programmable	N. C.	585.00	12
,,	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7213731	Compact control device	N. C.	585.00	12
7213732	Control device operated by an assistant	560.00	560.00	12
7213733	Control device for powered repositionning, for an accessory	100.00	100.00	12
7213734	Control device for powered repositionning, for four accessories	350.00	350.00	12
7213735	Infrared option	N. C.	N. C.	12
7213736	Bluetooth option	N. C.	N. C.	12
7213737	Separate control for powered tilt mechanism	510.00	510.00	12
7213738	Control device support, standard lateral, adjustable front-	N. C.	85.00	12
,,	rear position			
7213739	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7213740	Control device support, central, flip-up, adjustable front-	65.00	150.00	12
7213741	rear position Controller for multipurpose programmable electronic	N. C.	575.00	12
7213742	system Motor	N. C.	430.00	12
7213742	Electric brake	N. C. N. C.	60.00	12
7213743	Battery charger, compatible with group 22NF or 24	N. C. N. C.	145.00	12
1413144	batteries	IV. C.	17J.UU	12

7213745	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12		
7213746	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12		
7213747	Adapted non-proportional control, breath-controlled	850.00	850.00	12		
7213748	Adapted proportional control, cephalic	1,500.00	1,500.00	12		
7213749	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12		
7213750	Adapted proportional control, mini joystick	1,800.00	1,800.00	12		
7213750	Mounting bracket for adapted control	250.00	250.00	12		
7213751	Adapted control interface	365.00	950.00	12		
7213752	Mounting bracket for interface	400.00	400.00	12		
7213754	Lever extension, ball	55.00	55.00	12		
7213755	Lever extension, conicospherical	25.00	25.00	12		
7213756	Lever extension, stick	55.00	55.00	12		
7213757	Lever extension, T-shaped	65.00	65.00	12		
7213757	Lever extension, mushroom	55.00	55.00	12		
7213759	Lever extension, U-shaped	55.00	55.00	12		
7213760	Trajectory correction system	550.00	550.00	12		
/213/00	Trajectory correction system	330.00	330.00	12		
	WHEELS AND TIRES					
7213761	Drive wheel; 33 cm (13 in.)	N. C.	75.00	12		
7213762	Drive wheel tire, standard pressure inner tube; 33 cm (13	N. C.	55.00	1		
,210,02	in.)	1	20.00	-		
7213763	Puncture proof tire for drive wheel	10.00	65.00	1		
7213764	Caster wheel, with semi-pneumatic tire; 17.8 cm (7 in.)	N. C.	25.00	12		
7213767	Suspension independent of wheels	N. C.	120.00	12		
7213768	Fork, standard	N. C.	45.00	12		
			PRICE (including all the basic components)			
7213770	POWERED WHEELCHAIR		4,495.00			
	CATEGORY FMO-GM 2-B-P2 (MID-REAR WHEEL					
	DRIVE)					
	ORTHOFAB INC.					
	"OASIS PC" DEVICE					
	TECHNICAL SPECIFICATIONS OF THE DEVICE					
	Maximum weight capacity: 136 kg (300 lb.)					
	Seat-to-floor height: 39,4 cm to 49,6 cm (15½ in. to 19½ in.)					
	Frame: mid-rear wheel drive base, overall width ≤ 61 cm (* *				
	Drive system: manual freewheel lever; control cable replace	ceable separately				
		I Init maile C				
		Unit price of component	Unit price for	Warranty		
				warraniV		
	BASIC AND OPTIONAL COMPONENTS	•	component	•		
	BASIC AND OPTIONAL COMPONENTS	during device purchase	component replacement	(months)		

N. C.

240.00

60

BODY SUPPORT SYSTEM

7213771

Seat-to-back assembly structure; resizable

7213772	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.) or 58.4 cm (23 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) or 53.3 cm (21 in.)	N. C.	70.00	60
7213773	Seat, padded and contoured	50.00	120.00	60
7213776	Back support, padded and contoured; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61.0 cm (24 in.)	N. C.	300.00	60
7213774	Back support, flexible, non tension adjustable; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61.0 cm (24 in.)	N. C.	300.00	60
7213775	Back support, flexible, tension adjustable	N. C.	300.00	60
7213777	Back support upright, straight, height and angle adjustable; angle-adjustable from 90° to 110° by maximum increments of 6°	N. C.	75.00	60
7213778	Push handle, with hand grip	N. C.	105.00	60
7213780	Powered reclining back support, including biomechanical adjustment	700.00	700.00	60
7213781	Power tilt mechanism	600.00	600.00	60
7213782	Postural support pelvic belt	N. C.	10.00	60
7213783	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213784	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213785	U-shaped arm support, short, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213786	U-shaped arm support, long, flip-up and removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213787	U-shaped arm support, flip-up; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213789	L-shaped arm support, swing-away outward; height-adjustable, from 20.3 cm to 27.9 cm (8 in. to 11 in.) or from 27.9 cm to 35.6 cm (11 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7213790	Arm support pad, short, straight	N. C.	8.00	60

7213791	Arm support pad, long, straight	N. C.	8.00	60
7213792	Arm support pad, contoured	26.00	34.00	60
7213793	Arm support pad, gel	72.00	80.00	60
7213794	Parallel lower leg support, 60° or 70°; removable and	N. C.	100.00	60
	pivoting with locking mechanism; adjustable from			
	35.6 cm to 48.3 cm (14 in. to 19 in.) or from 45.7 cm to			
	58.4 cm (18 in. to 23 in.);			
	or 70°; removable and pivoting with locking mechanism;			
	adjustable length from 25.4 cm to 35.6 cm (10 in. to 14			
	in.), from 35.6 cm to 48.3 cm (14 in. to 19 in.) or from			
	45.7 cm to 58.4 cm (18 in. to 23 in.)			
7212705	T 1 2 2 2 1 2 21 1 1	200.00	200.00	60
7213795	Lower leg support, compensating elevating; with locking	200.00	300.00	60
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7213796	Powered elevating lower leg support, individually	900.00	1,000.00	60
	controlled			
7213797	Powered elevating lower leg support, paired control	900.00	1,000.00	60
7213798	Padded calf support, angle, height and depth adjustable,	30.00	30.00	60
	including flat pad			
7213799	Foot support, separate, flip-up, not angle adjustable,	N. C.	10.00	60
	standard lenght			
7213800	Foot support, separate, flip-up, not angle adjustable, extra	20.00	30.00	60
	long			
7213801	Foot support, separate, flip-up, angle and depth adjustable,	25.00	35.00	60
	standard lenght			
7213802	Foot support, separate, flip-up, angle and depth adjustable,	35.00	45.00	60
	extra long			
7213803	Heel loop, adjustable	5.00	5.00	60
7213804	Head support, depth adjustable	35.00	35.00	60
		65.00	65.00	
7213805	Contoured cushion for head support, all sizes			60
7213806	Back support tension bar	5.00	5.00	60
7213807	Securement for head support for back support tension bar	15.00	15.00	60
	FRAME			
7213808	Anti-tip device	N. C.	3.00	60
7213809	Front impact guard	5.00	5.00	60
7213810	Lighting systems	175.00	175.00	60
7213811	Reflective devices	N. C.	50.00	60
7213811	Emergency flashers	150.00	150.00	60
		5.00	5.00	60
7213813	Triangular-shaped flag, orange, 300 cm ² minimum surface	3.00	5.00	00
7213814	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
/213014	Securement points for strap-type fiedowns for transport	Ν. C.	π. ο.	00
	DRIVE SYSTEM			
7213815	Standard control device for multipurpose programmable	N. C.	800.00	60
,215016	electronics; drive control device; toggle or push switches	1	000.00	00
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7213816	Compact control device	N. C.	800.00	60
7213817	Control device operated by an assistant	200.00	200.00	60

7213818	Control device for powered repositionning, for an	N. C.	N. C.	60
7012010	accessory	N. C	N. C	60
7213819	Control device for powered repositionning, for four	N. C.	N. C.	60
7213820	accessories Infrared option	N. C.	N.C	60
7213820	Bluetooth option	1,600.00	N. C. 1,600.00	60
7213821	Separate control for powered tilt mechanism	350.00	350.00	60
7213822	Control device support, standard lateral, adjustable front-	N. C.	200.00	60
7213623	rear position	IV. C.	200.00	00
7213824	Control device support, lateral, flip-up with locking	N. C.	200.00	60
/213024	mechanism, adjustable front-rear position	14. C.	200.00	00
	•			
7213825	Control device support, central, flip-up, adjustable front-	N. C.	200.00	60
701000 6	rear position	N. C	575.00	
7213826	Controller for multipurpose programmable electronic	N. C.	575.00	60
7012027	system	NG	(00.00	(0
7213827	Motor, including electric brake	N. C.	600.00	60
7213829	Battery charger, compatible with 22NF or 24 batteries	N. C.	130.00	60
7213830	Adapted non-proportional control, cephalic	500.00	500.00	60
7213831	Adapted non-proportional control, chin-controlled	700.00	700.00	60
	1 1	500.00	500.00	60
7213832	Adapted non-proportional control, breath-controlled			
7213833	Adapted proportional control, cephalic	500.00	500.00	60
7213834	Adapted proportional control, chin-controlled	500.00	500.00	60
7213835	Adapted proportional control, mini joystick	2,500.00	2,500.00	60
7213836	Mounting bracket for adapted control	N. C.	N. C.	60
7213837	Adapted control interface	N. C.	800.00	60
7213838	Mounting bracket for interface	100.00	100.00	60
7213839	Lever extension, ball	20.00	20.00	60
7213840	Lever extension, conicospherical	20.00	20.00	60
7213841	Lever extension, stick	15.00	15.00	60
7213842	Lever extension, T-shaped	15.00	15.00	60
7213843	Lever extension, mushroom	15.00	15.00	60
7213844	Lever extension, U-shaped	15.00	15.00	60
7213845	Trajectory correction system	1,000.00	1,000.00	60
	WHEELS AND TIRES			
7213846	Drive wheel; 35.6 cm (14 in.)	N. C.	160.00	60
7213847	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	40.00	60
	(14 in.)			
7213848	Puncture proof tire for drive wheel	35.00	75.00	60
7213850	Caster wheel, with standard pressure inner tube tire; 20.3	N. C.	75.00	60
	cm (8 in.) or 22.9 cm (9 in.)			
7213851	Caster wheel, with puncture proof tire; 20.3 cm (8 in.) or	N. C.	75.00	60
	22.9 cm (9 in.)			
7213852	Suspension independent of wheels	N. C.	100.00	60
7213854	Fork, adjustable height	N. C.	100.00	60
			PRICE	
		(i	ncluding all	
			the basic	
7212055		С	omponents)	

CATEGORY FMO-GM 2-B-P2 (MID-REAR WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q500H MixIE" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Seat-to-floor height: 41.9 cm to 50.8 cm ($16\frac{1}{2}$ in. to 20 in.) **Frame:** mid-rear wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213856	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7213857	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	195.00	12
7213858	Seat, padded and contoured	N. C.	195.00	1
7213859	Back support, flexible, non tension adjustable; heights of 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29 in.) or 76.2 cm (30 in.)	N. C.	90.00	1
7213860	Back support, flexible, tension adjustable	60.00	150.00	1
7213861	Back support, padded and contoured; heights of 53.3 cm (21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)	N. C.	90.00	1
7213862	Back support upright, straight, height and angle adjustable; angle-adjustable from 85° to 110° by increments of 4°	N. C.	250.00	12
7213863	Push handle, with hand grip	N. C.	90.00	12
7213865	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7213866	Power tilt mechanism	1,200.00	1,200.00	12
7213867	Postural support pelvic belt	N. C.	25.00	12
7213868	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213869	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1

7213870	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213871	U-shaped arm support, long, flip-up and removable; height adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213873	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213874	L-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213875	Arm support pad, short, straight	N. C.	15.00	1
7213876	Arm support pad, long, straight	N. C.	15.00	1
7213877	Arm support pad, contoured	5.00	20.00	1
7213878	Arm support pad, gel	70.00	85.00	1
7213879	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°; removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	135.00	12
7213880	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7213881	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7213882	Powered elevating lower leg support, paired control	365.00	500.00	12
7213883	Padded calf support, angle, height and depth adjustable, including flat pad	70.00	70.00	12
7213884	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7213885	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7213886	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7213887	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7213888	Heel loop, adjustable	5.00	5.00	12
7213889	Head support, depth adjustable	55.00	55.00	12
7213890	Contoured cushion for head support, all sizes	35.00	35.00	12
7213891	Back support tension bar	20.00	20.00	12
7213892	Securement for head support for back support tension bar	40.00	40.00	12
7213893	FRAME Anti-tip device	N. C.	12.00	12
7213894	Front impact guard	12.00	12.00	12
7213895	Lighting systems	425.00	425.00	12
7213896	Reflective devices	N. C.	5.00	12
7213897	Emergency flashers	15.00	15.00	12
7213898	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12

7213899	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
7213900	DRIVE SYSTEM Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	585.00	12
7213901 7213902 7213903	Compact control device Control device operated by an assistant Control device for powered repositionning, for an	N. C. 560.00 100.00	585.00 560.00 100.00	12 12 12
7213903	accessory Control device for powered repositionning, for four	350.00	350.00	12
7213905	accessories Infrared option	N. C.	N. C.	12
7213906	Bluetooth option	N. C.	N. C.	12
7213907	Separate control for powered tilt mechanism	510.00	510.00	12
7213908	Control device support, standard lateral, adjustable front- rear position	N. C.	85.00	12
7213909	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7213910	Control device support, central, flip-up, adjustable front- rear position	65.00	150.00	12
7213911	Controller for multipurpose programmable electronic system	N. C.	575.00	12
7213912	Motor	N. C.	430.00	12
7213913	Electric brake	N. C.	60.00	12
7213914	Battery charger, compatible with group 22NF or 24 batteries	N. C.	145.00	12
7213915	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7213916	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7213917	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7213918	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7213919	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7213920	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7213921	Mounting bracket for adapted control	250.00	250.00	12
7213922	Adapted control interface	365.00	950.00	12
7213923	Mounting bracket for interface	400.00	400.00	12
7213924	Lever extension, ball	55.00	55.00	12
7213925	Lever extension, conicospherical	25.00	25.00	12
7213926	Lever extension, stick	55.00	55.00	12
7213927	Lever extension, T-shaped	65.00	65.00	12
7213928	Lever extension, mushroom	55.00	55.00	12
7213929	Lever extension, U-shaped	55.00	55.00	12
7213930	Trajectory correction system	550.00	550.00	12
7213931	WHEELS AND TIRES Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7213931	Drive wheel tire, standard pressure inner tube; 35.6 cm (14 in.)	N. C.	55.00	1
7213933	Puncture proof tire for drive wheel	10.00	65.00	1
7213934	Caster wheel, with semi-pneumatic tire; 22.9 cm (9 in.)	N. C.	25.00	12
7213937	Suspension independent of wheels	N. C.	120.00	12

7213938 Fork, standard N. C. 45.00 12

PRICE (including all the basic components)

7213940 POWERED WHEELCHAIR 4,100.00

CATEGORY FMO-GM 2-C-P2 (MID-FRONT WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q700M" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Seat-to-floor height: 41.9 cm to 50.8 cm ($16\frac{1}{2}$ in. to 20 in.) **Frame:** mid-front wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7213941	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7213942	Rigid seat base, witdth and depth adjustable; strips of	N. C.	195.00	12
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.);			
	depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16			
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or			
	50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7213943	Seet modded and contoured	N. C.	195.00	1
7213943	Seat, padded and contoured Back support, flexible, non tension adjustable; heights of	N. C. N. C.	90.00	1
1213944	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),	N. C.	90.00	1
	48.3 cm (19 in.), 50.8 cm (20 in.), 55.9 cm (22 in.),			
	58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm			
	(26 in.), 68.6 cm (27 in.) or 71.1 cm (28 in.)			
7213945	Back support, flexible, tension adjustable	60.00	150.00	1
7213946	Back support, padded and contoured; heights of 53.3 cm	N. C.	90.00	1
	(21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)			
7213947	Back support upright, straight, height and angle	N. C.	250.00	12
	adjustable; angle-adjustable from 85° to 110° by			
	increments of 4°			
7213948	Push handle, with hand grip	N. C.	90.00	12
7213950	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7213951	Power tilt mechanism	1,200.00	1,200.00	12
7213951	Postural support pelvic belt	N. C.	25.00	12
1213732	1 ostatul support pervie ooti	14. C.	25.00	12

7213953	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking	N. C.	150.00	1
7213954	mechanism T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
	increments of 2.5 cm (1 in.), with locking incenamsin			
7213955	U-shaped arm support, short, flip-up and removable;	N. C.	150.00	1
	height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism			
7213956	U-shaped arm support, long, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213958	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum	N. C.	150.00	1
	increments of 2.5 cm (1 in.), with locking mechanism			_
7213959	L-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (110 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7213960	Arm support pad, short, straight	N. C.	15.00	1
7213961	Arm support pad, long, straight	N. C. N. C.	15.00	1
7213961	Arm support pad, tong, straight Arm support pad, contoured	5.00	20.00	1
7213962	Arm support pad, contoured Arm support pad, gel	70.00	85.00	1
7213963	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°;	70.00 N. C.	135.00	12
/213904	removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	133.00	12
7213965	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7213966	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7213967	Powered elevating lower leg support, paired control	365.00	500.00	12
7213968	One-piece powered elevating lower leg support	845.00	980.00	12
7213969	Padded calf support, angle, height and depth adjustable, including flat pad	70.00	70.00	12
7213970	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7213971	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7213972	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7213973	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7213974	Foot support, flip-up, one-piece platform	190.00	225.00	12
7213975	Heel loop, adjustable	5.00	5.00	12
7213976	Head support, depth adjustable	55.00	55.00	12
7213977	Contoured cushion for head support, all sizes	35.00	35.00	12
7213978	Back support tension bar	20.00	20.00	12
7213979	Securement for head support for back support tension bar	40.00	40.00	12

	FRAME			
7213980	Front impact guard	12.00	12.00	12
7213980	Lighting systems	N. C.	425.00	12
7213982	Reflective devices	N. C.	5.00	12
7213983	Emergency flashers	15.00	15.00	12
7213984		15.00	15.00	12
7213904	Triangular-shaped flag, orange, 300 cm ² minimum surface	13.00	13.00	12
7213985	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7213986	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches	N. C.	585.00	12
	the functions: start-stop, horn and function selection; battery charge level indicator			
7213987	Compact control device	N. C.	585.00	12
7213988	Control device operated by an assistant	560.00	560.00	12
7213989	Control device for powered repositionning, for an accessory	100.00	100.00	12
7213990	Control device for powered repositionning, for four	350.00	350.00	12
	accessories			
7213991	Infrared option	N. C.	N. C.	12
7213992	Bluetooth option	N. C.	N. C.	12
7213993	Separate control for powered tilt mechanism	510.00	510.00	12
7213994	Control device support, standard lateral, adjustable front- rear position	N. C.	85.00	12
7213995	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7213996	Control device support, central, flip-up, adjustable front- rear position	65.00	150.00	12
7213997	Controller for multipurpose programmable electronic system	N. C.	575.00	12
7213998	Motor	N. C.	430.00	12
7213999	Electric brake	N. C.	60.00	12
7214000	Battery charger, compatible with group 22NF or 24	N. C.	145.00	12
721 1000	batteries	14. C.	113.00	12
7214001	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7214002	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7214003	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7214004	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7214005	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7214006	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7214007	Mounting bracket for adapted control	250.00	250.00	12
7214008	Adapted control interface	365.00	950.00	12
7214009	Mounting bracket for interface	400.00	400.00	12
7214010	Lever extension, ball	55.00	55.00	12
7214011	Lever extension, conicospherical	25.00	25.00	12
7214011	Lever extension, stick	55.00	55.00	12
7214012	Lever extension, T-shaped	65.00	65.00	12
7214013	Lever extension, mushroom	55.00	55.00	12
7214014	Lever extension, U-shaped	55.00	55.00	12
7214013	Trajectory correction system	550.00	550.00	12
,217010	rajectory correction system	550.00	220.00	12

	WHEELS AND TIRES			
7214017	Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7214018	Drive wheel tire, standard pressure inner tube; 35.6 cm (14 in.)	N. C.	55.00	1
7214019	Puncture proof tire for drive wheel	10.00	65.00	1
7214020	Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.)	N. C.	25.00	12
7214023	Suspension independent of wheels	N. C.	120.00	12
7214024	Fork, standard	N. C.	45.00	12
			PRICE (including all the basic components)	
7214026	POWERED WHEELCHAIR		4,100.00	
	CATEGORY FMO-GM 2-C-P2 (MID-REAR WHEEL DRIVE)			
	SUNRISE MEDICAL CANADA INC.			
	"QUICKIE Q500H" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE			
	Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in. Frame: mid-rear wheel drive base, overall width ≤ 61 cm (Drive system: manual freewheel lever; control cable replacements.)	24 in.)		
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7214027 7214028	Seat-to-back assembly structure; resizable Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16	N. C. N. C.	400.00 195.00	12 12
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7214029		N. C.	195.00	1

60.00

N.C.

150.00

90.00

1

(26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29

Back support, padded and contoured; heights of 53.3 cm

Back support, flexible, tension adjustable

(21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)

in.) or 76.2 cm (30 in.)

7214031

7214032

7214033	Back support upright, straight, height and angle adjustable; angle-adjustable from 85° to 110° by increments of 4°	N. C.	250.00	12
7214024		N. C	00.00	12
7214034 7214036	Push handle, with hand grip Powered reclining back support, including biomechanical	N. C. 1,250.00	90.00 1,250.00	12 12
	adjustment			
7214037	Power tilt mechanism	1,200.00	1,200.00	12
7214038	Postural support pelvic belt	N. C.	25.00	12
7214039	T-shaped arm support, short, removable; height-	N. C.	150.00	1
	adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7214040	T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
	from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7214041	U-shaped arm support, short, flip-up and removable;	N. C.	150.00	1
	height-adjustable, from 25.4 cm to 38.1 cm (10 in. to			
	15 in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism			
7214042		NC	150.00	1
7214042	U-shaped arm support, long, flip-up and removable; height	N. C.	150.00	1
	adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by			
	maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7214044	I-shaped arm support, flip-up; height-adjustable, from	N. C.	150.00	1
	25,4 cm to 38.1 cm (10 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7214045	L-shaped arm support, flip-up; height-adjustable, from	N. C.	150.00	1
7214043		IV. C.	150.00	1
	25,4 cm to 38.1 cm (10 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7214046	Arm support pad, short, straight	N. C.	15.00	1
7214047	Arm support pad, long, straight	N. C.	15.00	1
7214048	Arm support pad, contoured	5.00	20.00	1
7214049	Arm support pad, gel	70.00	85.00	1
7214050	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°;	N. C.	135.00	12
	removable and pivoting with locking mechanism;			
	adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)			
	adjustacio lengui nom 33 em to 3010 em (13 m. to 22 m.)			
7014051	war and the second of the seco	15.00	150.00	10
7214051	Lower leg support, compensating elevating; with locking	15.00	150.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7214052	Powered elevating lower leg support, individually	365.00	500.00	12
	controlled			
7214053	Powered elevating lower leg support, paired control	365.00	500.00	12
7214054	Padded calf support, angle, height and depth adjustable,	70.00	70.00	12
/214034	including flat pad	70.00	70.00	12
7214055		N. C	25.00	12
7214055	Foot support, separate, flip-up, not angle adjustable,	N. C.	35.00	12
	standard lenght			
7214056	Foot support, separate, flip-up, not angle adjustable, extra	N. C.	35.00	12
	long			
7214057	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	standard lenght			
7214058	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	extra long			

7214059	Heel loop, adjustable	5.00	5.00	12
7214060	Head support, depth adjustable	55.00	55.00	12
7214061	Contoured cushion for head support, all sizes	35.00	35.00	12
7214062	Back support tension bar	20.00	20.00	12
7214063		40.00	40.00	12
/214003	Securement for head support for back support tension bar	40.00	40.00	12
	FRAME			
7214064	Anti-tip device	N. C.	12.00	12
7214065	Front impact guard	12.00	12.00	12
7214066	Lighting systems	N. C.	425.00	12
7214067	Reflective devices	N. C.	5.00	12
7214068	Emergency flashers	15.00	15.00	12
7214069	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
7211005	Triangular-shaped hag, orange, 500 cm minimum surface	13.00	13.00	12
7214070	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7214071	Standard control device for multipurpose programmable	N. C.	585.00	12
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
	, ,			
7214072	Compact control device	N. C.	585.00	12
7214073	Control device operated by an assistant	560.00	560.00	12
7214074	Control device for powered repositionning, for an	100.00	100.00	12
	accessory			
7214075	Control device for powered repositionning, for four	350.00	350.00	12
	accessories			
7214076	Infrared option	N. C.	N. C.	12
7214077	Bluetooth option	N. C.	N. C.	12
7214078	Separate control for powered tilt mechanism	510.00	510.00	12
7214079	Control device support, standard lateral, adjustable front-	N. C.	85.00	12
	rear position			
7214080	Control device support, lateral, flip-up with locking	N. C.	85.00	12
	mechanism, adjustable front-rear position			
7214081	Control device support, central, flip-up, adjustable front-	65.00	150.00	12
,21.001	rear position			
7214082	Controller for multipurpose programmable electronic	N. C.	575.00	12
7211002	system	11. 0.	272.00	12
7214083	Motor	N. C.	430.00	12
7214084	Electric brake	N. C.	60.00	12
7214084	Battery charger, compatible with group 22NF or 24	N. C.	145.00	12
7214003	battery charger, compatible with group 22141 of 24	N. C.	145.00	12
7214086	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7214087	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7214088	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7214089	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7214090	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7214091	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7214092	Mounting bracket for adapted control	250.00	250.00	12
7214093	Adapted control interface	365.00	950.00	12
7214094	Mounting bracket for interface	400.00	400.00	12
7214095	Lever extension, ball	55.00	55.00	12

7214096	Lever extension, conicospherical	25.00	25.00	12
7214097	Lever extension, stick	55.00	55.00	12
7214098	Lever extension, T-shaped	65.00	65.00	12
7214099	Lever extension, mushroom	55.00	55.00	12
7214100	Lever extension, U-shaped	55.00	55.00	12
7214101	Trajectory correction system	550.00	550.00	12
	WHEELS AND TIRES			
7214102	Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7214103	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	55.00	1
	(14 in.)			
7214104	Puncture proof tire for drive wheel	10.00	65.00	1
7214105	Caster wheel, with semi-pneumatic tire; 22.9 cm (9 in.)	N. C.	25.00	12
7214108	Suspension independent of wheels	N. C.	120.00	12
7214109	Fork, standard	N. C.	45.00	12

PRICE
(including all
the basic
components)

7214111 POWERED WHEELCHAIR 4,600.00

CATEGORY FMO-GM 3-B-P2 (MID-FRONT WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q700M HD-MixIE" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 159 kg (350 lb.)

Seat-to-floor height: 41.9 cm to 50.8 cm ($16\frac{1}{2}$ in. to 20 in.) **Frame:** mid-front wheel drive base, overall width ≤ 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7214112	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7214113	Rigid seat base, witdth and depth adjustable; strips of	N. C.	195.00	12
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9			
	cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.);			
	depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16			
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.),			
	50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7214114	Seat, padded and contoured	N. C.	195.00	1
7214115	Back support, flexible, non tension adjustable; heights of	N. C.	90.00	1
,21,110	50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.),		,	_
	58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm			
	(26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29			
	in.) or 76.2 cm (30 in.)			
7214116	Back support, flexible, tension adjustable	60.00	150.00	1
7214117	Back support, padded and contoured; heights of 53.3 cm	N. C.	90.00	1
	(21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)			
7214118	Back support upright, straight, height and angle	N. C.	250.00	12
	adjustable; angle-adjustable from 85° to 110° by			
	increments of 4°			
7214119	Push handle, with hand grip	N. C.	90.00	12
7214121	Powered reclining back support, including biomechanical	1,250.00	1,250.00	12
	adjustment			
7214122	Power tilt mechanism	1,200.00	1,200.00	12
7214123	Postural support pelvic belt	N. C.	25.00	12

7214124	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214125	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214126	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214127	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214129	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214130	L-shaped arm support, flip-up height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214131	Arm support pad, short, straight	N. C.	15.00	1
7214132	Arm support pad, long, straight	N. C.	15.00	1
7214133	Arm support pad, contoured	5.00	20.00	1
7214134	Arm support pad, gel	70.00	85.00	1
7214135	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°; removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	135.00	12
7214136	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7214137	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7214138	Powered elevating lower leg support, paired control	365.00	500.00	12
7214139	One-piece powered elevating lower leg support	845.00	980.00	12
7214140	Padded calf support, angle, height and depth adjustable, including flat	70.00	70.00	12
7214141	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7214142	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7214143	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7214144	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7214145	Foot support, flip-up, one-piece platform	190.00	225.00	12
7214146	Heel loop, adjustable	5.00	5.00	12
7214147	Head support, depth adjustable	55.00	55.00	12
7214148	Contoured cushion for head support, all sizes	35.00	35.00	12
7214149	Back support tension bar	20.00	20.00	12
7214150	Securement for head support for back support tension bar	40.00	40.00	12

	FRAME			
7214151	Front impact guard	12.00	12.00	12
7214151	Lighting systems	425.00	425.00	12
7214152	Reflective devices	N. C.	5.00	12
7214153	Emergency flashers	15.00	15.00	12
7214154		15.00	15.00	12
7214133	Triangular-shaped flag, orange, 300 cm ² minimum surface	13.00	13.00	12
7214156	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7214157	Standard control device for multipurpose programmable	N. C.	585.00	12
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7214158	Compact control device	N. C.	585.00	12
7214159	Control device operated by an assistant	560.00	560.00	12
7214160	Control device for powered repositionning, for an	100.00	100.00	12
	accessory			
7214161	Control device for powered repositionning, for four	350.00	350.00	12
	accessories			
7214162	Infrared option	N. C.	N. C.	12
7214163	Bluetooth option	N. C.	N. C.	12
7214164	Separate control for powered tilt mechanism	510.00	510.00	12
7214165	Control device support, standard lateral, adjustable front- rear position	N. C.	85.00	12
7214166	Control device support, lateral, flip-up with locking	N. C.	85.00	12
	mechanism, adjustable front-rear position			
7214167	Control device support, central, flip-up, adjustable front-	65.00	150.00	12
	rear position			
7214168	Controller for multipurpose programmable electronic	N. C.	575.00	12
	system			
7214169	Motor	N. C.	430.00	12
7214170	Electric brake	N. C.	60.00	12
7214171	Battery charger, compatible with group 22NF or 24	N. C.	145.00	12
	batteries			
7214172	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7214173	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7214174	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7214175	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7214176	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7214177	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7214178	Mounting bracket for adapted control	250.00	250.00	12
7214179	Adapted control interface	365.00	950.00	12
7214180	Mounting bracket for interface	400.00	400.00	12
7214181	Lever extension, ball	55.00	55.00	12
7214182	Lever extension, conicospherical	25.00	25.00	12
7214183	Lever extension, stick	55.00	55.00	12
7214184	Lever extension, T-shaped	65.00	65.00	12
7214185	Lever extension, mushroom	55.00	55.00	12
7214186	Lever extension, U-shaped	55.00	55.00	12
7214187	Trajectory correction system	550.00	550.00	12

	WHEELS AND TIRES			
7214188	Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7214189	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	55.00	1
	(14 in.)			
7214190	Puncture proof tire for drive wheel	10.00	65.00	1
7214191	Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.)	N. C.	25.00	12
7214194	Suspension independent of wheels	N. C.	120.00	12
7214195	Fork, standard	N. C.	45.00	12
			PRICE	
		(in	cluding all	
		1	the basic	
		co	mponents)	
7214197	POWERED WHEELCHAIR		mponents) 4,495.00	
7214197	POWERED WHEELCHAIR CATEGORY FMO-GM 3-B-P2 (MID-REAR WHEEL DRIVE)		•	
7214197	CATEGORY FMO-GM 3-B-P2 (MID-REAR WHEEL		•	
7214197	CATEGORY FMO-GM 3-B-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PC-03" DEVICE		•	
7214197	CATEGORY FMO-GM 3-B-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PC-03" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE		•	
7214197	CATEGORY FMO-GM 3-B-P2 (MID-REAR WHEEL DRIVE) ORTHOFAB INC. "OASIS PC-03" DEVICE		•	

Frame: mid-rear wheel drive base, overall width \leq 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7214198	Seat-to-back assembly structure; resizable	N. C.	240.00	60
7214199	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.) or 58.4 cm (23 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) or 53.3 cm (21 in.)	N. C.	70.00	60
7214200	Seat, padded and contoured	50.00	120.00	60
7214203	Back support, padded and contoured; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)	N. C.	300.00	60
7214201	Back support, flexible, non tension adjustable; heights of 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)	N. C.	300.00	60
7214202	Back support, flexible, tension adjustable	N. C.	300.00	60

7214204	Back support upright, straight, height and angle adjustable; angle-adjustable from 90° to 110° by maximum increments of 6°	N. C.	75.00	60
7214205	Push handle, with hand grip	N. C.	105.00	60
7214207	Powered reclining back support, including biomechanical adjustment	700.00	700.00	60
7214208	Power tilt mechanism	600.00	600.00	60
7214209	Postural support pelvic belt	N. C.	10.00	60
7214210	T-shaped arm support, short, removable; height-	N. C.	110.00	60
7214211	adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in) by maximum increments of	N. C.	110.00	60
	2.5 cm (1 in.), with locking mechanism			
7214212	U-shaped arm support, short, flip-up and removable; height-adjustable, 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum	N. C.	110.00	60
7214213	increments of 2.5 cm (1 in.), with locking mechanism U-shaped arm support, long, flip-up and removable; height adjustable, 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7214214	U-shaped arm support, flip-up; height-adjustable, from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7214216	L-shaped arm support, swing-away outward; height-adjustable, from 20.3 cm to 28 cm (8 in. to 11 in.) or from 28 cm to 35.6 cm (11 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7214217	Arm support pad, short, straight	N. C.	8.00	60
7214218	Arm support pad, long, straight	N. C.	8.00	60
7214219	Arm support pad, contoured	26.00	34.00	60
7214220	Arm support pad, gel	72.00	80.00	60
7214221	Parallel lower leg support, 60° or 70°; removable and pivoting with locking mechanism; adjustable length from 35.6 cm to 48.3cm (14 in. to 19 in.) or from 45.7 cm to 58,4 cm (18 in. to 23 in.)	N. C.	100.00	60
7214222	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	200.00	300.00	60
7214223	Powered elevating lower leg support, individually	900.00	1,000.00	60
7214224	Powered elevating lower leg support, paired control	900.00	1,000.00	60
7214225	Padded calf support, angle, height and depth adjustable, including flat or contoured pad	30.00	30.00	60
7214226	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	10.00	60
7214227	Foot support, separate, flip-up, not angle adjustable, extra long	20.00	30.00	60

7214228	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	25.00	35.00	60
7214229	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	35.00	45.00	60
7214230	Heel loop, adjustable	5.00	5.00	60
7214231	Head support, depth adjustable	35.00	35.00	60
7214232	Contoured cushion for head support, all sizes	65.00	65.00	60
7214233	Back support tension bar	5.00	5.00	60
7214234	Securement for head support for back support tension bar	15.00	15.00	60
	FRAME			
7214235	Anti-tip device	N. C.	3.00	60
7214235	Front impact guard	5.00	5.00	60
7214237	Lighting systems	175.00	175.00	60
7214238	Reflective devices	N. C.	50.00	60
7214239	Emergency flashers	150.00	150.00	60
7214240	Triangular-shaped flag, orange, 300 cm ² minimum surface	5.00	5.00	60
7214241	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
	DRIVE SYSTEM			
7214242	Standard control device for multipurpose programmable	N. C.	800.00	60
	electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7214243	Compact control device	N. C.	800.00	60
7214244	Control device operated by an assistant	200.00	200.00	60
7214245	Control device for powered repositionning, for an accessory	N. C.	N. C.	60
7214246	Control device for powered repositionning, for four	N. C.	N. C.	60
7214247	accessories	N.C	N. C	(0
7214247	Infrared option	N. C.	N. C.	60 60
7214248 7214249	Bluetooth option Separate control for powered tilt mechanism	1,600.00 350.00	1,600.00 350.00	60
7214249	Control device support, standard lateral, adjustable front-	N. C.	200.00	60
/217230	rear position	14. C.	200.00	00
7214251	Control device support, lateral, flip-up with locking	N. C.	200.00	60
, = 1 . = 0 1	mechanism, adjustable front-rear position	1 0.	200.00	
7214252	Control device support, central, flip-up, adjustable front-	N. C.	200.00	60
7214253	rear position Controller for multipurpose programmable electronic	N. C.	575.00	60
7214233	system	N. C.	373.00	00
7214254	Motor, including electric brake	N. C.	600.00	60
7214256	Battery charger, compatible with group 22NF or 24	N. C.	130.00	60
	batteries			
7214257	Adapted non-proportional control, cephalic	500.00	500.00	60
7214258	Adapted non-proportional control, chin-controlled	700.00	700.00	60
7214259	Adapted non-proportional control, breath-controlled	500.00	500.00	60
7214260	Adapted proportional control, cephalic	500.00	500.00	60
7214261	Adapted proportional control, chin-controlled	500.00	500.00	60
7214262	Adapted proportional control, mini joystick	2,500.00	2,500.00	60
7214263	Mounting bracket for adapted control	N. C.	N. C.	60

BASIC AND OPTIONAL COMPONENTS during device purchase Component replacement (month month month					
7214265	7214264	Adapted control interface	N. C.	800.00	60
20.00 20.00 60	7214265	*	100.00		60
20.00 20.00 60					60
15.00 15.00 60		·	20.00	20.00	60
15.00 15.00 60		<u> •</u>	15.00	15.00	60
15.00 15.00 60			15.00	15.00	60
15.00 15.00 60			15.00	15.00	60
VHEELS AND TIRES			15.00	15.00	60
2214273 Drive wheel; 35.6 cm (14 in.) N. C. 160.00 60 7214274 Drive wheel tire, standard pressure inner tube; 35.6 cm N. C. 40.00 60 7214275 Puncture proof tire for drive wheel 35.0 75.00 75.00 60 7214277 Caster wheel, with standard pressure inner tube tire; 20.3 N. C. 75.00 60 7214278 Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9 N. C. 75.00 60 cm (9 in.) 22.9 cm (9 in.) 7214279 Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9 N. C. 75.00 60 cm (9 in.) 20 7214281 Fork, adjustable height N. C. 100.00 60 PRICE (including all the basic components) 7214282 POWERED WHEELCHAIR 4,600.00 CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase BODY SUPPORT SYSTEM Unit price for component replacement		•	1,000.00	1,000.00	60
Drive wheel tire, standard pressure inner tube; 35.6 cm N. C. 40.00 60 (14 in.)		WHEELS AND TIRES			
Drive wheel tire, standard pressure inner tube; 35.6 cm N. C. 40.00 60 (14 in.)	7214273	Drive wheel; 35.6 cm (14 in.)	N. C.	160.00	60
7214275 Puncture proof tire for drive wheel 35.00 75.00 60 7214277 Caster wheel, with standard pressure inner tube tire; 20.3 N. C. 75.00 60 cm (8 in.) or 22.9 cm (9 in.) 7214278 Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9 N. C. 75.00 60 cm (9 in.) 7214279 Suspension independent of wheels N. C. 100.00 60 7214281 Fork, adjustable height N. C. 100.00 60 PRICE (including all the basic components) 7214282 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16% in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component replacement Warra during device purchase BODY SUPPORT SYSTEM	7214274	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	40.00	60
7214277 Caster wheel, with standard pressure inner tube tire; 20.3 N. C. 75.00 60 cm (8 in.) or 22.9 cm (9 in.) 7214278 Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9 N. C. 75.00 60 cm (9 in.) 7214279 Suspension independent of wheels N. C. 100.00 60 7214281 Fork, adjustable height N. C. 100.00 60 PRICE (including all the basic components) 7214282 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase ### Unit price for component replacement ### Unit price for component during device purchase ### Unit price for component replacement ### Unit price for component during device purchase ### Unit price for component during device purchase	7214275		35.00	75.00	60
7214278 Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9 N. C. 75.00 60 cm (9 in.) 7214279 Suspension independent of wheels N. C. 100.00 60 7214281 Fork, adjustable height N. C. 100.00 60 7214281 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase BODY SUPPORT SYSTEM		Caster wheel, with standard pressure inner tube tire; 20.3			
7214281 Suspension independent of wheels N. C. 100.00 60 7214281 Fork, adjustable height N. C. 100.00 60 PRICE (including all the basic components) 7214282 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase Unit price for component replacement Warra (mont)	7214278	Caster wheel, puncture proof tire; 20.3 cm (8 in.) or 22.9	N. C.	75.00	60
7214282 Fork, adjustable height N. C. 100.00 60 PRICE (including all the basic components) 7214282 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase BODY SUPPORT SYSTEM	7214279		N. C.	100.00	60
7214282 POWERED WHEELCHAIR CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase Unit price for component replacement Warra (mont)		•	N. C.	100.00	60
CATEGORY FMO-GM 3-C-P2 (MID-FRON WHEEL DRIVE) SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warra (montice)				(including all the basic	
SUNRISE MEDICAL CANADA INC, "QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warra (montion)	7214282	POWERED WHEELCHAIR		4,600.00	
"QUICKIE Q700M HD-E" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warran (montification) Warran (montification)		· · · · · · · · · · · · · · · · · · ·			
TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warra (month)		SUNRISE MEDICAL CANADA INC,			
Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 41.9 cm to 50.8 cm (16½ in. to 20 in.) Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warra (mont)					
Frame: mid-front wheel drive base, overall width ≤ 61 cm (24 in.) Drive system: manual freewheel lever; control cable replaceable separately Unit price of component during device purchase Unit price for component replacement Warra (monting device purchase)		Maximum weight capacity: 159 kg (350 lb.)	.)		
BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase Unit price for component replacement Warran (mont)		,	*		
BASIC AND OPTIONAL COMPONENTS Unit price of component during device purchase Unit price for component replacement Warra (month		Drive system: manual freewheel lever; control cable replace	ceable separately		
BASIC AND OPTIONAL COMPONENTS component during device purchase Component replacement Warra (month)		, , , , , , , , , , , , , , , , , , , ,	1 ,		
BODY SUPPORT SYSTEM		BASIC AND OPTIONAL COMPONENTS	component during device	component	Warranty (months)
		DODY SHIDDODT SYSTEM			
	7214283	Seat-to-back assembly structure; resizable	N. C.	400.00	12

7214284	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	195.00	12
7214285 7214286	Seat, padded and contoured Back support, flexible, non tension adjustable; heights of 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29 in.) or 76.2 cm (30 in.)	N. C. N. C.	195.00 90.00	1 1
7214287	Back support, flexible, tension adjustable	60.00	150.00	1
7214288	Back support, padded and contoured; heights of 53.3 cm (21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)	N. C.	90.00	1
7214289	Back support upright, straight, height and angle adjustable; angle-adjustable from 85° to 110° by increments of 4°	N. C.	250.00	12
7214290	Push handle, with hand grip	N. C.	90.00	12
7214292	Powered reclining back support, including biomechanical adjustment	1,250.00	1,250.00	12
7214293	Power tilt mechanism	1,200.00	1,200.00	12
7214294	Postural support pelvic belt	N. C.	25.00	12
7214295	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214296	T-shaped arm support, long, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214297	U-shaped arm support, short, flip-up and removable; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214298	U-shaped arm support, long, flip-up and removable; height adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214300	I-shaped arm support, flip-up; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214301	L-shaped arm support, flip-up or swing-away outward; height-adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	150.00	1
7214302	Arm support pad, short, straight	N. C.	15.00	1
7214303	Arm support pad, long, straight	N. C.	15.00	1
7214304	Arm support pad, contoured	5.00	20.00	1
7214305	Arm support pad, gel	70.00	85.00	1

7214306	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°; removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)	N. C.	135.00	12
7214307	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	15.00	150.00	12
7214308	Powered elevating lower leg support, individually controlled	365.00	500.00	12
7214309	Powered elevating lower leg support, paired control	365.00	500.00	12
7214310	One-piece powered elevating lower leg support	845.00	980.00	12
7214311	Padded calf support, angle, height and depth adjustable, including flat	70.00	70.00	12
7214312	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	35.00	12
7214313	Foot support, separate, flip-up, not angle adjustable, extra long	N. C.	35.00	12
7214314	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	N. C.	35.00	12
7214315	Foot support, separate, flip-up, angle and depth adjustable, extra long	N. C.	35.00	12
7214316	Foot support, flip-up, one-piece platform	190.00	225.00	12
7214317	Heel loop, adjustable	5.00	5.00	12
7214318	Head support, depth adjustable	55.00	55.00	12
7214319	Contoured cushion for head support, all sizes	35.00	35.00	12
7214320	Back support tension bar	20.00	20.00	12
7214321	Securement for head support for back support tension bar	40.00	40.00	12
	FRAME			
7214322	Front impact guard	12.00	12.00	12
7214323	Lighting systems	N. C.	425.00	12
7214324	Reflective devices	N. C.	5.00	12
7214325	Emergency flashers	425.00	425.00	12
7214326	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
7214327	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7214328	Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	N. C.	585.00	12
7214329	Compact control device	N. C.	585.00	12
7214330	Control device operated by an assistant	560.00	560.00	12
7214331	Control device for powered repositionning, for an accessory	100.00	100.00	12
7214332	Control device for powered repositionning, for four accessories	350.00	350.00	12
7214333	Infrared option	N. C.	N. C.	12
7214334	Bluetooth option	N. C.	N. C.	12
7214335	Separate control for powered tilt mechanism	510.00	510.00	12

7214336	Control device support, standard lateral, adjustable front- rear position	N. C.	85.00	12
7214337	Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position	N. C.	85.00	12
7214338	Control device support, central, flip-up, adjustable front- rear position	65.00	150.00	12
7214339	Controller for multipurpose programmable electronic system	N. C.	575.00	12
7214340	Motor	N. C.	430.00	12
7214341	Electric brake	N. C.	60.00	12
7214342	Battery charger, compatible with group 22NF or 24 batteries	N. C.	145.00	12
7214343	Adapted non-proportional control, cephalic	1,200.00	1,200.00	12
7214344	Adapted non-proportional control, chin-controlled	1,200.00	1,200.00	12
7214345	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7214346	Adapted proportional control, cephalic	1,500.00	1,500.00	12
7214347	Adapted proportional control, chin-controlled	1,100.00	1,100.00	12
7214348	Adapted proportional control, mini joystick	1,800.00	1,800.00	12
7214349	Mounting bracket for adapted control	250.00	250.00	12
7214350	Adapted control interface	365.00	950.00	12
7214351	Mounting bracket for interface	400.00	400.00	12
7214352	Lever extension, ball	55.00	55.00	12
7214353	Lever extension, conicospherical	25.00	25.00	12
7214354	Lever extension, stick	55.00	55.00	12
7214355	Lever extension, T-shaped	65.00	65.00	12
7214356	Lever extension, mushroom	55.00	55.00	12
7214357	Lever extension, U-shaped	55.00	55.00	12
7214358	Trajectory correction system	550.00	550.00	12
	WHEELS AND TIRES			
7214359	Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7214360	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	55.00	1
	(14 in.)			
7214361	Puncture proof tire for drive wheel	10.00	65.00	1
7214362	Caster wheel, with semi-pneumatic tire; 15.2 cm (6 in.)	N. C.	25.00	12
7214365	Suspension independent of wheels	N. C.	120.00	12
7214366	Fork, standard	N. C.	45.00	12

PRICE (including all the basic components)

7214368 **POWERED WHEELCHAIR** 4,600.00

CATEGORY FMO-GM 3-C-P2 (MID-REAR WHEEL DRIVE)

SUNRISE MEDICAL CANADA INC.

"QUICKIE Q500H HD-E" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 159 kg (350 lb.)

Seat-to-floor height: 41.9 cm to 50.8 cm ($16\frac{1}{2}$ in. to 20 in.) **Frame:** mid-rear wheel drive base, overall width \leq 61 cm (24 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7214369	Seat-to-back assembly structure; resizable	N. C.	400.00	12
7214370	Rigid seat base, witdth and depth adjustable; strips of	N. C.	195.00	12
	"hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of			
	40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),			
	48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9			
	cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.);			
	depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16			
	in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.),			
	50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)			
7214371	Seat, padded and contoured	N. C.	195.00	1
7214372	Back support, flexible, non tension adjustable; heights of	N. C.	90.00	1
	50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.),			
	58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm			
	(26 in.), 68.6 cm (27 in.), 71.1 cm (28 in.), 73.6 cm (29			
	in.) or 76.2 cm (30 in.)			
7214373	Back support, flexible, tension adjustable	60.00	150.00	1
7214374	Back support, padded and contoured; heights of 53.3 cm	N. C.	90.00	1
5011055	(21 in.), 57.2 cm (22½ in.) or 61 cm (24 in.)		250.00	4.0
7214375	Back support upright, straight, height and angle	N. C.	250.00	12
	adjustable; angle-adjustable from 85° to 110° by			
7014276	increments of 4°	N.C	90.00	12
7214376 7214378	Push handle, with hand grip Powered reclining back support, including biomechanical	N. C. 1,250.00	1,250.00	12 12
12143/8	adjustment	1,230.00	1,230.00	12
7214379	Power tilt mechanism	1,200.00	1,200.00	12
7214379	Postural support pelvic belt	N. C.	25.00	12
, 21 1500	1 obtains support pervie out	11. 0.	25.00	12

7214381	T-shaped arm support, short, removable; height-adjustable, from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking	N. C.	150.00	1
	mechanism			
7214382	T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
/217302	from 20.3 cm to 38.1 cm (8 in. to 15 in.) by maximum	14. C.	130.00	1
	increments of 2.5 cm (1 in.), with locking mechanism			
	merements of 215 cm (1 mi), with rooming meetinging			
7214383	U-shaped arm support, short, flip-up and removable;	N. C.	150.00	1
	height-adjustable, from 25.4 cm to 38.1 cm (10 in. to			
	15 in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism			
7214384	U-shaped arm support, long, flip-up and removable; height	N. C.	150.00	1
	adjustable, from 25.4 cm to 38.1 cm (10 in. to 15 in.) by			
	maximum increments of 2.5 cm (1 in.), with locking			
	mechanism			
7214386	I-shaped arm support, flip-up; height-adjustable, from	N. C.	150.00	1
	25.4 cm to 38.1 cm (9 in. to 15 in.) by maximum			
	increments of 2.5 cm (1 in.), with locking mechanism			
7214387	L-shaped arm support, flip-up or swing-away outward;	N. C.	150.00	1
	height-adjustable, from 25.4 cm to 38.1 cm (11 in. to 15			
	in.) by maximum increments of 2.5 cm (1 in.), with			
	locking mechanism			
7214388	Arm support pad, short, straight	N. C.	15.00	1
7214389	Arm support pad, long, straight	N. C.	15.00	1
7214390	Arm support pad, contoured	5.00	20.00	1
7214391	Arm support pad, gel	70.00	85.00	1
7214392	Parallel lower leg support, 60°, 65°, 70°, 80°, 85° or 90°;	N. C.	135.00	12
	removable and pivoting with locking mechanism; adjustable length from 33 cm to 50.8 cm (13 in. to 22 in.)			
	adjustable length from 33 cm to 30.8 cm (13 m. to 22 m.)			
7214393	Lower leg support, compensating elevating; with locking	15.00	150.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7214394	Powered elevating lower leg support, individually	365.00	500.00	12
	controlled			
7214395	Powered elevating lower leg support, paired control	365.00	500.00	12
7214396	Padded calf support, angle, height and depth adjustable,	70.00	70.00	12
	including flat			
7214397	Foot support, separate, flip-up, not angle adjustable,	N. C.	35.00	12
	standard lenght			
7214398	Foot support, separate, flip-up, not angle adjustable, extra	N. C.	35.00	12
	long			
7214399	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	standard lenght			
7214400	Foot support, separate, flip-up, angle and depth adjustable,	N. C.	35.00	12
	extra long			
7214401	Heel loop, adjustable	5.00	5.00	12
7214402	Head support, depth adjustable	55.00	55.00	12
7214403	Contoured cushion for head support, all sizes	35.00	35.00	12
7214404	Back support tension bar	20.00	20.00	12
7214405	Securement for head support for back support tension bar	40.00	40.00	12

		FRAME			
12.00 12.0	7214406		N. C.	12.00	12
12214418		<u> </u>			
Page	7214408	1 0	N. C.	425.00	12
	7214409	Reflective devices	N. C.	5.00	12
N. C. 100.00 12	7214410	Emergency flashers	15.00	15.00	12
DRIVE SYSTEM Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	7214411	Triangular-shaped flag, orange, 300 cm ² minimum surface	15.00	15.00	12
DRIVE SYSTEM Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator					
Standard control device for multipurpose programmable electronics; drive control device; toggle or push switches the functions: start-stop, horn and function selection; battery charge level indicator	7214412	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
		DRIVE SYSTEM			
the functions: start-stop, horn and function selection; battery charge level indicator 7214414 Compact control device Part of the State Control device operated by an assistant 560.00 560.00 12 2 12 1416 Control device for powered repositionning, for an 100.00 100.00 12 2 12 1417 Control device for powered repositionning, for an 350.00 350.00 12 2 14 1418 Infrared option N. C. N. C. 12 1418 Infrared option N. C. N. C. 12 1418 Infrared option N. C. N. C. 12 1419 Bluetooth option N. C. N. C. 12 1419 Control device support, standard lateral, adjustable front-rear position N. C. 85.00 12 12 1419 Control device support, lateral, flip-up with locking N. C. 85.00 12 12 1414 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, lateral, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Control device support, central, flip-up, adjustable front-rear position N. C. 1510 Controller for multipurpose programmable electronic N. C. 1575.00 12 2 12 14424 Controller for multipurpose programmable electronic N. C. 1575.00 12 2 14425 Motor N. C. 1510 Controller N. C. 1	7214413	1 1 1 0	N. C.	585.00	12
Tell					
		*			
7214415 Control device operated by an assistant 560.00 560.00 12 7214416 Control device for powered repositionning, for an accessory 100.00 100.00 12 7214417 Control device for powered repositionning, for four accessories 350.00 350.00 12 7214418 Infrared option N. C. N. C. N. C. 12 7214419 Bluetooth option N. C. N. C. N. C. 12 7214420 Separate control for powered tilt mechanism 510.00 510.00 12 7214421 Control device support, standard lateral, adjustable front-rear position N. C. 85.00 12 7214422 Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position 85.00 12 7214423 Control device support, central, flip-up, adjustable front-rear position 85.00 12 7214424 Control device support, central, flip-up, adjustable front-rear position N. C. 450.00 12 7214425 Control device support, central, flip-up, adjustable front-rear position N. C. 450.00 12		battery charge level indicator			
7214415 Control device operated by an assistant 560.00 560.00 12 7214416 Control device for powered repositionning, for an accessory 100.00 100.00 12 7214417 Control device for powered repositionning, for four accessories 350.00 350.00 12 7214418 Infrared option N. C. N. C. N. C. 12 7214419 Bluetooth option N. C. N. C. N. C. 12 7214420 Separate control for powered tilt mechanism 510.00 510.00 12 7214421 Control device support, standard lateral, adjustable front-rear position N. C. 85.00 12 7214422 Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position 85.00 12 7214423 Control device support, central, flip-up, adjustable front-rear position 85.00 12 7214424 Control device support, central, flip-up, adjustable front-rear position N. C. 450.00 12 7214425 Control device support, central, flip-up, adjustable front-rear position N. C. 450.00 12	7214414	Compact control device	N C	585 00	12
Table		•			
Table Control device of proported repositionning, for four accessor's Control device for powered repositionning, for four accessories		* *			
		• • • •			
7214418 Infrared option N. C. N. C. 12 7214419 Bluetooth option N. C. N. C. 12 7214420 Separate control for powered tilt mechanism 510.00 \$10.00 12 7214421 Control device support, standard lateral, adjustable front-rear position N. C. 85.00 12 7214422 Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position N. C. 85.00 12 7214423 Control device support, central, flip-up, adjustable front-rear position 150.00 12 7214424 Controller for multipurpose programmable electronic system N. C. 575.00 12 7214425 Motor N. C. 430.00 12 7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, breath-controlled 1,200.00 1,500.00 <td< td=""><td>7214417</td><td></td><td>350.00</td><td>350.00</td><td>12</td></td<>	7214417		350.00	350.00	12
7214419 Bluetooth option N. C. N. C. 12 7214420 Separate control for powered tilt mechanism 510.00 510.00 12 7214421 Control device support, standard lateral, adjustable frontrear position N. C. 85.00 12 7214422 Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position N. C. 85.00 12 7214423 Control device support, central, flip-up, adjustable front-rear position 65.00 150.00 12 7214424 Controller for multipurpose programmable electronic system N. C. 575.00 12 7214425 Motor N. C. 430.00 12 7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted proportional control, cephalic 1,	7014410		N. C.	N. C	10
T214420 Separate control for powered tilt mechanism S10.00		÷			
7214421 Control device support, standard lateral, adjustable frontrear position N. C. 85.00 12 7214422 Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position N. C. 85.00 12 7214423 Control device support, central, flip-up, adjustable front-rear position 65.00 150.00 12 7214424 Controller for multipurpose programmable electronic system N. C. 575.00 12 7214425 Motor N. C. 430.00 12 7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted proportional control, breath-controlled 1,500.00 1,500.00 12 7214431 Adapted proportional control, chin-controlled 1,500.00 1,500.00 12 7214432 Adapted proport		•			
Table Tabl					
Total Control device support, lateral, flip-up with locking mechanism, adjustable front-rear position Control device support, central, flip-up, adjustable front-rear position Control for multipurpose programmable electronic system Control for multipurpose programmable electronic Control for for multipurpose programmable electronic Control for for for for for for electronic Control for	/217721		14. C.	05.00	12
mechanism, adjustable front-rear position 7214423 Control device support, central, flip-up, adjustable front-rear position 65.00 150.00 12 7214424 Controller for multipurpose programmable electronic system N. C. 575.00 12 7214425 Motor N. C. 430.00 12 7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214430 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,000.00 1,500.00 12 7214433 Adapted proportional control, chin-controlled 1,800.00 1,800.00 12 7214434 Mountin	7214422		N. C.	85.00	12
Tear position Tear positio					
7214424 Controller for multipurpose programmable electronic system N. C. 575.00 12 system 7214425 Motor N. C. 430.00 12 strates 7214426 Electric brake N. C. 60.00 12 strates 7214427 Battery charger, compatible with group 22NF or 24 batteries N. C. 145.00 12 strates 7214428 Adapted non-proportional control, cephalic batteries 1,200.00 1,200.00 12 strates 7214429 Adapted non-proportional control, chin-controlled batteries 1,200.00 1,200.00 12 strates 7214430 Adapted non-proportional control, chin-controlled batteries 1,500.00 1,500.00 12 strates 7214431 Adapted proportional control, cephalic brace 1,500.00 1,500.00 12 strates 7214432 Adapted proportional control, chin-controlled brace br	7214423	Control device support, central, flip-up, adjustable front-	65.00	150.00	12
T214425 Motor N. C. 430.00 12		1			
7214425 Motor N. C. 430.00 12 7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 batteries N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214433 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437	7214424		N. C.	575.00	12
7214426 Electric brake N. C. 60.00 12 7214427 Battery charger, compatible with group 22NF or 24 batteries N. C. 145.00 12 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12	701 440 5		N. G	420.00	10
7214427 Battery charger, compatible with group 22NF or 24 batteries N. C. 145.00 12 batteries 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 55.00 12 7214440 Lever extension, T-shaped					
batteries 7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214440 Lever extension, T-shaped 65.00 65.00					
7214428 Adapted non-proportional control, cephalic 1,200.00 1,200.00 12 7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441	/21442/		N. C.	143.00	12
7214429 Adapted non-proportional control, chin-controlled 1,200.00 1,200.00 12 7214430 Adapted non-proportional control, breath-controlled 850.00 850.00 12 7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever exte	7214428		1.200.00	1.200.00	12
7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, mushroom 55.00 65.00 12 7214441 Lever extension, U-shaped 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12			The state of the s		
7214431 Adapted proportional control, cephalic 1,500.00 1,500.00 12 7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, mushroom 55.00 65.00 12 7214441 Lever extension, U-shaped 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12	7214430	Adapted non-proportional control, breath-controlled	850.00	850.00	12
7214432 Adapted proportional control, chin-controlled 1,100.00 1,100.00 12 7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12					
7214433 Adapted proportional control, mini joystick 1,800.00 1,800.00 12 7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12					
7214434 Mounting bracket for adapted control 250.00 250.00 12 7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12		<u> </u>			
7214435 Adapted control interface 365.00 950.00 12 7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12		· · · · · · · · · · · · · · · ·			
7214436 Mounting bracket for interface 400.00 400.00 12 7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12					
7214437 Lever extension, ball 55.00 55.00 12 7214438 Lever extension, conicospherical 25.00 25.00 12 7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12		•			
7214439 Lever extension, stick 55.00 55.00 12 7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12	7214437		55.00	55.00	12
7214440 Lever extension, T-shaped 65.00 65.00 12 7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12	7214438	Lever extension, conicospherical	25.00	25.00	
7214441 Lever extension, mushroom 55.00 55.00 12 7214442 Lever extension, U-shaped 55.00 55.00 12					
7214442 Lever extension, U-shaped 55.00 55.00 12					
· 1					
1214443 Trajectory correction system 550.00 550.00 12		•			
	/214443	rajectory correction system	550.00	550.00	12

WHEELS AND TIRES

7214444	Drive wheel; 35.6 cm (14 in.)	N. C.	75.00	12
7214445	Drive wheel tire, standard pressure inner tube; 35.6 cm	N. C.	55.00	1
	(14 in.)			
7214446	Puncture proof tire for drive wheel	10.00	65.00	1
7214447	Caster wheel, with semi-pneumatic tire; 22.9 cm (9 in.)	N. C.	25.00	12
7214450	Suspension independent of wheels	N. C.	120.00	12
7214451	Fork, standard	N. C.	45.00	12

PRICE
(including all
the basic
components)

7214453 **POWERED WHEELCHAIR** 7,275.00

CATEGORY FMO-GM 4-B-P2 (MID-WHEEL DRIVE)

AMYLIOR INC.

"ALLTRACK M ATM4B" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 249 kg (550 lb.)

Seat-to-floor height: 41.2 cm to 52.1 cm ($16\frac{1}{4} \text{ in.}$ to $20\frac{1}{2} \text{ in.}$) **Frame:** mid-wheel drive base, overall width $\leq 84 \text{ cm}$ (33 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7214454	Seat-to-back assembly structure; resizable	N. C.	550.00	12
7214455	Rigid seat base, witdth and depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 (25 in.), 66 cm (26 in.), 68.5 cm (27 in.) or 71.1 cm (28 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.)	N. C.	200.00	12
7214456 7214459	Seat, padded and contoured Back support, padded and contoured; heights of 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.), 61 cm (24 in.), 63.5 cm (25 in.), 66 cm (26 in.) or 71.1 cm (28 in.)	350.00 N. C.	550.00 500.00	1 1
7214458	Back support, flexible, tension adjustable	N. C.	500.00	1
7214460	Back support upright, straight, height and angle adjustable; angle-adjustable from 82° to 110° by maximum increments of 4°	N. C.	94.00	12
7214461	Push handle, with hand grip	N. C.	8.00	12
7214463	Powered reclining back support, including biomechanical adjustment	2,500.00	2,500.00	12
7214464	Power tilt mechanism	2,200.00	2,200.00	12

7214465	Postural support pelvic belt	N. C.	25.00	12
7214466	T-shaped arm support, short, removable; height-adjustable, from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking	N. C.	150.00	1
7214467	mechanism T-shaped arm support, long, removable; height-adjustable,	N. C.	150.00	1
/21440/	from 18.4 cm to 38.7 cm (7½ in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	14. C.	130.00	1
7214468	U-shaped arm support, short, flip-up and removable; height-adjustable, from 18.4 cm to 38.7 cm (71/4 in. to 151/4 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7214469	U-shaped arm support, long, flip-up and removable; height adjustable, from 18.4 cm to 38.7 cm (7¼ in. to 15¼ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	33.00	183.00	1
7214471	I-shaped arm support, flip-up; height-adjustable, from 18.4 cm to 38.7 cm (71/4 in. to 151/4 in.) by maximum	33.00	183.00	1
7214472	increments of 2.5 cm (1 in.), with locking mechanism	25.00	175.00	1
7214472	L-shaped arm support, flip-up; height-adjustable, from 17.8 cm to 38.1 cm (7 in. to 15 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	25.00	175.00	1
7214473	Arm support pad, short, straight	N. C.	13.00	1
7214474	Arm support pad, long, straight	N. C.	13.00	1
7214475	Arm support pad, contoured	7.00	20.00	1
7214476	Arm support pad, gel	19.00	32.00	1
7214477	Parallel lower leg support, 60°, 70°; detachable and	N. C.	192.00	12
,2111,,	pivoting with locking mechanism; adjustable length from 31.8 cm to 49.5 cm (12½ in. to 19½ in.)	14. 6.	192.00	12
7214478	Lower leg support, compensating elevating; with locking mechanism; compatible with the same fastening system as the fixed lower leg support or supplied with its fastening system	108.00	300.00	12
7214479	Powered elevating lower leg support, individually controlled	808.00	1,000.00	12
7214480	Powered elevating lower leg support, paired control	808.00	1,000.00	12
7214481	One-piece powered elevating lower leg support	1,808.00	2,000.00	12
7214482	Padded calf support, angle, height and depth adjustable, including contoured pad	70.00	70.00	12
7214483	Foot support, separate, flip-up, not angle adjustable, standard lenght	N. C.	50.00	12
7214484	Foot support, separate, flip-up, not angle adjustable, extra long	30.00	80.00	12
7214485	Foot support, separate, flip-up, angle and depth adjustable, standard lenght	30.00	80.00	12
7214486	Foot support, separate, flip-up, angle and depth adjustable, extra long	30.00	80.00	12
7214487	Foot support, flip-up, one-piece platform	110.00	160.00	12
7214488	Heel loop, adjustable	10.00	10.00	12
7214489	Head support, depth adjustable	90.00	90.00	12
7214490	Contoured cushion for head support, all sizes	50.00	50.00	12
7214491	Back support tension bar	100.00	100.00	12
7214492	Securement for head support for back support tension bar	20.00	20.00	12

	FRAME			
7214493	Front impact guard	20.00	20.00	12
7214494	Lighting systems	400.00	400.00	12
7214495	Reflective devices	N. C.	10.00	12
7214496	Emergency flashers	N. C.	N. C.	12
7214497	Triangular-shaped flag, orange, 300 cm ² minimum surface	10.00	10.00	12
	Triangular shaped riag, stange, 500 cm minimum surrace			
7214498	Securement points for strap-type tiedowns for transport	N. C.	N. C.	12
	DRIVE SYSTEM			
7214499	Standard control device for multipurpose programmable	N. C.	750.00	12
	electronics; drive control device; toggle or push switches			
	the functions: start-stop, horn and function selection;			
	battery charge level indicator			
7214500	Compact control device	N. C.	750.00	12
7214501	Control device operated by an assistant	750.00	750.00	12
7214502	Control device for powered repositionning, for an	350.00	350.00	12
	accessory			
7214503	Control device for powered repositionning, for four	600.00	600.00	12
	accessories			
7214504	Infrared option	N. C.	N. C.	12
7214505	Bluetooth option	N. C.	N. C.	12
7214506	Separate control for powered tilt mechanism	250.00	250.00	12
7214507	Control device support, standard lateral, adjustable front-	N. C.	100.00	12
	rear position			
7214508	Control device support, lateral, flip-up with locking	100.00	200.00	12
	mechanism, adjustable front-rear position			
7214509	Control device support, central, flip-up, adjustable front-	200.00	300.00	12
	rear position			
7214510	Controller for multipurpose programmable electronic	N. C.	783.00	12
	system			
7214511	Motor, including electric brake	N. C.	600.00	12
7214513	Battery charger, compatible with group 24 batteries	N. C.	219.00	12
7214514	Adapted non-proportional control, cephalic	4,000.00	4,000.00	12
7214515	Adapted non-proportional control, chin-controlled	600.00	600.00	12
7214516	Adapted non-proportional control, breath-controlled	1,500.00	1,500.00	12
7214517	Adapted proportional control, cephalic	4,000.00	4,000.00	12
7214518	Adapted proportional control, chin-controlled	1,500.00	1,500.00	12
7214519	Adapted proportional control, mini joystick	1,500.00	1,500.00	12
7214520	Mounting bracket for adapted control	350.00	350.00	12
7214521	Adapted control interface	350.00	1,100.00	12
7214522	Mounting bracket for interface	350.00	350.00	12
7214523	Lever extension, ball	58.00	58.00	12
7214524	Lever extension, conicospherical	58.00	58.00	12
7214525	Lever extension, stick	58.00	58.00	12
7214526	Lever extension, T-shaped	58.00	58.00	12
7214527	Lever extension, mushroom	80.00 95.00	80.00 95.00	12 12
7214528 7214529	Lever extension, U-shaped Trajectory correction system	895.00	895.00 895.00	12
1214327	Trajectory correction system	073.00	073.00	12

1
1
12
12
12
12

DIVISION III: COMPLEMENTS FOR WHEELCHAIRS SUBDIVISION 1: FACULTATIVE COMPONENTS

	FACULTATIVE COMPONENTS	Maximum unit price of component during device purchase	Maximum unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7810014	Elastic mesh seat	495.00	495.00	12
7810000	Dynamic back for manual wheelchair	330.00	550.00	12
7810032	Reclining cylinder back support	415.00	635.00	12
7810006	Stump support, adjustable	330.00	330.00	12
7810020	Safety pelvic belt	325.00	325.00	12
7810025	Five points safety harness	150.00	150.00	12
7811017	Back support tension bar (FMA-GM 2-C-P1)	40.00	40.00	12
7811000	Securement for head support for back support tension bar, height adjustable (FMA-GM 2-C-P1)	100.00	100.00	12
7811092	Mounting kit for angle-adjustable foot support (FMA-GM 2-B-P2 pliant), (FMA-GM 2-C-P1), (FMA-GM 3-C-P2)	10.00	10.00	12
7811093	Mounting kit for angle-adjustable foot support (FMO-GM 2-A-P2), (FMO-GM 2-B-P2), (FMO-GM 3-B-P2)	40.00	40.00	12
	FRAME			
7810015	Angle adjustable push handle	105.00	105.00	12
7810017	Front locking tilt for positioning base	35.00	35.00	12
	DRIVE SYSTEM			
7810008	Handrim with thumb grip	270.00	295.00	12
7810010	Handrim, plastic-coated, ultra-light	185.00		12
7810010	Propulsion assistance module	4,950.00		12
7810013	Mid-wheel manual propulsion for positioning base	495.00		12
7811094	Optional repositioning module; 4 accessories (FMO-GM 2-A-P2), (FMO-GM 2-B-P2), (FMO-GM 3-B-P2)	768.00		12

SUBDIVISION 2: BATTERIES FOR POWERED WHEELCHAIRS BATTERIES (GEL)

		Price including delivery,
4590000	SUPPLIER: EAST PENN / POWER BATTERY	375.80
	GROUP 22NF BATTERIES	
	Model: 8G22NF	
4590001	SUPPLIER: EAST PENN / POWER BATTERY	492.36
	GROUP 24 BATTERIES	
	Model: 8G24T881	
4590002	SUPPLIER: EAST PENN / POWER BATTERY	242.61
	GROUP U1 BATTERIES	
	Model: 8GU1	

DIVISION IV: POSITIONNING BASES SUBDIVISION 1: MASS GROUP 1

			PRICE (including all the basic components)	
7216000	POSITIONING BASES CATEGORY BPO-GM 1-A-P2 (RIGID FRAME)		1,425.00	
	SUNRISE MEDICAL CANADA INC.			
	"ZIPPIE IRIS" DEVICE			
	TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 50 kg (110 lb.) Seat-to-floor height: 33 cm to 48.3 cm (13 in. to 19 in.) Frame: back height from 35.6 cm to 63.5 cm (14 in. to 25 in.)	n.)		
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7216001	Seat, rigid base, depth and width adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.); depths of 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.)	N. C.	75.00	12
7216002	Back support, rigid plate	N. C.	150.00	1
7216003	Back support, flexible, tension adjustable	35.00	185.00	1
7216005	Dynamic back support	175.00	175.00	1
7216004	Reclining back support	420.00	420.00	1
7216006	Back support upright, straight, angle and height adjustable; adjustable from 85° to 120° by increments of 5°;	N. C.	40.00	12
7216007	Push handle, with hand grip	N. C.	N. C.	12
7216008	Raised and adjustable push bar, with hand grip	95.00	95.00	12
7216009	Power tilt mechanism controlled by the occupant	850.00	850.00	12
7216010	Postural support pelvic belt	N. C.	25.00	12
7216011	T-shaped arm support, short, removable; height-adjustable, from 17,8 cm to 40.1 cm (7 in. to 15¾ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7216012	T-shaped arm support, long, removable; height-adjustable, from 17,8 cm to 40.1 cm (7 in. to 15¾ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	114.00	1
7216013	Arm support pad, short, straight	N. C.	6.00	1

7216014	Arm support pad, long, straight	N. C.	6.00	1
7216015	Arm support pad, contoured	9.00	15.00	1
7216016	Arm support pad, gel	14.00	20.00	1
7216017	Lower leg support, parallel, removable and swing-away;	N. C.	55.00	12
	adjustable length from 8.9 cm to 24.2 cm (3½ in. to 9½			
	in.) or from 22.9 cm to 50.8 cm (9 in. to 19 in.)			
7216020	Lower leg support, compensating elevating; with locking	55.00	110.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its own			
	fastening system			
7216023	Padded calf support, angle, height and depth adjustable,	25.00	25.00	12
	including flat			
7216021	Calf support strap, single	15.00	15.00	12
7216022	Calf support strap, double	18.00	18.00	12
7216024	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	35.00	12
	standard lenght			
7216025	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	35.00	12
	extra long			
7216026	Foot support, flip-up, full width, depth and angle	N. C.	35.00	12
	adjustable			
7216027	Heel loop, adjustable	1.00	1.00	12
7216028	Head support, depth adjustable	55.00	55.00	12
7216029	Contoured cushion for head support, all sizes	35.00	35.00	12
7216030	Back support tension bar	35.00	35.00	12
7216031	Securement for head support for back support tension bar,	40.00	40.00	12
	height adjustable			
	FRAME			
7216032	Anti-tip device	N. C.	18.00	12
7216033	Reflective devices	5.00	5.00	12
7216034	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
	DRIVE SYSTEM			
7216035	Handrim, smooth	N. C.	40.00	12
7216036	Handrim, plasticized	N. C.	40.00	12
7216037	Parking brake, push-type activation	N. C.	25.00	12
7216038	Parking brake, pull-type activation	N. C.	25.00	12
7216039	Brake lever extension, plug-in	5.00	5.00	12
7216040	Fork, adjustable height	N. C.	15.00	12
	WHEELS AND TIRES			
7216041	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	65.00	12
	61 cm (24 in.)			
7216042	Drive wheel, plastic; 30.5 cm (12 in.), 40.6 cm (16 in.),	N. C.	65.00	12
	50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7216043	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	20.00	1
	cm (22 in.) or 61 cm (24 in.); width of 2.9 cm (13/8 in.)			
7216044	Drive wheel tire, standard pressure inner tube; 30.5 cm	N. C.	20.00	1
	(12 in.), 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22			
	in.) or 61 cm (24 in.) width of 2.9 cm (13/8 in.)			
7216045	Caster wheel, with semi-pneumatic tire; 10.2 cm (4 in.),	N. C.	15.00	12
	12.7 cm (5 in.), 15.2 cm (6 in.) or 20.3 cm (8 in.)	_		
7216046	Drive wheel axle, fixed	N. C.	10.00	12
7216047	Drive wheel axle, quick release	N. C.	10.00	12
7216048	Spoke guards	20.00	20.00	12

PRICE			
(including all			
the basic			
components)			

			the basic			
			components)			
7216049	POSITIONING BASES		1,055.00			
	CATEGORY BPO-GM 2-A-P2 (RIGID FRAME)					
	ORTHOFAB INC.					
	"TANGO AC" DEVICE					
	TECHNICAL SPECIFICATIONS OF THE DEVICE					
	Maximum weight capacity: 136 kg (300 lb.)					
	Seat-to-floor height: 33 cm to 48.3 cm (13 in. to 19 in.)					
	Frame: back height from 45.7 cm to 61 cm (18 in. to 24 in.)					
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)		
	BODY SUPPORT SYSTEM					
7216050	Seat, rigid base, depth adjustable; strips of "hook" Velcro,	N. C.	40.00	60		
	2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.),					
	38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.),					
	45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.),					
	53.3 cm (21 in.) or 55.9 cm (22 in.);					
	depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm					
	(17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm					
	(20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)					
7216051	Back support, rigid plate	N. C.	200.00	60		
7216052	Back support, flexible, tension adjustable	N. C.	200.00	60		
7216054	Dynamic back support	110.00	110.00	60		
7216053	Reclining back support	210.00	210.00	60		
7216055	Back support upright, straight, angle and height	N. C.	75.00	60		
	adjustable; angle-adjustable from 90° to 120° by					
	maximum increments of 8°					
7216056	Push handle, with hand grip	N. C.	20.00	60		
7216057	Raised and adjustable push bar, with hand grip	130.00	150.00	60		
7216058	Power tilt mechanism controlled by the occupant	1,000.00	1,000.00	60		
7216059	Postural support pelvic belt	N. C.	10.00	60		
7216060	U-shaped arm support, short, removable; height-adjustable	N. C.	110.00	60		
	from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm					
	to 35.6 cm (10 in. to 14 in.) by maximum increments of					
	2.5 cm (1 in.), with locking mechanism; including					
7217071	clothing guard	NG	110.00	(0)		
7216061	U-shaped arm support, long, removable; height-adjustable from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm	N. C.	110.00	60		
	to 35.6 cm (10 in. to 14 in.) by maximum increments of					
	2.5 cm (10 in.), with locking mechanism; including					
501 (0.00	4 4 1	¥. ~	0.00			
7216062	Arm support pad, short, straight	N. C.	8.00	60		
7216063	Arm support pad, long, straight	N. C.	8.00	60		
7216064	Arm support pad, contoured	20.00	28.00	60		

7216065	Arm support pad, gel	72.00	80.00	60
7216066	Lower leg support, parallel, removable and swing-away;	N. C.	40.00	60
	adjustable length from 30.5 cm to 35.6 cm (12 in. To 14			
	in.), 35.6 cm to 48.3 cm (14 in. to 19 in.) or from 48.3 cm			
	to 53.3 cm (19 in. to 21 in.)			
7216069	Lower leg support, compensating elevating; with locking	N. C.	40.00	60
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7216072	Padded calf support, angle, height and depth adjustable,	100.00	100.00	60
/2100/2		100.00	100.00	00
7217070	including flat	15.00	15.00	60
7216070	Calf support strap, single		15.00	60
7216071	Calf support strap, double	30.00	30.00	60
7216073	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	standard lenght			
7216074	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	extra long			
7216075	Foot support, flip-up, full width, depth and angle	45.00	100.00	60
	adjustable			
7216076	Heel loop, adjustable	5.00	5.00	60
7216077	Head support, depth adjustable	20.00	20.00	60
7216078	Contoured cushion for head support, all sizes	30.00	30.00	60
7216079	Back support tension bar	50.00	50.00	60
7216080	Securement for head support for back support tension bar,	50.00	50.00	60
	height adjustable			
	FRAME			
7216081	Anti-tip device	N. C.	12.00	60
7216082	Reflective devices	50.00	50.00	60
7216083	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
7210003	becarement points for strup type treatowns for transport	14. 0.	14. 6.	00
	DRIVE SYSTEM			
7216084	Handrim, smooth	N. C.	80.00	60
7216084	Handrim, plasticized	N. C.	80.00	60
7216085		N. C. N. C.	30.00	60
	Parking brake, push-type activation			
7216087	Parking brake, pull-type activation	N. C.	30.00	60
7216088	Brake lever extension, telescopic	10.00	10.00	60
7216089	Fork, adjustable height	N. C.	10.00	60
	WHEELS AND TIRES			
7216090	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	30.00	60
7210090		N. C.	30.00	00
721 (001	61 cm (24 in.)	NC	20.00	(0
7216091	Drive wheel, plastic; 30.5 cm (12 in.)	N. C.	30.00	60
7216092	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	30.00	60
	cm (22 in.) or 61 cm (24 in); widths of 2.5 cm (1 in.) or			
	3.8 cm (1½ in.)		• • • •	
7216093	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	30.00	60
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.); widths of			
	$2.5 \text{ cm } (1 \text{ in.}) \text{ or } 3.8 \text{ cm } (1\frac{1}{2} \text{ in.})$			
7216094	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	40.00	60
	15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.); widths			
	of 2.5 cm (1 in.) or 3.8 cm (1½ in.)			
7216095	Drive wheel axle, fixed	N. C.	7.00	60
7216096	Drive wheel axle, quick release	N. C.	7.00	60
7216097	Spoke guards	70.00	70.00	60
	· -			

PRICE			
(including all			
the basic			
components)			

==1.6000			components)			
7216098	POSITIONING BASES		1,100.00			
	CATEGORY BPO-GM 2-A-P2 (RIGID FRAME)					
	SUNRISE MEDICAL CANADA INC.					
	"QUICKIE SR45" DEVICE					
	TECHNICAL SPECIFICATIONS OF THE DEVICE					
	Maximum weight capacity: 120 kg (265 lb.)					
	Seat-to-floor height: 35.6 cm to 52.2 cm (14 in. to 20½ in.)					
	Frame: back height from 38.1 cm to 63.5 cm (15 in. to 25 in.)					
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)		
	BODY SUPPORT SYSTEM					
7216099	Seat, rigid base, depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	75.00	12		
7216100	Back support, rigid plate	N. C.	150.00	1		
7216101	Back support, flexible, tension adjustable	35.00	185.00	1		
7216103	Dynamic back support	175.00	175.00	1		
7216102	Reclining back support	420.00	420.00	1		
7216104	Back support upright, straight, angle and height adjustable; angle-adjustable from 85° to 120° by maximum increments of 5°	N. C.	40.00	12		
7216105	Push handle, with hand grip	N. C.	N. C.	12		
7216106	Raised and adjustable push bar, with hand grip	95.00	95.00	12		
7216107	Power tilt mechanism controlled by the occupant	850.00	850.00	12		
7216108	Postural support pelvic belt	N. C.	25.00	12		
7216109	T-shaped arm support, short, removable; height-adjustable, from 18.4 cm to 40.1 cm (7½ in. to 15¾ in.) or U-type arm support, short, flip-up; height-adjustable, from 24.9 cm to 40.1 cm (9¾ in. to 15¾ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism;	N. C.	114.00	1		
7216110	T-shaped arm support, long, removable; height-adjustable, from 18.4 cm to 41.1 cm (7½ in. to 15¾ in.) or U-type arm support, long, flip-up; height-adjustable, from 24.9 cm to 40.1 cm (9¾ in. to 15¾ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including	N. C.	114.00	1		
7216111	Arm support pad, short, straight	N. C.	6.00	1		

7216112	Arm support pad, long, straight	N. C.	6.00	1
7216113	Arm support pad, contoured	9.00	15.00	1
7216114	Arm support pad, gel	14.00	20.00	1
7216115	Lower leg support, parallel, removable and swing-away;	N. C.	55.00	12
	adjustable length from 7.6 cm to 24.2 cm (3 in. to 9½ in.)			
	or from 22.9 cm to 48.3 cm (9 in. to 19 in.)			
7216118	Lower leg support, compensating elevating; with locking	55.00	110.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7216121	Padded calf support, angle, height and depth adjustable,	25.00	25.00	12
	including flat			
7216119	Calf support strap, single	15.00	15.00	12
7216120	Calf support strap, double	18.00	18.00	12
7216122	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	35.00	12
	standard lenght			
7216123	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	35.00	12
	extra long			
7216124	Foot support, flip-up, full width, depth and angle	N. C.	35.00	12
	adjustable			
7216125	Heel loop, adjustable	1.00	1.00	12
7216126	Head support, depth adjustable	55.00	55.00	12
7216127	Contoured cushion for head support, all sizes	35.00	35.00	12
7216128	Back support tension bar	35.00	35.00	12
7216129	Securement for head support for back support tension bar,	40.00	40.00	12
	height adjustable			
	FRAME			
7216130	Anti-tip device	N. C.	18.00	12
7216130	Reflective devices	5.00	5.00	12
7216131	Securement points for strap-type tiedowns for transport	N. C.	100.00	12
,210102	2000 mile in partie for the property of the control			
	DRIVE SYSTEM			
7216133	Handrim, smooth	N. C.	40.00	12
7216134	Handrim, plasticized	N. C.	40.00	12
7216135	Parking brake, push-type activation	N. C.	25.00	12
7216136	Parking brake, pull-type activation	N. C.	25.00	12
7216137	Brake lever extension, plug-in	5.00	5.00	12
7216138	Fork, adjustable height	N. C.	15.00	12
501 (100	WHEELS AND TIRES	N. G	65.00	10
7216139	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	65.00	12
7016140	61 cm (24 in.)	N. C	65.00	10
7216140	Drive wheel, plastic; 30.5 cm (12 in.), 40.6 cm (16 in.),	N. C.	65.00	12
7017141	50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C	20.00	1
7216141	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	20.00	1
7216142	cm (22 in.) or 61 cm (24 in.); width of 2.9 cm (13/8 in.)	N. C.	20.00	1
7216142	Drive wheel tire, standard pressure inner tube; 30.5 cm (12 in.), 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22	N. C.	20.00	1
	in.) or 61 cm (24 in.); width of 4.5 cm (13/4 in.)			
7216143	Caster wheel, with semi-pneumatic tire; 10.2 cm (4 in.),	N. C.	15.00	12
1210143	12.7 cm (5 in.), 15.2 cm (6 in.) or 20.3 cm (8 in.)	IV. C.	13.00	12
7216144	Drive wheel axle, fixed	N. C.	10.00	12
7216145	Drive wheel axle, nixed Drive wheel axle, quick release	N. C.	10.00	12
7216146	Spoke guards	20.00	20.00	12
	1 0	_ 5.00		12

PRICE
(including all
the basic
components)

		<i> </i>
7216147	POSITIONING BASES	1,108.00
	CATEGORY BPO-GM 2-B-P2 (RIGID FRAME)	

LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

"NEOX" DEVICE

TECHNICAL SPECIFICATIONS OF THE DEVICE

Maximum weight capacity: 120 kg (265 lb.)

Seat-to-floor height: 30.5 cm to 50.8 cm (12 in. to 20 in.) **Frame:** back height from 40.6 cm to 68.6 cm (16 in. to 27 in.)

	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
7216148	BODY SUPPORT SYSTEM Seat, rigid base, depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	115.00	12
7216149 7216150 7216152 7216151 7216153 7216154 7216155	Back support, rigid plate Back support, flexible, tension adjustable Dynamic back support Reclining back support Back support upright, straight, angle and height adjustable; angle-adjustable from 85° to 120° by maximum increments of 5° Push handle, with hand grip Raised and adjustable push bar, with hand grip	N. C. 26.00 241.50 462.00 N. C. N. C.	69.00 95.00 241.50 462.00 28.00	1 1 1 1 12
7216156 7216157 7216158	Power tilt mechanism controlled by the occupant Postural support pelvic belt T-shaped arm support, short, removable; height-adjustable from 17.2 cm to 26.7 cm (6¾ in. to 10½ in.), from 20.3 cm to 31.8 cm (8 in. to 12½ in.) or from 25.4 cm to 36.9 cm (10 in. to 14½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	750.00 N. C. N. C.	750.00 15.50 90.00	12 12 1
7216159	U-shaped arm support, long, flip-up or removable; height-adjustable from 17.2 cm to 24.2 cm (6¾ in. to 9½ in.), 21.6 cm to 33 cm (8½ in. to 13 in.) or from 30.5 cm to 41.9 cm (12 in. to 16½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1

7216160	Arm support pad, short, straight	N. C.	5.50	1
7216161	Arm support pad, long, straight	N. C.	5.50	1
7216162	Arm support pad, contoured	34.50	40.00	1
	** *			
7216163	Arm support pad, gel	50.50	56.00	1
7216164	Lower leg support, parallel, removable and swing-away;	N. C.	59.50	12
	adjustable length from 26.7 cm to 33 cm (10½ in. to 13			
	in.), from 30.5 cm to 43.2 cm (12 in. to 17 in.) or from			
	40.6 cm to 53.3 cm (16 in. to 21 in.)			
7216167	Lower leg support, compensating elevating; with locking	130.50	190.00	12
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7216170	Padded calf support, angle, height and depth adjustable,	60.50	60.50	12
/2101/0		00.50	00.50	12
	including flat or contoured pad			
7216168	Calf support strap, single	20.00	20.00	12
7216169	Calf support strap, double	20.00	20.00	12
7216171	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	50.00	12
	standard lenght			
7216172	Foot support, separate, flip-up, depth and angle adjustable,	15.00	65.00	12
/2101/2		13.00	03.00	12
	extra long			
7216173	Foot support, flip-up, full width, depth and angle	80.00	130.00	12
	adjustable			
7216174	Heel loop, adjustable	3.00	3.00	12
7216175	Head support, depth adjustable	80.00	80.00	12
		57.00		12
7216176	Contoured cushion for head support, all sizes		57.00	
7216177	Back support tension bar	30.00	30.00	12
7216178	Securement for head support for back support tension bar,	57.00	57.00	12
	height adjustable			
	FRAME			
7217170		N C	17.00	12
7216179	Anti-tip device	N. C.	17.00	12
7216180	Reflective devices	5.00	5.00	12
7216181	Securement points for strap-type tiedowns for transport	N. C.	5.00	12
	DRIVE SYSTEM			
7216182	Handrim, smooth	N. C.	16.00	12
7216183	Handrim, plasticized	18.00	34.00	12
7216184	Parking brake, push-type activation	N. C.	25.00	12
7216185	Parking brake, pull-type activation	N. C.	25.00	12
7216186	Brake lever extension, telescopic or fixed	10.00	10.00	12
7216187	Fork, adjustable height	N. C.	12.00	12
7210107	1 ork, adjustation neight	1	12.00	12
	WHEEL CAND TIDEC			
	WHEELS AND TIRES			
7216188	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	21.00	12
	61 cm (24 in.)			
7216189	Drive wheel, plastic; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	21.00	12
	61 cm (24 in.)			
7216100	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N C	24.50	1
7216190	- · · · · · · · · · · · · · · · · · · ·	N. C.	24.30	1
	cm (22 in.) or 61 cm (24 in.)			
7216191	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	24.50	1
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)			
7216192	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	11.25	12
0 1 / 2	15.2 cm (6 in.) or 20.3 cm (8 in.); widths of 3.8 cm		-	
7016100	(1½ in.)	N 0	<i>5</i> 00	10
7216193	Drive wheel axle, fixed	N. C.	5.00	12

7216194 7216195	Drive wheel axle, quick release Spoke guards	5.00 56.00	10.00 56.00	12 12
			PRICE (including all the basic components)	
7216196	POSITIONING BASES CATEGORY BPO-GM 2-C-P1 (RIGID FRAME)		1,150.00	
	LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.			
	"NEOX DYNAMIC" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 120 kg (265 lb.) Seat-to-floor height: 33 cm to 48.3 cm (13 in. to 19 in.) Frame: back height from 40.6 cm to 63.5 cm (16 in. to 25 in.)	n.)		
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
7216197	BODY SUPPORT SYSTEM Seat, rigid base, depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.); depths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in.)	N. C.	115.00	12
7216198 7216199 7216200 7216201	Back support, rigid plate Back support, flexible, tension adjustable Reclining back support Back support upright, straight, angle and height adjustable; angle-adjustable from 85° to 120° by	N. C. 26.00 462.00 N. C.	69.00 95.00 462.00 28.00	1 1 1 12
7216202	maximum increments of 5° Push handle, with hand grip	N. C.	17.50	12
7216203	Raised and adjustable push bar, with hand grip	47.50	65.00	12
7216204 7216205	Postural support pelvic belt T-shaped arm support, short, removable; height- adjustable, from 20.3 cm to 39.4 cm (8 in. to 15½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C. N. C.	15.50 90.00	12 1
7216206	U-shaped arm support, long, flip-up or removable; height-adjustable, from 17.2 cm to 41.9 cm (6¾ in. to 16½ in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	90.00	1
7216207 7216208 7216209	Arm support pad, short, straight Arm support pad, long, straight Arm support pad, contoured	N. C. N. C. 34.50	5.50 5.50 40.00	1 1 1

7216210	Arm support pad, gel	50.50	56.00	1
7216211	Lower leg support, parallel, removable and swing-away;	N. C.	59.50	12
	adjustable length from 26.7 cm to 53.3 cm (10½ in. to			
	21 in.)			
7216214	Lower leg support, compensating elevating; with locking	130.50	190.00	12
,21021.	mechanism; compatible with the same fastening system as	100.00	1,000	
	the fixed lower leg support or supplied with its fastening			
	- 11 11			
5016015	system	60.50	60.50	10
7216217	Padded calf support, angle, height and depth adjustable,	60.50	60.50	12
	including flat or contoured pad			
7216215	Calf support strap, single	20.00	20.00	12
7216216	Calf support strap, double	20.00	20.00	12
7216218	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	50.00	12
7210210	standard lenght	7 0.	20.00	12
7216219	Foot support, separate, flip-up, depth and angle adjustable,	15.00	65.00	12
/21021)	extra long	13.00	03.00	12
721 (220		90.00	120.00	12
7216220	Foot support, flip-up, full width, depth and angle	80.00	130.00	12
701 (001	adjustable	2.00	2.00	10
7216221	Heel loop, adjustable	3.00	3.00	12
7216222	Head support, depth adjustable	80.00	80.00	12
7216223	Contoured cushion for head support, all sizes	57.00	57.00	12
7216224	Back support tension bar	30.00	30.00	12
7216225	Securement for head support for back support tension bar,	57.00	57.00	12
	height adjustable			
	FRAME			
7216226	Anti-tip device	N. C.	17.00	12
7216227	Reflective devices	5.00	5.00	12
7216228	Securement points for strap-type tiedowns for transport	N. C.	5.00	12
7210220	seement permit for study type treat mile for transport	7 0.	2.00	
	DRIVE SYSTEM			
7216229	Handrim, smooth	N. C.	16.00	12
7216230	Handrim, plasticized	18.00	34.00	12
7216230	Parking brake, push-type activation	N. C.	25.00	12
7216232	Parking brake, pull-type activation	N. C.	25.00	12
7216233	Brake lever extension, telescopic or fixed	10.00	10.00	12
7216234	Fork, adjustable height	N. C.	12.00	12
	WHEELS AND TIRES			
7216235	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	21.00	12
	61 cm (24 in.)			
7216236	Drive wheel, plastic; 50.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	21.00	12
	61 cm (24 in.)			
7216237	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	24.50	1
	cm (22 in.) or 61 cm (24 in); width of 2.9 cm (13% in.)			
7216238	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	24.50	1
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in); width of 2.8 cm			
	(1½ in.)			
7216239	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	11.25	12
1210237	15.2 cm (6 in.) or 20.3 cm (8 in.); width of 3.8 cm (1½ in.)	11. C.	11.40	12
	13.2 cm (6 m.) of 20.3 cm (6 m.), widdi of 3.6 cm (1/2 m.)			
7216240	Drive wheel evile fived	N C	5.00	10
7216240	Drive wheel axle, fixed	N. C.	5.00	12
7216241	Drive wheel axle, quick release	5.00	10.00	12
7216242	Spoke guards	56.00	56.00	12

PRICE
(including all
the basic
components)

			the basic	
			components)	
7216243	POSITIONING BASES CATEGORY BPO-GM 3-A-P2 (RIGID FRAME)		1,055.00	
	ORTHOFAB INC.			
	"TANGO AC-03" DEVICE			
	TECHNICAL SPECIFICATIONS OF THE DEVICE			
	Maximum weight capacity: 136 kg (300 lb.)			
	Seat-to-floor height: 33 cm to 48.3 cm (13 in. to 19 in.)			
	Frame: back height from 45.7 cm to 61 cm (18 in. to 24 in.)		
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
	BODY SUPPORT SYSTEM			
7216244	Seat, rigid base, depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	40.00	60
7216245	Back support, rigid plate	N. C.	200.00	60
7216246	Back support, flexible, tension adjustable	N. C.	200.00	60
7216248	Dynamic back support	110.00	110.00	60
7216247	Reclining back support	210.00	210.00	60
7216249	Back support upright, straight, angle and height adjustable; angle-adjustable from 90° to 120° by maximum increments of 8°	N. C.	75.00	60
7216250	Push handle, with hand grip	N. C.	20.00	60
7216251	Raised and adjustable push bar, with hand grip	130.00	150.00	60
7216252	Power tilt mechanism controlled by the occupant	1,000.00	1,000.00	60
7216252	Postural support pelvic belt	N. C.	10.00	60
7216253	U-shaped arm support, short, flip-up or removable; height-	N. C.	110.00	60
7210234	adjustable from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N.C.	110.00	
7216255	U-shaped arm support, long, flip-up or removable; height-adjustable from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism; including clothing guard	N. C.	110.00	60
7216256	Arm support pad, short, straight	N. C.	8.00	60

7216257	Arm support pad, long, straight	N. C.	8.00	60
7216258	Arm support pad, contoured	20.00	28.00	60
7216259	Arm support pad, gel	72.00	80.00	60
7216260	Lower leg support, parallel, removable and swing-away;	N. C.	40.00	60
	adjustable length from 30.5 cm to 35.6 cm (12 in. to 14			
	in.), 35.6 cm to 48.3 cm (14 in. to 19 in.) or from 48.3 cm			
	to 53.3 cm (19 in. to 21 in.)			
	,			
7216263	Lower leg support, compensating elevating; with locking	N. C.	40.00	60
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7216266	Padded calf support, angle, height and depth adjustable,	100.00	100.00	60
	including flat pad			
7216264	Calf support strap, single	15.00	15.00	60
7216265	Calf support strap, double	30.00	30.00	60
7216267	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	standard lenght			
7216268	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	extra long			
7216269	Foot support, flip-up, full width, depth and angle	45.00	100.00	60
	adjustable	- 00	7 .00	
7216270	Heel loop, adjustable	5.00	5.00	60
7216271	Head support, depth adjustable	20.00	20.00	60
7216272	Contoured cushion for head support, all sizes	30.00	30.00	60
7216273	Back support tension bar	50.00	50.00	60
7216274	Securement for head support for back support tension bar,	50.00	50.00	60
	height adjustable			
	FRAME			
7216275	Anti-tip device	N. C.	12.00	60
7216276	Reflective devices	50.00	50.00	60
7216277	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
,,	71			
	DRIVE SYSTEM			
7216278	Handrim, smooth	N. C.	80.00	60
7216279	Handrim, plasticized	N. C.	80.00	60
7216280	Parking brake, push-type activation	N. C.	30.00	60
7216281	Parking brake, pull-type activation	N. C.	30.00	60
7216282	Brake lever extension, telescopic	10.00	10.00	60
7216283	Fork, adjustable height	N. C.	10.00	60
	WHEELS AND TIRES			
7216284	Drive wheel, spoked; 30.8 cm (20 in.), 55.9 cm (22 in.) or	N. C.	30.00	60
	61 cm (24 in.)			
7216285	Drive wheel, plastic; 30.5 cm (12 in.)	N. C.	30.00	60
7216286	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C.	30.00	60
	cm (22 in.) or 61 cm (24 in.); widths of 2.5 cm (1 in.) or			
501 (205	3.8 cm (1½ in.)	N. C	20.00	60
7216287	Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	30.00	60
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.); widths of			
701 (200	2.5 cm (1 in.) or 3.8 cm (1½ in.)	N. C	40.00	
7216288	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	40.00	60
	15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.); widths			
	of 2.5 cm (1 in.) or 3.8 cm ($1\frac{1}{2}$ in.)			

7216289 7216290 7216291	Drive wheel axle, fixed Drive wheel axle, quick release Spoke guards	N. C. N. C. 70.00	7.00 7.00 70.00	60 60 60
			PRICE (including all the basic components)	
7216292	POSITIONING BASES CATEGORY BPO-GM 3-B-P1 (RIGID FRAME)		1,285.00	
	ORTHOFAB INC.			
	"TANGO CE" DEVICE TECHNICAL SPECIFICATIONS OF THE DEVICE Maximum weight capacity: 159 kg (350 lb.) Seat-to-floor height: 35.6 cm to 50.8 cm (14 in. to 20 in.) Frame: back height from 40.6 cm to 61 cm (16 in. to 24 in.))		
	BASIC AND OPTIONAL COMPONENTS	Unit price of component during device purchase	Unit price for component replacement	Warranty (months)
7216293	BODY SUPPORT SYSTEM Seat, rigid base, depth adjustable; strips of "hook" Velcro, 2.5 cm (1 in.) wide or wider; widths of 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61 cm (24 in.); depths of 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	N. C.	40.00	60
7216294 7216295	Back support, rigid plate Back support, flexible, tension adjustable	N. C. N. C.	200.00 200.00	60 60
7216296 7216297	Reclining back support Back support upright, straight, angle and height adjustable; angle-adjustable from 90° to 120° by maximum increments of 8°	210.00 N. C.	210.00 75.00	60 60
7216298 7216299	Push handle, with hand grip Raised and adjustable push bar, with hand grip	N. C. 130.00	20.00 150.00	60 60
7216300 7216301	Postural support pelvic belt T-shaped arm support, short, removable; height-adjustable from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of	N. C. N. C.	10.00 110.00	60 60
7216302	2.5 cm (1 in.), with locking mechanism T-shaped arm support, long, removable; height-adjustable from 20.3 cm to 30.5 cm (8 in. to 12 in.) or from 25.4 cm to 35.6 cm (10 in. to 14 in.) by maximum increments of 2.5 cm (1 in.), with locking mechanism	N. C.	110.00	60
7216303 7216304	Arm support pad, short, straight Arm support pad, long, straight	N. C. N. C.	8.00 8.00	60 60
7216304	Arm support pad, contoured	20.00	28.00	60

7216306	Arm support pad, gel	72.00	80.00	60
7216307	Lower leg support, parallel, removable and swing-away;	N. C.	40.00	60
	adjustable length from 30.5 cm to 35.6 cm (12 in. to 14			
	in.), 35.6 cm to 48.3 cm (14 in. to 19 in.) or from 48.3 cm			
	to 53.3 cm (19 in. to 21 in.)			
7216310	Lower leg support, compensating elevating; with locking	N. C.	40.00	60
	mechanism; compatible with the same fastening system as			
	the fixed lower leg support or supplied with its fastening			
	system			
7216313	Padded calf support, angle, height and depth adjustable,	100.00	100.00	60
	including flat			
7216311	Calf support strap, single	15.00	15.00	60
7216312	Calf support strap, double	30.00	30.00	60
7216314	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	standard lenght			
7216315	Foot support, separate, flip-up, depth and angle adjustable,	N. C.	55.00	60
	extra long			
7216316	Foot support, flip-up, full width, depth and angle	45.00	100.00	60
	adjustable			
7216317	Heel loop, adjustable	5.00	5.00	60
7216318	Head support, depth adjustable	20.00	20.00	60
7216319	Contoured cushion for head support, all sizes	30.00	30.00	60
7216320	Back support tension bar	50.00	50.00	60
7216321	Securement for head support for back support tension bar,	50.00	50.00	60
	height adjustable			
	•			
	FRAME			
7216322	Anti-tip device	N. C.	12.00	60
7216323	Reflective devices	50.00	50.00	60
7216324	Securement points for strap-type tiedowns for transport	N. C.	N. C.	60
	DDIVE CVCTEM			
7216225	DRIVE SYSTEM	N. C	00.00	(0
7216325	Handrim, smooth	N. C.	80.00	60
7216326	Handrim, plasticized	N. C.	80.00	60
7216327	Parking brake, push-type activation	N. C.	30.00	60
7216328	Parking brake, pull-type activation	N. C.	30.00	60
7216329	Brake lever extension, telescopic	10.00	10.00	60
7216330	Fork, adjustable height	N. C.	10.00	60
	WHEEL CAND TIDEC			
7216331	WHEELS AND TIRES Drive wheel speked 50 8 cm (20 in) 55 0 cm (22 in) or	N. C.	30.00	60
/210331	Drive wheel, spoked; 50.8 cm (20 in.), 55.9 cm (22 in.) or 61 cm (24 in.)	N. C.	30.00	00
7216332	Drive wheel, plastic; 30.5 cm (12 in.)	N. C.	30.00	60
	Drive wheel tire, semi-pneumatic; 50.8 cm (20 in.), 55.9	N. C. N. C.	30.00	60
7216333	cm (22 in.) or 61 cm (24 in.); widths of 2.5 cm (1 in.) or	N. C.	30.00	00
7216224	3.8 cm (1½ in.) Drive wheel tire, standard pressure inner tube; 50.8 cm	N. C.	20.00	60
7216334	<u>*</u>	N. C.	30.00	60
	(20 in.), 55.9 cm (22 in.) or 61 cm (24 in.); widths of			
7216225	2.5 cm (1 in.) or 3.8 cm (1½ in.)	N. C	40.00	(0
7216335	Caster wheel, with semi-pneumatic tire; 12.7 cm (5 in.),	N. C.	40.00	60
	15.2 cm (6 in.), 17.8 cm (7 in.) or 20.3 cm (8 in.); widths			
701/00/	of 2.5 cm (1 in.) or 3.8 cm (1½ in.)	N. C	7.00	6 2
7216336	Drive wheel axle, fixed	N. C.	7.00	60
7216337	Drive wheel axle, quick release	N. C.	7.00	60
7216338	Spoke guards	70.00	70.00	60
7216339	Clothing guard	N. C.	N. C.	60

DIVISION V: STROLLERS AND ORTHOMOBILES

	DEVICE	Maximum price
	Buggy Major-type stroller, including footrests and harness	
4495602	less than three years of age *	660.00
4495610	three years of age and over	660.00
	Available Component(s)	
4495651	padded seat	96.00
4494993	other components	S. C.
4493862	thoracic support	96.00
4493870	chest pad	57.00

DURATION OF GUARANTEE: 12 months

	DEVICE	Maximum price
4495701	Other strollers*	S. C.
2192300	Orthomobiles	S. C.

PART II: POSTURE DEVICE

1111111111	Description	Maximum price
	DEVICE	priec
4565058	Positioning device * The price of the positioning device is equal to the total price of the positioning components.	*
	WARRANTY PERIOD: 3 months	
4490223 4490249 4499646	Standardized cushion, multilayer or injected foam Standardized cushion, viscoelastic foam and gel Standardized cushion, viscofluid foam and gel	400.00 400.00 400.00
4499869	Standardized cushion, static air-adjustable, single-compartment (by adjusting pressure or cell quantity)	500.00
4490215	Standardized cushion, static air-adjustable, multi- compartment (by adjusting pressure or cell quantity)	500.00
4499695	Standardized cushion, viscoelastic gel	500.00
4490231	Standardized cushion, viscofluid gel	500.00
4490256	Standardized cushion, foam with air insert	500.00
4490248	Standardized convoluted cushion, fusion-bonded thermoplastic polymer	500.00
4490272	Customized cushion, multilayer or injected foam	425.00
4490280	Customized cushion, viscoelastic foam and gel	425.00
4490298	Customized cushion, viscofluid foam and gel	425.00
4490306	Customized cushion, foam with air insert	525.00
4490307	Customized cushion, fusion-bonded thermoplastic polymer	600.00
4020510	Standard cover for specialized seat cushion	75.00
4020511	Commercial waterproof cover for specialized seat cushion	100.00
4020512	Surcharge payable for 2 commercial waterproof covers, provided with purchase or replacement of specialized seat cushion, as substitution for 2 standard covers	50.00
4020513	Waterproof cover for seat cushion (all sizes)	75.00
4020515	Surcharge payable for bariatric cushion, width of more than 50.8 cm (20 in.)	150.00
4565078	Adjustable pediatric posture seat for adaptable stroller, including positioning for torso, pelvis and lower limbs	1 200,00
4565069	Positioning components for head and neck, standardized or standardized modular components	350.00
4565060	Positioning components for torso, pelvis or both, standardized or standardized modular components, excluding seat cushion	450.00

4565070	Positioning belt specialized for pelvis, standardized	100.00
4565061 4565062	Positioning harness for torso, standardized Right upper limb positioning components, standardized or standardized modular components	100.00 170.00
4565063	Left upper limb positioning components, standardized or standardized modular components	170.00
4565064	Right lower limb positioning components, standardized or standardized modular components	200.00
4565066	Left lower limb positioning components, standardized or standardized modular components	200.00
4565067	Bilateral upper limb positioning components, standardized or standardized modular components	200.00
4565068	Bilateral lower limb positioning components, standardized or standardized modular components	200.00
4565071	Additional or replacement standard cover for specialized back	75.00
4565074	Additional or replacement waterproof cover for specialized back	100.00
4565072	Surcharge payable upon purchase or replacement of back or cover for complete or partial water proofing	50.00
4565075	Surcharge payable for a large positioning component for torso, pelvis or both, width or height of more than 50.8 cm (20 in.)	50.00
4565080	Surcharge payable for hardware allowing thoracic supports to swing away, flip back or fold	200.00
4499900	Head or neck components, moulded or customized	450.00
4499888	Torso positioning components, moulded or customized	500.00
4499889	Bilateral lower limb positioning components, moulded or customized	300.00
4499890	Torso and pelvic positioning component, one-piece, customized contouring	900.00
4499891	Pelvic positioning component, moulded or customized, excluding seat cushion	200.00
4499892 4499894	Torso positioning harness, customized Right upper limb positioning components, moulded or	100.00 270.00
4499895	customized Left upper limb positioning components, moulded or	270.00
4499896	customized Right lower limb positioning components, moulded or customized	300.00
4499897	Left lower limb positioning components, moulded or customized	300.00
4499899	Bilateral upper limb positioning components, moulded or customized	300.00

PART III: ELEMENTS INCLUDED IN THE PRICES OF THE DEVICES 1. The maximum or the fixed price for the purchase or replacement of an insured device referred to in Part I or II of this Title includes the

TITLE THREE: INSURED RELATED SERVICES PART I: PROSTHESES, ORTHOSES, AMBULATION AIDS OR STANDING AIDS

		Labour rate	Labour rate or lump sum	
		Laboratory (s.25)	Institution (s.25)	
Codes	Description			
5550001	Labour for the manufacture of a device with at least one component whose purchase or replacement price is stated as « S.C. » or for the repair of an orthosis, prosthesis, ambulation aid, standing aid or their components and supplements (rate per minute)	1.55	0.00	
4499976	Lump sum for recovery, safety check, cleaning, reallocation and inventory management of a walker with thorax support	111.79	0.00	
5442257	Lump sum for initial purchase or replacement of an ambulation aid provided as a complement to an orthosis or prosthesis	23.21	0.00	
5442258	Lump sum for initial purchase or replacement of an ambulation aid provided as a device to an adult	46.42	0.00	
5442259	Lump sum for initial purchase or replacement of an ambulation aid provided as a device to a person under 19 years of age	69.60	0.00	

Labour rate or lump sum

		Institution	
		(s.57)	
Codes	Description		
5550000	Labour for the manufacture or repair of a locomotor assist, positioning device or their components, including repairs made under supplier's warranty (rate per minute)	0.00	
4499968	Lump sum for the initial purchase or replacement of a manual wheel chair	0.00	
4499992	Lump sum for the initial purchase or replacement of a powered wheel chair	0.00	
5442260	Lump sum for initial purchase or replacement of a positioning base	0.00	
5442272	Non-listed lump sum for initial purchase or replacement of adapted stroller (S.C.)	0.00	
4495552	Lump sum for the initial purchase or replacement of a Buggy Major-type stroller	0.00	
4499596	Lump sum for the initial purchase or replacement of a propulsion assistance module	0.00	
4499950	Lump sum when a device must be adjusted to the growth of an insured person under age 19	0.00	
4499935	Lump sum for initial purchase or replacement of a manual wheelchair when the insured person dies before taking final receipt of device	0.00	
4499927	Lump sum for initial purchase or replacement of a powered wheelchair when the insured person dies before taking final receipt of device	0.00	
5442269	Lump sum for initial purchase or replacement of a positioning base when the insured person dies before taking final receipt of device	0.00	
4499943	Lump sum for initial purchase or replacement of a stroller when the insured person dies before taking final receipt of device	0.00	
5442254	Lump sum for specialized cushion seat positioning	0.00	
5442261	Lump sum for head or neck positioning	0.00	
5442262	Lump sum for positioning of torso, pelvis or both (excluding specialized seat cushion-related service)	0.00	
5442263	Lump sum for right upper limb positioning	0.00	

5442264	Lump sum for left upper limb positioning	0.00
5442265	Lump sum for right lower limb positioning	0.00
5442266	Lump sum for left lower limb positioning	0.00